



Maston - RUBBERcomp Synthetic rubber coating spray
Kumimaalispray
191210-199980

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: Maston - RUBBERcomp Synthetic rubber coating spray -
Kumimaalispray 191210-199980

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Paint

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Spray Shop Supplies Pty Ltd

38 Cyber Loop, Victoria, Australia

Tel: 61 3 9799 2007

Email: orders@sprayshopsupplies.com.au

Emergency number: 61 3 9799 2007 (from 8:00 am – 4:30 pm)

www.sprayshopsupplies.com.au

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) n° 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) n° 1272/2008.

Aerosol 1: Pressurised container: May burst if heated., H229

Aerosol 1: Flammable aerosols, Category 1, H222

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412

2.2 Label elements:

CLP Regulation (EC) n° 1272/2008:

Danger



Hazard statements:

Aerosol 1: H229 - Pressurised container: May burst if heated

Aerosol 1: H222 - Extremely flammable aerosol

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects **Precautionary**

statements: P102: Keep out of reach of children

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking P211: Do not spray on an open flame or other ignition source

P251: Do not pierce or burn, even after use

P260: Do not breathe dust/fume/gas/mist/vapours/spray

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F **Supplementary information:**

EUH066: Repeated exposure may cause skin dryness or cracking

2.3 Other hazards:

DK. Mal Code 3-1

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

- CONTINUED ON NEXT PAGE -
















**Maston - RUBBERcomp Synthetic rubber coating spray
 Kumimaalispray
 191210-199980**
3.1 Substance:

Non-applicable

3.2 Mixture:
Chemical description: Aerosol

Components:
SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

In accordance with Annex II of Regulation (EC) n°1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: 115-10-6 EC: 204-065-8 Index: 603-019-00-8 REACH:01-2119472128-37-XXXX	Dimethyl ether ATP CLP00		10 - <20 %
	Regulation 1272/2008	Flam. Gas 1: H220; Press. Gas: H280 - Danger 	
CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH:01-2119485493-29-XXXX	Butyl Acetate ATP CLP00		10 - <20 %
	Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336 - Warning  	
CAS: 64742-49-0 EC: 265-151-9 Index: 649-328-00-1 REACH:01-2119475133-43-XXXX	Naphtha (petroleum), hydrotreated light , < 0.1 % EC 200-753-7 ATP ATP01		10 - <20 %
	Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 2: H225 - Danger   	
CAS: 64742-48-9 EC: 265-150-3 Index: 649-327-00-6 REACH:01-2119486659-16-XXXX	Naphtha (petroleum), < 0.1 % EC 200-753-7 ATP ATP01		10 - <20 %
	Regulation 1272/2008	Asp. Tox. 1: H304; Flam. Liq. 3: H226 - Danger  	
CAS: 106-97-8 EC: 203-448-7 Index: 601-004-00-0 REACH:01-2119474691-32-XXXX	Butane ATP CLP00		10 - <20 %
	Regulation 1272/2008	Flam. Gas 1: H220; Press. Gas: H280 - Danger 	
CAS: 74-98-6 EC: 200-827-9 Index: 601-003-00-5 REACH:01-2119486944-21-XXXX	Propane ATP CLP00		5 - <10 %
	Regulation 1272/2008	Flam. Gas 1: H220; Press. Gas: H280 - Danger 	
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH:01-2119488216-32-XXXX	Xylene (mixture of isomers) ATP CLP00		5 - <10 %
	Regulation 1272/2008	Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning  	
CAS: 78-93-3 EC: 201-159-0 Index: 606-002-00-3 REACH:01-2119457290-43-XXXX	2-butanone ATP CLP00		5 - <10 %
	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336 - Danger  	
CAS: 108-65-6 EC: 203-603-9 Index: 607-195-00-7 REACH:01-2119475791-29-XXXX	2-methoxy-1-methylethyl acetate ATP ATP01		0,25 - <1 %
	Regulation 1272/2008	Flam. Liq. 3: H226 - Warning 	

To obtain more information on the risk of the substances consult sections 8, 11, 12, 15 and 16.

SECTION 4: FIRST AID MEASURES

- CONTINUED ON NEXT PAGE -



Maston - RUBBERcomp Synthetic rubber coating spray
Kumimaalispray
191210-199980

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product. **By inhalation:**

This product is not classified as hazardous through inhalation, however, it is recommended in case of intoxication symptoms to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection. **By eye contact:**

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product. **By ingestion/aspiration:**

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

SECTION 4: FIRST AID MEASURES (continued)

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed: Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂).

IT IS RECOMMENDED NOT to use tap water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment.

Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

- CONTINUED ON NEXT PAGE -



Maston - RUBBERcomp Synthetic rubber coating spray
Kumimaalispray
191210-199980

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inertization agent. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up: It is

recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections: See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling: A.-

Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Avoid projections and pulverizations. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

SECTION 7: HANDLING AND STORAGE (continued)

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C
Maximum Temp.: 50 °C
Maximum time: 36 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

- CONTINUED ON NEXT PAGE -



**Maston - RUBBERcomp Synthetic rubber coating spray
Kumimaalispray
191210-199980**

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the work environment

Identification	Environmental limits		
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	IOELV (8h)	50 ppm	275 mg/m ³
	IOELV (STEL)	100 ppm	550 mg/m ³
	Year	2015	
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	IOELV (8h)	1000 ppm	1920 mg/m ³
	IOELV (STEL)		
	Year	2015	
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	IOELV (8h)	50 ppm	221 mg/m ³
	IOELV (STEL)	100 ppm	442 mg/m ³
	Year	2015	
2-butanone CAS: 78-93-3 EC: 201-159-0	IOELV (8h)	200 ppm	600 mg/m ³
	IOELV (STEL)	300 ppm	900 mg/m ³
	Year	2015	

8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protection Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands Non-applicable

D.- Ocular and facial protection Non-applicable

E.- Bodily protection Non-applicable

F.- Additional emergency measures

It is not necessary to take additional emergency measures.

Environmental exposure controls:

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D **Volatile organic compounds:**

With regard to Directive 2010/75/EU, this product has the following characteristics:

- V.O.C. (Supply): 88.03 % weight
- V.O.C. density at 20 °C: 641.75 kg/m³ (641.75 g/L)
- Average carbon number: 7
- Average molecular weight: 109.33 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

- CONTINUED ON NEXT PAGE -



Maston - RUBBERcomp Synthetic rubber coating spray
Kumimaalispray
191210-199980

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet. **Appearance:**

Physical state at 20 °C: Aerosol
Appearance: Not available Color: Not available
Odor: Not available

Volatility:

Boiling point at atmospheric pressure: -1 °C (Propellant)
Vapour pressure at 20 °C: 359970 Pa
Vapour pressure at 50 °C: 359970 Pa (360 kPa)
Evaporation rate at 20 °C: Non-applicable *

Product description:

Density at 20 °C: 729 kg/m³
Relative density at 20 °C: 0.73
Dynamic viscosity at 20 °C: Non-applicable * Kinematic viscosity at 20 °C: Non-applicable *
Kinematic viscosity at 40 °C: Non-applicable *
Concentration: Non-applicable * pH: Non-applicable *
Vapour density at 20 °C: Non-applicable *
Partition coefficient n-octanol/water 20 °C: Non-applicable *
Solubility in water at 20 °C: Non-applicable * Solubility properties: Non-applicable * Decomposition temperature:
Non-applicable * Melting point/freezing point: Non-applicable *
Recipient pressure: 359970 Pa (3.6 bar)
Explosive properties: Non-applicable *
Oxidising properties: Non-applicable *
Flammability:
Flash Point: -60 °C (Propellant)
Autoignition temperature: 365 °C (Propellant)
Lower flammability limit: 0.8 % Volume
Upper flammability limit: 12 % Volume
*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

9.2 Other information:

Surface tension at 20 °C: Non-applicable *
Refraction index: Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

- CONTINUED ON NEXT PAGE -



Maston - RUBBERcomp Synthetic rubber coating spray
Kumimaalispray
191210-199980

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

10.5	Shock and friction	<input type="checkbox"/> Contact with air	Increase in temperature	Sunlight	Humidity
	Not applicable	<input type="checkbox"/> Not applicable	Risk of combustion	Avoid direct impact	Not applicable

Incompatible materials: _____

10.6 Haz	Acids	<input type="checkbox"/> Water	Combustive materials	Combustible materials	Others
	Avoid strong acids	<input type="checkbox"/> Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. With possibility of effects that are hazardous to the health, it is recommended not to breathe the vapours for long periods of time.

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure: A.- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, however it does contain substances classified as dangerous for this effect. For more information see section 3. B- Inhalation (acute effect):
- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3. C- Contact with the skin and the eyes (acute effect):
- Contact with the skin: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for skin contact. For more information see section 3.
- Contact with the eyes: Based on available data, the classification criteria are not met, however it does contain substances classified as dangerous for this effect. For more information see section 3.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- CONTINUED ON NEXT PAGE -



**Maston - RUBBERcomp Synthetic rubber coating spray
Kumimaalispray
191210-199980**

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3. E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
 - Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3. F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3. - Skin: Repeated exposure may cause skin dryness or cracking H- Aspiration hazard:

Based on available data, the classification criteria are not met, however it does contain substances classified as dangerous for this effect. For more information see section 3. **Other information:** Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
	Route	Dose	
Butyl Acetate CAS: 123-86-4 EC: 204-658-1	LD50 oral	12789 mg/kg	Rat
	LD50 dermal	14112 mg/kg	Rabbit
	LC50 inhalation	23.4 mg/L (4 h)	Rat
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg (ATEi)	Rat
	LC50 inhalation	11 mg/L (4 h) (ATEi)	
2-butanone CAS: 78-93-3 EC: 201-159-0	LD50 oral	4000 mg/kg	Rat
	LD50 dermal	6400 mg/kg	Rabbit
	LC50 inhalation	23.5 mg/L (4 h)	Rat
Naphtha (petroleum), hydrotreated light, < 0.1 % EC 200-753-7 CAS: 64742-49-0 EC: 265-151-9	LD50 oral	5100 mg/kg	Rat
	LD50 dermal	3160 mg/kg	Rabbit
	LC50 inhalation	12 mg/L (4 h)	Rat
Naphtha (petroleum), < 0.1 % EC 200-753-7 CAS: 64742-48-9 EC: 265-150-3	LD50 oral	15000 mg/kg	Rat
	LD50 dermal	3160 mg/kg	Rabbit
	LC50 inhalation	Non-applicable	
Butane CAS: 106-97-8 EC: 203-448-7	LD50 oral	Non-applicable	
	LD50 dermal	Non-applicable	
	LC50 inhalation	658 mg/L (4 h)	Rat
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	LD50 oral	Non-applicable	
	LD50 dermal	Non-applicable	
	LC50 inhalation	308.5 mg/L (4 h)	Rat
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	LD50 oral	8532 mg/kg	Rat
	LD50 dermal	5100 mg/kg	Rat
	LC50 inhalation	30 mg/L (4 h)	Rat

SECTION 12: ECOLOGICAL INFORMATION

- CONTINUED ON NEXT PAGE -



Safety data sheet
According to 1907/2006/EC (REACH), 453/2010/EU, 2015/830/EU

Maston - RUBBERcomp Synthetic rubber coating spray
Kumimaalispray
191210-199980

The experimental information related to the eco-toxicological properties of the product itself is not available

SECTION 12: ECOLOGICAL INFORMATION (continued)

- CONTINUED ON NEXT PAGE -



Maston - RUBBERcomp Synthetic rubber coating spray
Kumimaalispray
191210-199980

12.1 Toxicity:

Identification	Acute toxicity		Species	Genus
	LC50			
Butyl Acetate CAS: 123-86-4 EC: 204-658-1	LC50	62 mg/L (96 h)	Leuciscus idus	Fish
	EC50	73 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	675 mg/L (72 h)	Scenedesmus subspicatus	Algae
Naphtha (petroleum), hydrotreated light , < 0.1 % EC 200-753-7 CAS: 64742-49-0 EC: 265-151-9	LC50	Non-applicable		
	EC50	4.3 mg/L (96 h)	Crangon crangon	Crustacean
	EC50	Non-applicable		
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	LC50	13.5 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	0.6 mg/L (96 h)	Gammarus lacustris	Crustacean
	EC50	10 mg/L (72 h)	Skeletonema costatum	Algae
2-butanone CAS: 78-93-3 EC: 201-159-0	LC50	3220 mg/L (96 h)	Pimephales promelas	Fish
	EC50	5091 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	4300 mg/L (168 h)	Scenedesmus quadricauda	Algae
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	LC50	161 mg/L (96 h)	Pimephales promelas	Fish
	EC50	481 mg/L (48 h)	Daphnia sp.	Crustacean
	EC50	Non-applicable		

12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
Butyl Acetate CAS: 123-86-4 EC: 204-658-1	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	5 days
	BOD5/COD	0.79	% Biodegradable	84 %
2-butanone CAS: 78-93-3 EC: 201-159-0	BOD5	2.03 g O2/g	Concentration	Non-applicable
	COD	2.31 g O2/g	Period	20 days
	BOD5/COD	0.88	% Biodegradable	89 %
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	BOD5	Non-applicable	Concentration	785 mg/L
	COD	Non-applicable	Period	8 days
	BOD5/COD	Non-applicable	% Biodegradable	100 %

12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential	
Butyl Acetate CAS: 123-86-4 EC: 204-658-1	BCF	4
	Pow Log	1.78
	Potential	Low
Naphtha (petroleum), hydrotreated light , < 0.1 % EC 200-753-7 CAS: 64742-49-0 EC: 265-151-9	BCF	380
	Pow Log	3.7
	Potential	High
Butane CAS: 106-97-8 EC: 203-448-7	BCF	33
	Pow Log	2.89
	Potential	Moderate
Propane CAS: 74-98-6	BCF	13
	Pow Log	2.86

- CONTINUED ON NEXT PAGE -



Maston - RUBBERcomp Synthetic rubber coating spray
Kumimaalispray
191210-199980

EC: 200-827-9	Potential	Low
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	BCF	9
	Pow Log	2.77
	Potential	Low
2-butanone CAS: 78-93-3 EC: 201-159-0	BCF	3
	Pow Log	0.29
	Potential	Low
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	BCF	1
	Pow Log	0.43
	Potential	Low

12.4 Mobility in soil:

- CONTINUED ON NEXT PAGE -

**Maston - RUBBERcomp Synthetic rubber coating spray
Kumimaalispray
191210-199980**

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Absorption/desorption		Volatility		
			Henry		
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	Koc	Non-applicable	Henry		Non-applicable
	Conclusion	Non-applicable	Dry soil		Non-applicable
	Surface tension	1.136E-2 N/m (25 °C)	Moist soil		Non-applicable
Butyl Acetate CAS: 123-86-4 EC: 204-658-1	Koc	Non-applicable	Henry		Non-applicable
	Conclusion	Non-applicable	Dry soil		Non-applicable
	Surface tension	2.478E-2 N/m (25 °C)	Moist soil		Non-applicable
Butane CAS: 106-97-8 EC: 203-448-7	Koc	900	Henry		9.626E+4 Pa·m ³ /mol
	Conclusion	Low	Dry soil		Yes
	Surface tension	1.187E-2 N/m (25 °C)	Moist soil		Yes
Propane CAS: 74-98-6 EC: 200-827-9	Koc	460	Henry		7.164E+4 Pa·m ³ /mol
	Conclusion	Moderate	Dry soil		Yes
	Surface tension	7.02E-3 N/m (25 °C)	Moist soil		Yes
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	Koc	202	Henry		5.249E+2 Pa·m ³ /mol
	Conclusion	Moderate	Dry soil		Yes
	Surface tension	Non-applicable	Moist soil		Yes
2-butanone CAS: 78-93-3 EC: 201-159-0	Koc	30	Henry		5.765E+0 Pa·m ³ /mol
	Conclusion	Very High	Dry soil		Yes
	Surface tension	2.396E-2 N/m (25 °C)	Moist soil		Yes

12.5 Results of PBT and vPvB assessment: Non-applicable

12.6 Other adverse effects:
Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
16 05 04*	Gases in pressure containers (including halons) containing dangerous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue.

We do not recommended disposal down the drain. See paragraph 6.2. **Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) n°1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

- CONTINUED ON NEXT PAGE -

**Maston - RUBBERcomp Synthetic rubber coating spray
 Kumimaalispray
 191210-199980**

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land: With regard to ADR 2015 and RID 2015:

SECTION 14: TRANSPORT INFORMATION (continued)



14.1 UN number: UN1950
14.2 UN proper shipping name: AEROSOLS, flammable
14.3 Transport hazard class(es): 2
 Labels: 2.1
14.4 Packing group: N/A
14.5 Dangerous for the environment: No
14.6 Special precautions for user
 Special regulations: 190, 327, 344, 625
 Tunnel restriction code: D
 Physico-Chemical properties: see section 9
 Limited quantities: 1 L
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 37-14:



14.1 UN number: UN1950
14.2 UN proper shipping name: AEROSOLS, flammable
14.3 Transport hazard class(es): 2
 Labels: AEROSOLS, flammable
14.4 Packing group: 2
14.5 Dangerous for the environment: 2.1
14.6 Special precautions for user N/A
 Special regulations: No
 EmS Codes:
 Physico-Chemical properties: 63, 190, 277, 327, 344, 959
 Limited quantities: F-D, S-U see section 9
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: 1 L
 Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2015:



14.1 UN number: UN1950
14.2 UN proper shipping name: AEROSOLS, flammable
14.3 Transport hazard class(es): 2
 Labels: 2.1
14.4 Packing group: N/A
14.5 Dangerous for the environment: No
14.6 Special precautions for user
 Physico-Chemical properties: see section 9
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: Non-applicable

SECTION 15: REGULATORY INFORMATION

- CONTINUED ON NEXT PAGE -



**Maston - RUBBERcomp Synthetic rubber coating spray
Kumimaalispray
191210-199980**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) 1907/2006 (REACH): Non-applicable
Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable
Regulation (EC) 1005/2009, about substances that deplete the ozone layer: Non-applicable

SECTION 15: REGULATORY INFORMATION (continued)

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Non-applicable

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

Council Directive 75/324/EEC of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers

Commission Directive 94/1/EC of 6 January 1994 adapting some technicalities of Council Directive 75/324/EEC on the approximation of the laws of the relating Member States to aerosol dispensers

Commission Directive 2008/47/EC of 8 April 2008 amending, for the purposes of adapting to technical progress, Council Directive

75/324/EEC on the approximation of the laws of the Member States relating to aerosol dispensers

Commission Directive 2013/10/EU of 19 March 2013 amending Council Directive 75/324/EEC on the approximation of the laws of the Member States relating to aerosol dispensers in order to adapt its labelling provisions to Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

- CONTINUED ON NEXT PAGE -



Maston - RUBBERcomp Synthetic rubber coating spray
Kumimaalispray
191210-199980

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) N° 1907/2006 (Regulation (EU) N° 453/2010, Regulation (EC) N° 2015/830)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS:

- Added Content
Naphtha (petroleum), < 0.1 % EC 200-753-7 (64742-48-9) CLP

Regulation (EC) n° 1272/2008:

- Pictograms
- Hazard statements

Texts of the legislative phrases mentioned in section 2:

H412: Harmful to aquatic life with long lasting effects

H229: Pressurised container: May burst if heated

H222: Extremely flammable aerosol

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3 **CLP Regulation (EC) n° 1272/2008:**

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways

Eye Irrit. 2: H319 - Causes serious eye irritation

Flam. Gas 1: H220 - Extremely flammable gas

Flam. Liq. 2: H225 - Highly flammable liquid and vapour

Flam. Liq. 3: H226 - Flammable liquid and vapour

Press. Gas: H280 - Contains gas under pressure, may explode if heated

Skin Irrit. 2: H315 - Causes skin irritation

STOT SE 3: H336 - May cause drowsiness or dizziness **Classification**

procedure:

Aquatic Chronic 3: Calculation method

Aerosol 1: Calculation method

Aerosol 1: Calculation method



Maston - RUBBERcomp Synthetic rubber coating spray
Kumimaalispray
191210-199980

SECTION 16: OTHER INFORMATION (continued)

Advice related to training:

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. **Principal bibliographical**

sources:

<http://esis.jrc.ec.europa.eu>
<http://echa.europa.eu> <http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5-day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
CL50: Lethal Concentration 50
EC50: Effective concentration 50
Log-POW: Octanol–water partition coefficient
Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -