

TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

FADE OUT THINNER

PRODUCT DESCRIPTION

Fade-out thinner for spot repairs on 2-component clear acrylic lacquer surfaces. Eliminates dust on the surface under repair, while also minimizing visible differences between older and newer coats of clear coat.

Guarantees quick and easy shading, even when used with HS and VHS lacquers.

- ✓ Quick-drying.
- ✓ Smooths rough surfaces.
- ✓ Shades non-matte surfaces.
- ✓ Retains gloss finish even under high temperatures (to 60°C).
- ✓ Easy to use.

Color - Transparent

APPLICATION

Can be used with MASTER and INTER TROTON Clear Coats.
Especially recommended for HS and VHS products.

Directions:

- 1/Apply 1÷3 thin layers of Fade-Out Thinner where old coats meet with new clear coat.
- 2/Apply immediately after applying last coat of clear coat.

This card presents the procedure of coats fading out.

Spraying Viscosity:

Product is ready for use, about 10s., DIN 4/20⁰C.

GENERAL NOTES

Thinners are indispensable here they complete the lacquer and primer lines. They are used for thinning so that proper spraying viscosity of these products can be achieved.

Caution: *To maintain safety, always follow the instructions given in the MSDS for the products.*

STORAGE

Store the product components in a sealed container, in dry and cool places, away from fire and heat sources, as well as direct sunlight.

Note: *After each use the container with product shall be immediately closed!*

WARRANTY PERIOD

Fade Out Thinner - 12 months from the date of Manufacture.

Important Information:

The information contained in this document corresponds to our present knowledge and is a guide to our products and their uses.

Read all directions and warnings prior to using Troton products - Safety Data Sheets can be found online at www.troton.com.pl or will be sent according to your request: troton@troton.com.pl

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that Troton believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Many factors beyond Troton's control and uniquely within user's knowledge and control can affect the use and performance of a Troton product in a particular application. Given the variety of factors that can affect the use and performance of a Troton product, user is solely responsible for evaluating the Troton product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Limitation of Liability: Except where prohibited by law, Troton will not be liable for any loss or damage arising from the Troton product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

If used as instructed, this product is designed to comply with the European Volatile Organic Compound (VOC) Emission Standard for Automotive Refinish Coatings. Confirm compliance with your country, state and local air quality rules before use. The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Troton assumes no obligation or liability for use of this information.