

TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

MASTER SPRAY STRUCTURE PAINT FOR PLASTIC



PRODUCT DESCRIPTION

Structure spray for plastic is designed to restore the structure of damaged external elements (e.g. mirrors, door-frame etc.) and internal elements (e.g. dashboard, door panels etc.). Perfect for spot repairs.

PHISICAL AND CHEMICAL PROPERTIES

- Color: black, grey
- Glass grade: mat
- Capacity: 500 ml.
- Efficiency: 1,5 m² (depending on the consistency and color of the substrate)
- Density: 0,792 g/cm³ (in temp. 20⁰C)
- Temperature resistance: to 80⁰C

Drying time (in temp. 20⁰C)*:

- Dust dry: after approx. 10 minutes
- Tack free: after approx. 30 minutes

*Drying time depends on air temperature, humidity and thickness of the layer.

CONTENT OF VOLATILE MATTER

VOC = 639 [g/l]

This product satisfies requirements of the European Union Directive (2004/42/WE), which for this product category (B/5) gives the limit value of content of volatile matter at the level of 840 [g/l] of the ready-for-use product.

USAGE

- Clear the surface carefully, dry and degrease.
- Shake before using for 2 – 3 minutes and try it on cardboard.
- Structure is dependent on the number of coats and the spraying distance.
- Apply several thin coats to get desired texture.
- **Clean the spray nozzle after use!** – Hold the can with the valve pointing downward, press the button emptying the content for about 5 seconds.

Caution: For safety reasons always comply with information provided in the Material Safety Data Sheet.

STORAGE

Store the product in sealed container, in dry and cool places, away from heat sources, as well as direct sunlight.

WARRANTY PERIOD

5 years from production date.

Important Information:

The information contained in this document corresponds to our present knowledge and is a guide to our products and their uses.

Read all directions and warnings prior to using Troton products - Safety Data Sheets can be found online at www.troton.com.pl or will be sent according to your request: troton@troton.com.pl

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that Troton believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Many factors beyond Troton's control and uniquely within user's knowledge and control can affect the use and performance of a Troton product in a particular application. Given the variety of factors that can affect the use and performance of a Troton product, user is solely responsible for evaluating the Troton product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Limitation of Liability: Except where prohibited by law, Troton will not be liable for any loss or damage arising from the Troton product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability. If used as instructed, this product is designed to comply with the European Volatile Organic Compound (VOC) Emission Standard for Automotive Refinish Coatings. Confirm compliance with your country, state and local air quality rules before use. The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Troton assumes no obligation or liability for use of this information.

TROTON Sp. z o.o.
Ząbrowo, Poland