



Safety data
sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: CAR-REP - Anti-Rust Primer
CR01015, CR01016, CR01017, CR01018 **Other**

means of identification:

Tuotenumero/Produkt numbers:
CR01015, CR01016, CR01017, CR01018

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Paint

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Spray Shop Supplies Pty Ltd
38 Cyber Loop, Dandenong South,
Victoria, 3175, Australia
Phone: +61 03 9799 2007
orders@sprayshopaupplies.com.au
www.sprayshopsupplies.com.au

1.4 Emergency telephone number: +61 03 9799 2007
(8:00am – 4:30pm)

SECTION 2: HAZARDS IDENTIFICATION **

- CONTINUED ON NEXT PAGE



CAR-REP - Anti-Rust

Primer

SECTION 2: HAZARDS IDENTIFICATION ** (continued)

2.3 Other hazards:

CR01018

Product fails to meet PBT/vPvB criteria
Endocrine-disrupting properties: The product fails to meet the criteria.
DK MAL code 4-1

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aerosol 1: Pressurised container: May burst if heated., H229

Aerosol 1: Flammable aerosols, Category 1, H222

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412 Eye Irrit. 2: Eye irritation, Category 2, H319

STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger



Hazard statements:

Aerosol 1: H229 - Pressurised container: May burst if heated.

Aerosol 1: H222 - Extremely flammable aerosol.

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Eye Irrit. 2: H319 - Causes serious eye irritation.

STOT SE 3: H336 - May cause drowsiness or dizziness. **Precautionary**

statements: P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P260: Do not breathe spray.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F **Supplementary information:**

EUH066: Repeated exposure may cause skin dryness or cracking.

EUH211: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. **Substances that contribute to the classification**

acetone (CAS: 67-64-1); N-butyl acetate (CAS: 123-86-4); Butanone (CAS: 78-93-3); Butan-2-ol (CAS: 78-92-2)

UFI: GX50-D045-S005-GCG7

** Changes with regards to the previous version

** Changes with regards to the previous version

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **

- CONTINUED ON NEXT PAGE



Safety data
sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Aerosol

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 67-64-1 EC: 200-662-2 Index: 606-001-00-8 REACH: 01-2119471330-49XXXX	acetone ¹	ATP CLP00
	Regulation 1272/2008 Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32XXXX	Xylene ¹	ATP CLP00
	Regulation 1272/2008 Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning	
CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH: 01-2119485493-29XXXX	N-butyl acetate ¹	ATP CLP00
	Regulation 1272/2008 Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning	
CAS: 78-93-3 EC: 201-159-0 Index: 606-002-00-3 REACH: 01-2119457290-43XXXX	Butanone ¹	ATP CLP00
	Regulation 1272/2008 Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	
CAS: 78-92-2 EC: 201-158-5 Index: 603-004-01-3 REACH: 01-2119475146-36XXXX	Butan-2-ol ¹	ATP CLP00
	Regulation 1272/2008 Eye Irrit. 2: H319; Flam. Liq. 3: H226; STOT SE 3: H335; STOT SE 3: H336 - Warning	
CAS: 108-65-6 EC: 203-603-9 Index: 607-195-00-7 REACH: 01-2119475791-29XXXX	2-methoxy-1-methylethyl acetate ²	ATP ATP01
	Regulation 1272/2008 Flam. Liq. 3: H226 - Warning	
CAS: 13463-67-7 EC: 236-675-5 Index: 022-006-00-2 REACH: 01-2119489379-17XXXX	Titanium dioxide (aerodynamic diameter ≤ 10 µm) ¹	ATP ATP14
	Regulation 1272/2008 Carc. 2: H351 - Warning	
CAS: Non-applicable EC: 905-588-0 Index: Non-applicable REACH: 01-2119539452-40XXXX	Reaction mass of ethylbenzene and xylene ²	Self-classified
	Regulation 1272/2008 Acute Tox. 4: H312+H332; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	
CAS: 108-65-6 EC: 203-603-9 Index: 607-195-00-7 REACH: 01-2119475791-29XXXX	2-methoxy-1-methylethyl acetate ²	Self-classified
	Regulation 1272/2008 Flam. Liq. 3: H226; STOT SE 3: H336 - Warning	



¹ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878 ²
Substance with a Union workplace exposure limit

** Changes with regards to the previous
version

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS ** (continued)

- CONTINUED ON NEXT PAGE

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

Identification	Chemical name/Classification		Concentration
CAS: 1314-13-2 EC: 215-222-5 Index: 030-013-00-7 REACH: 01-2119463881-32XXXX	zinc oxide ¹	ATP CLP00 Aquatic Acute 1: H400; Aquatic Chronic 1: H410 - Warning	0,25 - <1 %
	Regulation 1272/2008		
CAS: 100-41-4 EC: 202-849-4 Index: 601-023-00-4 REACH: 01-2119489370-35XXXX	Ethylbenzene ²	Self-classified Acute Tox. 4: H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger	0,1 - <0,15 %
	Regulation 1272/2008		
CAS: 95-63-6 EC: 202-436-9 Index: 601-043-00-3 REACH: 01-2119472135-42XXXX	1,2,4-trimethylbenzene ²	ATP CLP00 Acute Tox. 4: H332; Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H335 - Warning	0,05 - <0,1 %
	Regulation 1272/2008		
CAS: 100-41-4 EC: 202-849-4 Index: 601-023-00-4 REACH: 01-2119489370-35XXXX	Ethylbenzene ²	ATP ATP06 Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger	0,05 - <0,1 %
	Regulation 1272/2008		
CAS: 108-90-7 EC: 203-628-5 Index: 602-033-00-1 REACH: 01-2119432722-45XXXX	Chlorobenzene ²	ATP ATP09 Acute Tox. 4: H332; Aquatic Chronic 2: H411; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning	0,015 - <0,05 %
	Regulation 1272/2008		
CAS: 108-67-8 EC: 203-604-4 Index: 601-025-00-5 REACH: 01-2120738996-34XXXX	Mesitylene ²	ATP CLP00 Aquatic Chronic 2: H411; Flam. Liq. 3: H226; STOT SE 3: H335 - Warning	<0,015 %
	Regulation 1272/2008		
CAS: 98-82-8 EC: 202-704-5 Index: 601-024-00-X REACH: 01-2119473983-24XXXX	Cumene ²	ATP ATP18 Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Carc. 1B: H350; Flam. Liq. 3: H226; STOT SE 3: H335 - Danger	<0,015 %
	Regulation 1272/2008		
CAS: 108-88-3 EC: 203-625-9 Index: 601-021-00-3 REACH: 01-2119471310-51XXXX	Toluene ²	ATP CLP00 Asp. Tox. 1: H304; Flam. Liq. 2: H225; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H336 - Danger	<0,015 %
	Regulation 1272/2008		
CAS: 71-43-2 EC: 200-753-7 Index: 601-020-00-8 REACH: 01-2119496063-37XXXX	Benzene ²	ATP CLP00 Asp. Tox. 1: H304; Carc. 1A: H350; Eye Irrit. 2: H319; Flam. Liq. 2: H225; Muta. 1B: H340; Skin Irrit. 2: H315; STOT RE 1: H372 - Danger	<0,015 %
	Regulation 1272/2008		
CAS: 107-21-1 EC: 203-473-3 Index: 603-027-00-1 REACH: 01-2119456816-28XXXX	Ethanediol ²	ATP CLP00 Acute Tox. 4: H302 - Warning	<0,015 %
	Regulation 1272/2008		

¹ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878 ²
Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identification	Specific concentration limit
Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0	% (w/w) >=10: STOT RE 2 - H373
Mesitylene CAS: 108-67-8 EC: 203-604-4	% (w/w) >=25: STOT SE 3 - H335

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE



Safety data
sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product. **By inhalation:**

SECTION 4: FIRST AID MEASURES (continued)

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance. **By skin contact:**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection. **By eye contact:**

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed: Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC. **Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

- CONTINUED ON NEXT PAGE



**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8).

Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground. **For emergency responders:**

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up: It is

recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections: See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling: A.-

General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 50 °C

Maximum time: 60 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

- CONTINUED ON NEXT PAGE



Safety data
sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
	IOELV (8h)		
Xylene CAS: 1330-20-7 EC: 215-535-7	IOELV (8h)	50 ppm	221 mg/m ³
	IOELV (STEL)	100 ppm	442 mg/m ³
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	IOELV (8h)	50 ppm	241 mg/m ³
	IOELV (STEL)	150 ppm	723 mg/m ³
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	IOELV (8h)	100 ppm	442 mg/m ³
	IOELV (STEL)	200 ppm	884 mg/m ³
1,2,4-trimethylbenzene CAS: 95-63-6 EC: 202-436-9	IOELV (8h)	20 ppm	100 mg/m ³
	IOELV (STEL)		
Mesitylene	IOELV (8h)	20 ppm	100 mg/m ³

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

- CONTINUED ON NEXT PAGE



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification		Occupational exposure limits	
CAS: 108-67-8	EC: 203-604-4	IOELV (STEL)	
Cumene		IOELV (8h)	10 ppm / 50 mg/m ³
CAS: 98-82-8	EC: 202-704-5	IOELV (STEL)	50 ppm / 250 mg/m ³
Toluene		IOELV (8h)	50 ppm / 192 mg/m ³
CAS: 108-88-3	EC: 203-625-9	IOELV (STEL)	100 ppm / 384 mg/m ³
Benzene		IOELV (8h)	1 ppm / 3,25 mg/m ³
CAS: 71-43-2	EC: 200-753-7	IOELV (STEL)	
Ethanediol		IOELV (8h)	20 ppm / 52 mg/m ³
CAS: 107-21-1	EC: 203-473-3	IOELV (STEL)	40 ppm / 104 mg/m ³
2-methoxy-1-methylethyl acetate		IOELV (8h)	50 ppm / 275 mg/m ³
CAS: 108-65-6	EC: 203-603-9	IOELV (STEL)	100 ppm / 550 mg/m ³
Butanone		IOELV (8h)	200 ppm / 600 mg/m ³
CAS: 78-93-3	EC: 201-159-0	IOELV (STEL)	300 ppm / 900 mg/m ³
acetone		IOELV (8h)	500 ppm / 1210 mg/m ³
CAS: 67-64-1	EC: 200-662-2	IOELV (STEL)	
Ethylbenzene		IOELV (8h)	100 ppm / 442 mg/m ³
CAS: 100-41-4	EC: 202-849-4	IOELV (STEL)	200 ppm / 884 mg/m ³
Chlorobenzene		IOELV (8h)	5 ppm / 23 mg/m ³
CAS: 108-90-7	EC: 203-628-5	IOELV (STEL)	15 ppm / 70 mg/m ³
Reaction mass of ethylbenzene and xylene		IOELV (8h)	50 ppm / 221 mg/m ³
CAS: Non-applicable	EC: 905-588-0	IOELV (STEL)	100 ppm / 442 mg/m ³
2-methoxy-1-methylethyl acetate		IOELV (8h)	50 ppm / 275 mg/m ³
CAS: 108-65-6	EC: 203-603-9	IOELV (STEL)	100 ppm / 550 mg/m ³

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
acetone CAS: 67-64-1 EC: 200-662-2	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	186 mg/kg	Non-applicable
	Inhalation	Non-applicable	2420 mg/m ³	1210 mg/m ³	Non-applicable
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	212 mg/kg	Non-applicable
	Inhalation	442 mg/m ³	442 mg/m ³	221 mg/m ³	221 mg/m ³
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	11 mg/kg	Non-applicable	11 mg/kg	Non-applicable
	Inhalation	600 mg/m ³	600 mg/m ³	300 mg/m ³	300 mg/m ³
Butanone CAS: 78-93-3 EC: 201-159-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	1161 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	600 mg/m ³	Non-applicable
Butan-2-ol CAS: 78-92-2 EC: 201-158-5	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	405 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	600 mg/m ³	Non-applicable

- CONTINUED ON NEXT PAGE



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	796 mg/kg	Non-applicable
	Inhalation	Non-applicable	550 mg/m ³	275 mg/m ³	Non-applicable
Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	212 mg/kg	Non-applicable
	Inhalation	442 mg/m ³	442 mg/m ³	221 mg/m ³	221 mg/m ³
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	796 mg/kg	Non-applicable
	Inhalation	Non-applicable	550 mg/m ³	275 mg/m ³	Non-applicable
zinc oxide CAS: 1314-13-2 EC: 215-222-5	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	5 mg/m ³	0,5 mg/m ³

- CONTINUED ON NEXT PAGE



Safety data
sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

- CONTINUED ON NEXT PAGE

-



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
	Inhalation	Non-applicable	293 mg/m ³	77 mg/m ³	Non-applicable
1,2,4-trimethylbenzene CAS: 95-63-6 EC: 202-436-9	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	16171 mg/kg	Non-applicable
	Inhalation	100 mg/m ³	100 mg/m ³	100 mg/m ³	100 mg/m ³
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
	Inhalation	Non-applicable	293 mg/m ³	77 mg/m ³	Non-applicable
Chlorobenzene CAS: 108-90-7 EC: 203-628-5	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	15 mg/kg	Non-applicable	5 mg/kg	Non-applicable
	Inhalation	70 mg/m ³	Non-applicable	23 mg/m ³	Non-applicable
Mesitylene CAS: 108-67-8 EC: 203-604-4	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	16171 mg/kg	Non-applicable
	Inhalation	100 mg/m ³	100 mg/m ³	100 mg/m ³	100 mg/m ³
Cumene CAS: 98-82-8 EC: 202-704-5	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	15,4 mg/kg	Non-applicable
	Inhalation	Non-applicable	250 mg/m ³	100 mg/m ³	Non-applicable
Toluene CAS: 108-88-3 EC: 203-625-9	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	384 mg/kg	Non-applicable
	Inhalation	384 mg/m ³	384 mg/m ³	192 mg/m ³	192 mg/m ³
Ethandiol CAS: 107-21-1 EC: 203-473-3	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	106 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	35 mg/m ³

DNEL (General population):

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
acetone CAS: 67-64-1 EC: 200-662-2	Oral	Non-applicable	Non-applicable	62 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	62 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	200 mg/m ³	Non-applicable
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	125 mg/kg	Non-applicable
	Inhalation	260 mg/m ³	260 mg/m ³	65,3 mg/m ³	65,3 mg/m ³
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	2 mg/kg	Non-applicable	2 mg/kg	Non-applicable
	Dermal	6 mg/kg	Non-applicable	6 mg/kg	Non-applicable
	Inhalation	300 mg/m ³	300 mg/m ³	35,7 mg/m ³	35,7 mg/m ³
Butanone CAS: 78-93-3 EC: 201-159-0	Oral	Non-applicable	Non-applicable	31 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	412 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	106 mg/m ³	Non-applicable
Butan-2-ol	Oral	Non-applicable	Non-applicable	15 mg/kg	Non-applicable

- CONTINUED ON NEXT PAGE



Safety data
sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

CAS: 78-92-2 EC: 201-158-5	Dermal	Non-applicable	Non-applicable	203 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	213 mg/m ³	Non-applicable
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Oral	Non-applicable	Non-applicable	36 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	320 mg/kg	Non-applicable
Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0	Inhalation	Non-applicable	Non-applicable	33 mg/m ³	33 mg/m ³
	Oral	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Dermal	Non-applicable	Non-applicable	125 mg/kg	Non-applicable
	Inhalation	260 mg/m ³	260 mg/m ³	65,3 mg/m ³	65,3 mg/m ³
	Oral	Non-applicable	Non-applicable	36 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	320 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	33 mg/m ³	33 mg/m ³

- CONTINUED ON NEXT PAGE



Safety data
sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

- CONTINUED ON NEXT PAGE

-



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
zinc oxide CAS: 1314-13-2 EC: 215-222-5	Oral	Non-applicable	Non-applicable	0,83 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	2,5 mg/m ³	Non-applicable
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	15 mg/m ³	Non-applicable
1,2,4-trimethylbenzene CAS: 95-63-6 EC: 202-436-9	Oral	Non-applicable	Non-applicable	15 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	9512 mg/kg	Non-applicable
	Inhalation	29,4 mg/m ³	29,4 mg/m ³	29,4 mg/m ³	29,4 mg/m ³
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	15 mg/m ³	Non-applicable
Chlorobenzene CAS: 108-90-7 EC: 203-628-5	Oral	3 mg/kg	Non-applicable	3 mg/kg	Non-applicable
	Dermal	3 mg/kg	Non-applicable	3 mg/kg	Non-applicable
	Inhalation	1 mg/m ³	Non-applicable	1 mg/m ³	Non-applicable
Mesitylene CAS: 108-67-8 EC: 203-604-4	Oral	Non-applicable	Non-applicable	15 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	9512 mg/kg	Non-applicable
	Inhalation	29,4 mg/m ³	29,4 mg/m ³	29,4 mg/m ³	29,4 mg/m ³
Cumene CAS: 98-82-8 EC: 202-704-5	Oral	Non-applicable	Non-applicable	5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	1,2 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	16,6 mg/m ³	Non-applicable
Toluene CAS: 108-88-3 EC: 203-625-9	Oral	Non-applicable	Non-applicable	8,13 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	226 mg/kg	Non-applicable
	Inhalation	226 mg/m ³	226 mg/m ³	56,5 mg/m ³	56,5 mg/m ³
Ethanediol CAS: 107-21-1 EC: 203-473-3	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	53 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	7 mg/m ³

PNEC:

Identification				
acetone CAS: 67-64-1 EC: 200-662-2	STP	100 mg/L	Fresh water	10,6 mg/L
	Soil	29,5 mg/kg	Marine water	1,06 mg/L
	Intermittent	21 mg/L	Sediment (Fresh water)	30,4 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	3,04 mg/kg
Xylene CAS: 1330-20-7 EC: 215-535-7	STP	6,58 mg/L	Fresh water	0,327 mg/L
	Soil	2,31 mg/kg	Marine water	0,327 mg/L
	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	STP	35,6 mg/L	Fresh water	0,18 mg/L
	Soil	0,09 mg/kg	Marine water	0,018 mg/L
	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981 mg/kg

- CONTINUED ON NEXT PAGE



Safety data
sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

	Oral	Non-applicable	Sediment (Marine water)	0,098 mg/kg
Butanone CAS: 78-93-3 EC: 201-159-0	STP	709 mg/L	Fresh water	55,8 mg/L
	Soil	22,5 mg/kg	Marine water	55,8 mg/L
	Intermittent	55,8 mg/L	Sediment (Fresh water)	284,74 mg/kg
	Oral	1 g/kg	Sediment (Marine water)	284,7 mg/kg
Butan-2-ol CAS: 78-92-2 EC: 201-158-5	STP	761 mg/L	Fresh water	47,1 mg/L
	Soil	11,58 mg/kg	Marine water	47,1 mg/L
	Intermittent	47,1 mg/L	Sediment (Fresh water)	196,19 mg/kg
	Oral	1 g/kg	Sediment (Marine water)	196,19 mg/kg

- CONTINUED ON NEXT PAGE



Safety data
sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

- CONTINUED ON NEXT PAGE

-



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

Identification				
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	STP	100 mg/L	Fresh water	0,635 mg/L
	Soil	0,29 mg/kg	Marine water	0,064 mg/L
	Intermittent	6,35 mg/L	Sediment (Fresh water)	3,29 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,329 mg/kg
Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0	STP	6,58 mg/L	Fresh water	0,327 mg/L
	Soil	2,31 mg/kg	Marine water	0,327 mg/L
	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	STP	100 mg/L	Fresh water	0,635 mg/L
	Soil	0,29 mg/kg	Marine water	0,064 mg/L
	Intermittent	6,35 mg/L	Sediment (Fresh water)	3,29 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,329 mg/kg
zinc oxide CAS: 1314-13-2 EC: 215-222-5	STP	0,1 mg/L	Fresh water	0,0206 mg/L
	Soil	35,6 mg/kg	Marine water	0,0061 mg/L
	Intermittent	Non-applicable	Sediment (Fresh water)	117,8 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	56,5 mg/kg
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	STP	9,6 mg/L	Fresh water	0,1 mg/L
	Soil	2,68 mg/kg	Marine water	0,01 mg/L
	Intermittent	0,1 mg/L	Sediment (Fresh water)	13,7 mg/kg
	Oral	0,02 g/kg	Sediment (Marine water)	1,37 mg/kg
1,2,4-trimethylbenzene CAS: 95-63-6 EC: 202-436-9	STP	2,41 mg/L	Fresh water	0,12 mg/L
	Soil	2,34 mg/kg	Marine water	0,12 mg/L
	Intermittent	0,12 mg/L	Sediment (Fresh water)	13,56 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	13,56 mg/kg
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	STP	9,6 mg/L	Fresh water	0,1 mg/L
	Soil	2,68 mg/kg	Marine water	0,01 mg/L
	Intermittent	0,1 mg/L	Sediment (Fresh water)	13,7 mg/kg
	Oral	0,02 g/kg	Sediment (Marine water)	1,37 mg/kg
Chlorobenzene CAS: 108-90-7 EC: 203-628-5	STP	1,4 mg/L	Fresh water	0,032 mg/L
	Soil	0,166 mg/kg	Marine water	0,003 mg/L
	Intermittent	Non-applicable	Sediment (Fresh water)	0,922 mg/kg
	Oral	0,01 g/kg	Sediment (Marine water)	0,092 mg/kg
Mesitylene CAS: 108-67-8 EC: 203-604-4	STP	2,02 mg/L	Fresh water	0,101 mg/L
	Soil	1,34 mg/kg	Marine water	0,101 mg/L
	Intermittent	0,101 mg/L	Sediment (Fresh water)	7,86 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	7,86 mg/kg
Cumene CAS: 98-82-8 EC: 202-704-5	STP	200 mg/L	Fresh water	0,035 mg/L
	Soil	0,624 mg/kg	Marine water	0,004 mg/L
	Intermittent	0,012 mg/L	Sediment (Fresh water)	3,22 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,322 mg/kg
Toluene CAS: 108-88-3	STP	13,61 mg/L	Fresh water	0,68 mg/L
	Soil	2,89 mg/kg	Marine water	0,68 mg/L

- CONTINUED ON NEXT PAGE



Safety data
sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

EC: 203-625-9	Intermittent	0,68 mg/L	Sediment (Fresh water)	16,39 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	16,39 mg/kg
Benzene CAS: 71-43-2 EC: 200-753-7	STP	39 mg/L	Fresh water	1,9 mg/L
	Soil	4,8 mg/kg	Marine water	1,9 mg/L
	Intermittent	1,9 mg/L	Sediment (Fresh water)	33 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	33 mg/kg
Ethanediol CAS: 107-21-1 EC: 203-473-3	STP	199,5 mg/L	Fresh water	10 mg/L
	Soil	1,53 mg/kg	Marine water	1 mg/L
	Intermittent	10 mg/L	Sediment (Fresh water)	37 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	3,7 mg/kg

8.2 Exposure controls:

- CONTINUED ON NEXT PAGE



Safety data
sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)



- CONTINUED ON NEXT PAGE

-



**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal. B.- Respiratory protection



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases, vapours and particles		EN 149:2001+A1:2009 EN 405:2002+A1:2010 EN ISO 136:1998	Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected.

C.- Specific protection for the hands





Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)		EN ISO 21420:2020	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.



D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Face shield		EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 139821:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties		EN ISO 13287:2020 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

- CONTINUED ON NEXT PAGE



Safety data
sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D **Volatile organic compounds:**

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 81,38 % weight

- CONTINUED ON NEXT PAGE



Safety data
sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

CAR-REP - Anti-Rust

Primer

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

V.O.C. density at 20 °C:	625,77 kg/m ³	CR01018 (625,77 g/L)
Average carbon number:	4,64	
Average molecular weight:	80,39 g/mol	

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

- CONTINUED ON NEXT PAGE



Safety data
sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Aerosol
Appearance:	Not available
Colour:	According to the markings on the package
Odour:	Not available
Odour threshold:	Non-applicable *

Volatility:

Boiling point at atmospheric pressure:	-42 - 330 °C (Propellant)
Vapour pressure at 20 °C:	359970 Pa
Vapour pressure at 50 °C:	<300000 Pa (300 kPa)
Evaporation rate at 20 °C:	Non-applicable *

Product description:

Density at 20 °C:	769 kg/m ³
Relative density at 20 °C:	0,77
Dynamic viscosity at 20 °C:	Non-applicable * Kinematic viscosity at 20 °C: Non-applicable *
Kinematic viscosity at 40 °C:	Non-applicable *
Concentration:	Non-applicable * pH: Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable * Solubility properties: Non-applicable * Decomposition temperature: Non-applicable * Melting point/freezing point: Non-applicable * Recipient pressure: 359970 Pa (3,6 bar)

Flammability:

Flash Point:	Non-applicable
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	365 °C (Propellant)
Lower flammability limit:	0,8 % Volume
Upper flammability limit:	12 % Volume

Particle characteristics:

Median equivalent diameter:	Non-applicable
-----------------------------	----------------

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Non-applicable *
-----------------------	------------------

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

- CONTINUED ON NEXT PAGE



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

Oxidising properties: Non-applicable * Corrosive to metals: Non-applicable
* Heat of combustion: Non-applicable *
Aerosols-total percentage (by mass) of flammable Non-applicable * components:

Other safety characteristics:

Surface tension at 20 °C: Non-applicable *

Refraction index: Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

10.5	Shock and friction	<input type="checkbox"/> Contact with air	Increase in temperature	Sunlight	Humidity
	Not applicable	<input type="checkbox"/> Not applicable	Risk of combustion	Avoid direct impact	Not applicable

Incompatible materials:

10.6	Acids	<input type="checkbox"/> Water	Oxidising materials	Combustible materials	Others
	Avoid strong acids	<input type="checkbox"/> Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

Hazardous decomposition products:

Contains substances which require external energy for spontaneous decomposition. Form explosive peroxides when distilled, evaporated or otherwise concentrated.

SECTION 11: TOXICOLOGICAL INFORMATION

- CONTINUED ON NEXT PAGE



Safety data
sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure: A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.

- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3. B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- CONTINUED ON NEXT PAGE



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3.
IARC: Xylene (3); Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 (3); Ethylbenzene (2B); Cumene (2B); Toluene (3); Lead monoxide (2A); Benzene (1); Ethylbenzene (2B); Hydrocarbons, C9, aromatics (3); Reaction mass of ethylbenzene and xylene (3); Titanium dioxide (aerodynamic diameter ≤ 10 µm) (2B)
- Mutagenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with mutagenic effects. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:
Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

- G- Specific target organ toxicity (STOT)-repeated exposure:
Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

- H- Aspiration hazard:
Skin: Repeated exposure may cause skin dryness or cracking

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3. **Other information:**

CAS 13463-67-7 Titanium dioxide (aerodynamic diameter ≤ 10 µm): The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
Xylene CAS: 1330-20-7 EC: 215-535-7	LD50 oral	3523 mg/kg	Rat
	LD50 dermal	1100 mg/kg	
	LC50 inhalation	11 mg/L (ATEi)	
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LD50 oral	12789 mg/kg	Rat
	LD50 dermal	14112 mg/kg	Rabbit
	LC50 inhalation	23,4 mg/L (4 h)	Rat
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	LD50 oral	8532 mg/kg	Rat
	LD50 dermal	5100 mg/kg	Rat
	LC50 inhalation	30 mg/L (4 h)	Rat
Butanone CAS: 78-93-3 EC: 201-159-0	LD50 oral	4000 mg/kg	Rat
	LD50 dermal	6400 mg/kg	Rabbit
	LC50 inhalation	23,5 mg/L (4 h)	Rat
Butan-2-ol CAS: 78-92-2 EC: 201-158-5	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>20 mg/L	

- CONTINUED ON NEXT PAGE



Safety data
sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

acetone CAS: 67-64- 1 EC: 200-662-2	LD50 oral	5800 mg/kg	Rat
	LD50 dermal	7426 mg/kg	Rabbit
	LC50 inhalation	76 mg/L (4 h)	Rat

- CONTINUED ON NEXT PAGE



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
Titanium dioxide (aerodynamic diameter ≤ 10 µm) CAS: 13463-67-7 EC: 236-675-5	LD50 oral	10000 mg/kg	Rat
	LD50 dermal	10000 mg/kg	Rabbit
	LC50 inhalation	>5 mg/L	
Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg	Rat
	LC50 inhalation	11 mg/L (4 h)	Rat
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	LD50 oral	8532 mg/kg	Rat
	LD50 dermal	>5000 mg/kg	Rat
	LC50 inhalation	30 mg/L (4 h)	Rat
zinc oxide CAS: 1314-13-2 EC: 215-222-5	LD50 oral	7950 mg/kg	Mouse
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>5 mg/L	
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	LD50 oral	3500 mg/kg	Rat
	LD50 dermal	15354 mg/kg	Rabbit
	LC50 inhalation	17,2 mg/L (4 h)	Rat
1,2,4-trimethylbenzene CAS: 95-63-6 EC: 202-436-9	LD50 oral	3400 mg/kg	Rat
	LD50 dermal	3160 mg/kg	Rabbit
	LC50 inhalation	11 mg/L (4 h)	Rat
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	LD50 oral	3500 mg/kg	Rat
	LD50 dermal	15354 mg/kg	Rabbit
	LC50 inhalation	17,2 mg/L (4 h)	Rat
Chlorobenzene CAS: 108-90-7 EC: 203-628-5	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	11 mg/L (4 h)	Rat
Mesitylene CAS: 108-67-8 EC: 203-604-4	LD50 oral	6000 mg/kg	Rat
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>20 mg/L	
Cumene CAS: 98-82-8 EC: 202-704-5	LD50 oral	2700 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>20 mg/L	
Toluene CAS: 108-88-3 EC: 203-625-9	LD50 oral	5580 mg/kg	Rat
	LD50 dermal	12124 mg/kg	Rat
	LC50 inhalation	28,1 mg/L (4 h)	Rat
Benzene CAS: 71-43-2	LD50 oral	2900 mg/kg	Rat
	LD50 dermal	8263 mg/kg	Rabbit

- CONTINUED ON NEXT PAGE



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

EC: 200-753-7	LC50 inhalation	44,45 mg/L (4 h)	Rat
Ethanediol CAS: 107-21-1 EC: 203-473-3	LD50 oral	500 mg/kg	Rat
	LD50 dermal	>5000 mg/kg	Rabbit
	LC50 inhalation	>20 mg/L	

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

- CONTINUED ON NEXT PAGE



Safety data
sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

SECTION 12: ECOLOGICAL INFORMATION (continued)

- CONTINUED ON NEXT PAGE

-



Safety data
sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

Identification	Concentration		Species	Genus
	LC50	EC50		
acetone CAS: 67-64-1 EC: 200-662-2	LC50	5540 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	8800 mg/L (48 h)	Daphnia pulex	Crustacean
	EC50	3400 mg/L (48 h)	Chlorella pyrenoidosa	Algae
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LC50	Non-applicable		
	EC50	Non-applicable		
	EC50	675 mg/L (72 h)	Scenedesmus subspicatus	Algae
Butanone CAS: 78-93-3 EC: 201-159-0	LC50	3220 mg/L (96 h)	Pimephales promelas	Fish
	EC50	5091 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	4300 mg/L (168 h)	Scenedesmus quadricauda	Algae
Butan-2-ol CAS: 78-92-2 EC: 201-158-5	LC50	3670 mg/L (96 h)	Pimephales promelas	Fish
	EC50	3750 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	95 mg/L (168 h)	Scenedesmus quadricauda	Algae
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	LC50	161 mg/L (96 h)	Pimephales promelas	Fish
	EC50	481 mg/L (48 h)	Daphnia sp.	Crustacean
	EC50	Non-applicable		
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	LC50	161 mg/L (96 h)	Pimephales promelas	Fish
	EC50	481 mg/L (48 h)	Daphnia sp.	Crustacean
	EC50	Non-applicable		
zinc oxide CAS: 1314-13-2 EC: 215-222-5	LC50	0,82 mg/L (96 h)	Oncorhynchus kisutch	Fish
	EC50	3,4 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	Non-applicable		
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	LC50	42,3 mg/L (96 h)	Pimephales promelas	Fish
	EC50	75 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	63 mg/L (3 h)	Chlorella vulgaris	Algae
1,2,4-trimethylbenzene CAS: 95-63-6 EC: 202-436-9	LC50	7,72 mg/L (96 h)	Pimephales promelas	Fish
	EC50	6,14 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	Non-applicable		
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	LC50	42,3 mg/L (96 h)	Pimephales promelas	Fish
	EC50	75 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	63 mg/L (3 h)	Chlorella vulgaris	Algae
Chlorobenzene CAS: 108-90-7 EC: 203-628-5	LC50	7,4 mg/L (96 h)	Lepomis macrochirus	Fish
	EC50	19,9 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	12,5 mg/L (96 h)	Selenastrum capricornutum	Algae
Mesitylene CAS: 108-67-8 EC: 203-604-4	LC50	12,5 mg/L (96 h)	Carassius auratus	Fish
	EC50	50 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	53 mg/L (48 h)	Scenedesmus subspicatus	Algae
Cumene CAS: 98-82-8 EC: 202-704-5	LC50	2,7 mg/L (96 h)	Salmo gairdneri	Fish
	EC50	10,8 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	2,6 mg/L (72 h)	Selenastrum capricornutum	Algae

- CONTINUED ON NEXT PAGE



Safety data
sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

Toluene CAS: 108-88-3 EC: 203-625-9	LC50	5,5 mg/L (96 h)	Oncorhynchus kisutch	Fish
	EC50	3,78 mg/L (48 h)	Ceriodaphnia dubia	Crustacean
	EC50	Non-applicable		
Benzene CAS: 71-43-2 EC: 200-753-7	LC50	5,9 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	66 mg/L (24 h)	Artemia salina	Crustacean
	EC50	29 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae
Ethanediol CAS: 107-21-1 EC: 203-473-3	LC50	53000 mg/L (96 h)	Pimephales promelas	Fish
	EC50	51000 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	24000 mg/L (168 h)	Selenastrum capricornutum	Algae

Chronic toxicity:

Identification		Concentration	Species	Genus
acetone CAS: 67-64-1 EC: 200-662-2	NOEC	Non-applicable		
	NOEC	2212 mg/L	Daphnia magna	Crustacean

- CONTINUED ON NEXT PAGE



Safety data
sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

SECTION 12: ECOLOGICAL INFORMATION (continued)

- CONTINUED ON NEXT PAGE

-

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

Identification	Concentration		Species	Genus
	NOEC	Concentration		
Xylene CAS: 1330-20-7 EC: 215-535-7	NOEC	1,3 mg/L	Oncorhynchus mykiss	Fish
	NOEC	1,17 mg/L	Ceriodaphnia dubia	Crustacean
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	NOEC	Non-applicable		
	NOEC	23,2 mg/L	Daphnia magna	Crustacean
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	NOEC	47,5 mg/L	Oryzias latipes	Fish
	NOEC	100 mg/L	Daphnia magna	Crustacean
Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0	NOEC	1,3 mg/L	Oncorhynchus mykiss	Fish
	NOEC	1,17 mg/L	Ceriodaphnia dubia	Crustacean
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	NOEC	47,5 mg/L	Oryzias latipes	Fish
	NOEC	100 mg/L	Daphnia magna	Crustacean
zinc oxide CAS: 1314-13-2 EC: 215-222-5	NOEC	0,44 mg/L	Oncorhynchus mykiss	Fish
	NOEC	0,031 mg/L	Daphnia magna	Crustacean
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	NOEC	Non-applicable		
	NOEC	0,96 mg/L	Ceriodaphnia dubia	Crustacean
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	NOEC	Non-applicable		
	NOEC	0,96 mg/L	Ceriodaphnia dubia	Crustacean
Chlorobenzene CAS: 108-90-7 EC: 203-628-5	NOEC	4,8 mg/L	Danio rerio	Fish
	NOEC	0,32 mg/L	Daphnia magna	Crustacean
Mesitylene CAS: 108-67-8 EC: 203-604-4	NOEC	0,277 mg/L	N/A	Fish
	NOEC	0,4 mg/L	Daphnia magna	Crustacean
Cumene CAS: 98-82-8 EC: 202-704-5	NOEC	0,38 mg/L	Pimephales promelas	Fish
	NOEC	0,35 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
	Parameter	Value	Parameter	Value
acetone CAS: 67-64-1 EC: 200-662-2	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	96 %
Xylene CAS: 1330-20-7 EC: 215-535-7	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	88 %
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	5 days
	BOD5/COD	Non-applicable	% Biodegradable	84 %
Butanone CAS: 78-93-3 EC: 201-159-0	BOD5	2,03 g O2/g	Concentration	Non-applicable
	COD	2,31 g O2/g	Period	20 days

- CONTINUED ON NEXT PAGE



Safety data
sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

	BOD5/COD	0,88	% Biodegradable	89 %
Butan-2-ol CAS: 78-92-2 EC: 201-158-5	BOD5	0 g O2/g	Concentration	100 mg/L
	COD	0 g O2/g	Period	14 days
	BOD5/COD	0,75	% Biodegradable	73,5 %
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	BOD5	Non-applicable	Concentration	785 mg/L
	COD	Non-applicable	Period	8 days
	BOD5/COD	Non-applicable	% Biodegradable	100 %
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	BOD5	Non-applicable	Concentration	785 mg/L
	COD	Non-applicable	Period	8 days
	BOD5/COD	Non-applicable	% Biodegradable	100 %
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	90 %
1,2,4-trimethylbenzene CAS: 95-63-6 EC: 202-436-9	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	18 %

- CONTINUED ON NEXT PAGE



Safety data
sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

SECTION 12: ECOLOGICAL INFORMATION (continued)

- CONTINUED ON NEXT PAGE

-



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

Identification	Degradability		Biodegradability	
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	90 %
Chlorobenzene CAS: 108-90-7 EC: 203-628-5	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	0 %
Mesitylene CAS: 108-67-8 EC: 203-604-4	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	0 %
Cumene CAS: 98-82-8 EC: 202-704-5	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	40 %
Toluene CAS: 108-88-3 EC: 203-625-9	BOD5	2,5 g O2/g	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	100 %
Benzene CAS: 71-43-2 EC: 200-753-7	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	40 %
Ethanediol CAS: 107-21-1 EC: 203-473-3	BOD5	0,47 g O2/g	Concentration	100 mg/L
	COD	1,29 g O2/g	Period	14 days
	BOD5/COD	0,36	% Biodegradable	90 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential	
acetone CAS: 67-64-1 EC: 200-662-2	BCF	1
	Pow Log	-0.24
	Potential	Low
Xylene CAS: 1330-20-7 EC: 215-535-7	BCF	9
	Pow Log	2.77
	Potential	Low
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	BCF	4
	Pow Log	1.78
	Potential	Low

- CONTINUED ON NEXT PAGE



Safety data
sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

Butanone CAS: 78-93-3 EC: 201-159-0	BCF	3
	Pow Log	0.29
	Potential	Low
Butan-2-ol CAS: 78-92-2 EC: 201-158-5	BCF	3
	Pow Log	0.61
	Potential	Low
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	BCF	1
	Pow Log	0.43
	Potential	Low
Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0	BCF	9
	Pow Log	2.77
	Potential	Low
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	BCF	1
	Pow Log	0.43
	Potential	Low
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	BCF	1
	Pow Log	3.15
	Potential	Low

- CONTINUED ON NEXT PAGE



Safety data
sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

SECTION 12: ECOLOGICAL INFORMATION (continued)

- CONTINUED ON NEXT PAGE

-



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

Identification	Bioaccumulation potential	
1,2,4-trimethylbenzene CAS: 95-63-6 EC: 202-436-9	BCF	154
	Pow Log	3.78
	Potential	High
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	BCF	1
	Pow Log	3.15
	Potential	Low
Chlorobenzene CAS: 108-90-7 EC: 203-628-5	BCF	22
	Pow Log	2.84
	Potential	Low
Mesitylene CAS: 108-67-8 EC: 203-604-4	BCF	182
	Pow Log	3.42
	Potential	High
Cumene CAS: 98-82-8 EC: 202-704-5	BCF	120
	Pow Log	3.66
	Potential	High
Toluene CAS: 108-88-3 EC: 203-625-9	BCF	90
	Pow Log	2.73
	Potential	Moderate
Benzene CAS: 71-43-2 EC: 200-753-7	BCF	4
	Pow Log	2.13
	Potential	Low
Ethanedial CAS: 107-21-1 EC: 203-473-3	BCF	10
	Pow Log	-1.36
	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
acetone CAS: 67-64-1 EC: 200-662-2	Koc	1	Henry	2,93 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2,304E-2 N/m (25 °C)	Moist soil	Yes
Xylene CAS: 1330-20-7 EC: 215-535-7	Koc	202	Henry	524,86 Pa·m ³ /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	Non-applicable	Moist soil	Yes
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2,478E-2 N/m (25 °C)	Moist soil	Non-applicable
Butanone CAS: 78-93-3 EC: 201-159-0	Koc	30	Henry	5,77 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Yes

- CONTINUED ON NEXT PAGE



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

	Surface tension	2,396E-2 N/m (25 °C)	Moist soil	Yes
Butan-2-ol CAS: 78-92-2 EC: 201-158-5	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2,433E-2 N/m (25 °C)	Moist soil	Non-applicable
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Koc	520	Henry	798,44 Pa·m ³ /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	2,859E-2 N/m (25 °C)	Moist soil	Yes
1,2,4-trimethylbenzene CAS: 95-63-6 EC: 202-436-9	Koc	537	Henry	624,16 Pa·m ³ /mol
	Conclusion	Low	Dry soil	Yes
	Surface tension	2,919E-2 N/m (25 °C)	Moist soil	Yes
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Koc	520	Henry	798,44 Pa·m ³ /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	2,859E-2 N/m (25 °C)	Moist soil	Yes

- CONTINUED ON NEXT PAGE



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Absorption/desorption		Volatility		
			Henry		
Chlorobenzene CAS: 108-90-7 EC: 203-628-5	Koc	Non-applicable	Henry	<input type="text"/>	Non-applicable
	Conclusion	Non-applicable	Dry soil	<input type="text"/>	Non-applicable
	Surface tension	3,293E-2 N/m (25 °C)	Moist soil	<input type="text"/>	Non-applicable
Mesitylene CAS: 108-67-8 EC: 203-604-4	Koc	1445	Henry	<input type="text"/>	888,62 Pa·m ³ /mol
	Conclusion	Low	Dry soil	<input type="text"/>	Yes
	Surface tension	2,805E-2 N/m (25 °C)	Moist soil	<input type="text"/>	Yes
Cumene CAS: 98-82-8 EC: 202-704-5	Koc	Non-applicable	Henry	<input type="text"/>	Non-applicable
	Conclusion	Non-applicable	Dry soil	<input type="text"/>	Non-applicable
	Surface tension	2,769E-2 N/m (25 °C)	Moist soil	<input type="text"/>	Non-applicable
Toluene CAS: 108-88-3 EC: 203-625-9	Koc	178	Henry	<input type="text"/>	672,8 Pa·m ³ /mol
	Conclusion	Moderate	Dry soil	<input type="text"/>	Yes
	Surface tension	2,793E-2 N/m (25 °C)	Moist soil	<input type="text"/>	Yes
Benzene CAS: 71-43-2 EC: 200-753-7	Koc	Non-applicable	Henry	<input type="text"/>	Non-applicable
	Conclusion	Non-applicable	Dry soil	<input type="text"/>	Non-applicable
	Surface tension	2,821E-2 N/m (25 °C)	Moist soil	<input type="text"/>	Non-applicable
Ethanediol CAS: 107-21-1 EC: 203-473-3	Koc	0	Henry	<input type="text"/>	1,327E-1 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	<input type="text"/>	No
	Surface tension	4,989E-2 N/m (25 °C)	Moist soil	<input type="text"/>	No

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

- CONTINUED ON NEXT PAGE



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
16 05 04*	gases in pressure containers (including halons) containing hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue.

Waste should not be disposed of to drains. See paragraph 6.2. **Regulations**

related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land: With regard to ADR 2021 and RID 2021:

SECTION 14: TRANSPORT INFORMATION (continued)



2

- 14.1 UN number or ID number:** UN1950
- 14.2 UN proper shipping name:** AEROSOLS
- 14.3 Transport hazard class(es):** 2.1

Labels:

- 14.4 Packing group:** N/A
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
 - Special regulations: 190, 327, 344, 625
 - Tunnel restriction code: D
 - Physico-Chemical properties: see section 9
 - Limited quantities: 1 L
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 40-20:

- 14.1 UN number or ID number:** UN1950
- 14.2 UN proper shipping name:** AEROSOLS
- 14.3 Transport hazard class(es):** 2.1



Labels:

- CONTINUED ON NEXT PAGE

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

N/A



2

14.4 Packing group:

14.5 Marine pollutant:

14.6 Special precautions for user

Special regulations:	63, 959, 190, 277, 327, 344
EmS Codes:	F-D, S-U
Physico-Chemical properties:	see section 9
Limited quantities:	1 L
Segregation group:	Non-applicable

14.7 Maritime transport in bulk according to IMO instruments:

No

Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2023:

14.1 UN number or ID number:

UN1950
AEROSOLS

14.2 UN proper shipping name:

2



2

14.3 Transport hazard class(es):

Labels:	2.1
	N/A

14.4 Packing group:

14.5 Environmental hazards:

14.6 Special precautions for user

Physico-Chemical properties:	see section 9
------------------------------	---------------

14.7 Maritime transport in bulk according to IMO instruments:

Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable
 Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable
 Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable
 Article 95, REGULATION (EU) No 528/2012: Non-applicable

SECTION 15: REGULATORY INFORMATION (continued)

- CONTINUED ON NEXT PAGE



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

CAR-REP - Anti-Rust Primer
CR01015, CR01016, CR01017, CR01018

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Contains Benzene

Seveso III:

Table with 4 columns: Section, Description, Lower-tier requirements, Upper-tier requirements. Row 1: P3a, FLAMMABLE AEROSOLS, 150, 500

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors: Contains acetone. Product under the provisions of Article 9. However, products that contain explosives precursors only to such a small extent and in such complex mixtures that the extraction of the explosives precursors is technically extremely difficult should be excluded from the scope of this Regulation.

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
-tricks and jokes,
-games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Contains Octamethylcyclotetrasiloxane. 1. | Shall not be placed on the market in wash-off cosmetic products in a concentration equal to or greater than 0,1 % by weight of either substance, after 31 January 2020. | 2. | For the purposes of this entry, "washoff cosmetic products" means cosmetic products as defined in Article 2(1)(a) of Regulation (EC) No 1223/2009 that, under normal conditions of use, are washed off with water after application.'

Contains Lead monoxide. 1. Shall not be placed on the market or used in any individual part of jewellery articles if the concentration of lead ; (b) internal components of watch timepieces inaccessible to consumers; (c) non-synthetic or reconstructed precious and semiprecious stones (CN code 7103 , as established by Regulation (EEC) No 2658/87), unless they have been treated with lead or its compounds or mixtures containing these substances; (d) enamels, defined as vitrifiable mixtures resulting from the fusion, vitrification or sintering of minerals melted at a temperature of at least 500 °C. 5. By way of derogation, paragraph 1 shall not apply to jewellery articles placed on the market for the first time before 9 October 2013 and jewellery articles produced before 10 December 1961. 6. By 9 October 2017, the Commission shall re-evaluate paragraphs 1 to 5 of this entry in the light of new scientific information, including the availability of alternatives and the migration of lead from the articles referred to in paragraph 1 and, if appropriate, modify this entry accordingly. 7. Shall not be placed on the market or used in articles supplied to the general public, if the concentration of lead (expressed as metal) in those articles or accessible parts thereof is equal to or greater than 0,05 % by weight, and those articles or accessible parts thereof may, during normal or reasonably foreseeable conditions of use, be placed in the mouth by children. That limit shall not apply where it can be demonstrated that the rate of lead release from such an article or any such accessible part of an article, whether coated or uncoated, does not exceed 0,05 µg/cm2 per hour (equivalent to 0,05 µg/g/h), and, for coated articles, that the coating is sufficient to ensure that this release rate is not exceeded for a period of at least two years of normal or reasonably foreseeable conditions of use of the article. For the purposes of this paragraph, it is considered that an article or accessible part of an article may be placed in the mouth by children if it is smaller than 5 cm in one dimension or has a detachable or protruding part of that size. 8. By way of derogation, paragraph 7 shall not apply to: (a) jewellery articles covered by paragraph 1; (b) crystal glass as defined in Annex I (categories 1, 2, 3 and 4) to Directive 69/493/EEC; (c) non-synthetic or reconstructed precious and semiprecious stones (CN code 7103 as established by Regulation (EEC) No 2658/87) unless they have been treated with lead or its compounds or mixtures containing these substances; (d) enamels, defined as vitrifiable mixtures resulting from the fusion, vitrification or sintering of mineral melted at a temperature of at least 500 °C; (e) keys and locks, including padlocks; (f) musical instruments; (g) articles and parts of articles comprising brass alloys, if the concentration of lead (expressed as metal) in the brass alloy does not exceed 0,5 % by weight; (h) the tips of writing instruments; (i) religious articles; (j) portable zinc-carbon batteries and button cell batteries; (k) articles within the scope of: (i) Directive 94/62/EC; (ii) Regulation (EC) No 1935/2004; (iii) Directive 2009/48/EC of the European Parliament and of the Council (*15); (iv) Directive 2011/65/EU of the European Parliament and of the Council (*16) 9. By 1 July 2019, the Commission shall re-evaluate paragraphs 7 and 8(e), (f), (i) and (j) of this entry in the light of new scientific information, including the availability of alternatives and the migration of lead from the articles referred to in paragraph 7, including the requirement on coating integrity, and, if appropriate, modify this entry accordingly. 10. By way of derogation paragraph 7 shall not apply to articles placed on the market for the first time before 1 June 2016.

Contains Chrome antimony titanium buff rutile. This product may not be used in the fabrication of articles intended for prolonged direct contact with the skin:

- earrings
- necklaces, bracelets and chains, anklets, finger rings,
- wrist-watch cases, watch straps and tighteners,
- rivet buttons, tighteners, rivets, zippers and metal marks, when these are used in garments

if the rate of nickel release from the parts of these articles coming into direct and prolonged contact with the skin is greater than 0,5 µg/cm 2 /week.

- CONTINUED ON NEXT PAGE



Safety data
sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

- CONTINUED ON NEXT PAGE



Safety data
sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer**

SECTION 15: REGULATORY INFORMATION (continued)

The product could be affected by sectorial legislation

CR01018

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

- CONTINUED ON NEXT PAGE

-



Safety data
sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**CAR-REP - Anti-Rust
Primer
CR01015, CR01016, CR01017,
CR01018**

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3):

- Removed substances
Butane (106-97-8)

Propane (74-98-6)

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- Supplementary information

Texts of the legislative phrases mentioned in section 2:

H336: May cause drowsiness or dizziness.

H412: Harmful to aquatic life with long lasting effects.

H229: Pressurised container: May burst if heated.

H222: Extremely flammable aerosol.

H319: Causes serious eye irritation.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3 **CLP Regulation (EC) No 1272/2008:**

Acute Tox. 4: H302 - Harmful if swallowed.

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.

Acute Tox. 4: H332 - Harmful if inhaled.

Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Carc. 1A: H350 - May cause cancer.

Carc. 1B: H350 - May cause cancer.

Carc. 2: H351 - Suspected of causing cancer (Inhalation).

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Muta. 1B: H340 - May cause genetic defects.

Repr. 2: H361d - Suspected of damaging the unborn child.

Skin Irrit. 2: H315 - Causes skin irritation.

STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Inhalation).

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

STOT SE 3: H335 - May cause respiratory irritation.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

STOT SE 3: Calculation method

Aquatic Chronic 3: Calculation method

Aerosol 1: Calculation method

Aerosol 1: Calculation method

Eye Irrit. 2: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

- CONTINUED ON NEXT PAGE



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

CAR-REP - Anti-Rust Primer
CR01015, CR01016, CR01017, CR01018

SECTION 16: OTHER INFORMATION (continued)

<http://echa.europa.eu> <http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -