

**Maston - Zinc Cold Galvanized, Zinc Aluminium  
400171, 400172**

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

**1.1 Product identifier:** Maston - Zinc Cold Galvanized, Zinc Aluminium  
400171, 400172

**Other means of identification:** Non-applicable

**1.2 Relevant identified uses of the substance or mixture and uses advised against:**

Relevant uses: Paint

Uses advised against: All uses not specified in this section or in section 7.3

**1.3 Details of the supplier of the safety data sheet:**

Spray Shop Supplies Pty Ltd  
38 Cyber Loop, Dandenong South,  
Victoria, Australia.

Phone.: +61 3 9799 2007

Fax: +61 9799 6568

orders@sprayshopsupplies.com.au  
www.sprayshopsupplies.com.au

**1.4 Emergency telephone number:** (8:00-16:00)+61 3 9799 2007

**SECTION 2: HAZARDS IDENTIFICATION**

**2.1 Classification of the substance or mixture:**

**CLP Regulation (EC) No 1272/2008:**

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aerosol 1: Pressurised container: May burst if heated., H229

Aerosol 1: Flammable aerosols, Category 1, H222

Aquatic Acute 1: Hazardous to the aquatic environment, acute hazard, Category 1, H400

Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard, Category 1, H410 Eye Irrit. 2: Eye irritation, Category 2, H319

STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

**2.2 Label elements:**

**CLP Regulation (EC) No 1272/2008:**

**Danger**



**Hazard statements:**

Aerosol 1: H229 - Pressurised container: May burst if heated.

Aerosol 1: H222 - Extremely flammable aerosol.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Eye Irrit. 2: H319 - Causes serious eye irritation.

STOT SE 3: H336 - May cause drowsiness or dizziness. **Precautionary**

**statements:** P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F **Supplementary information:**

EUH066: Repeated exposure may cause skin dryness or cracking. **Substances that contribute to the**

**classification**

acetone (CAS: 67-64-1); N-butyl acetate (CAS: 123-86-4); Butanone (CAS: 78-93-3) **UFI:** RX20-N0Y9-

100U-AE2Y

**2.3 Other hazards:**

**SECTION 2: HAZARDS IDENTIFICATION (continued)**

- CONTINUED ON NEXT PAGE -

**Maston - Zinc Cold Galvanized, Zinc Aluminium  
400171, 400172**

Product fails to meet PBT/vPvB criteria  
DK. Mal Code 3-1

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

**3.1 Substance:**















Non-applicable

**3.2 Mixture:**

**Chemical description:** Aerosol

**Components:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: 7440-66-6 EC: 231-175-3 Index: 030-002-00-7 REACH: 01-2119467174-37XXXX	<b>Zinc powder - zinc dust (stabilised)<sup>(1)</sup></b>	ATP CLP00	<b>25 - &lt;30 %</b>
	Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 1: H410 - Warning 	
CAS: 67-64-1 EC: 200-662-2 Index: 606-001-00-8 REACH: 01-2119471330-49XXXX	<b>acetone<sup>(2)</sup></b>	ATP CLP00	<b>20 - &lt;25 %</b>
	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger  	
CAS: 106-97-8 EC: 203-448-7 Index: 601-004-00-0 REACH: 01-2119474691-32XXXX	<b>Butane<sup>(2)</sup></b>	ATP CLP00	<b>10 - &lt;20 %</b>
	Regulation 1272/2008	Flam. Gas 1A: H220; Press. Gas: H280 - Danger 	
CAS: 74-98-6 EC: 200-827-9 Index: 601-003-00-5 REACH: 01-2119486944-21XXXX	<b>Propane<sup>(2)</sup></b>	ATP CLP00	<b>10 - &lt;20 %</b>
	Regulation 1272/2008	Flam. Gas 1A: H220; Press. Gas: H280 - Danger 	
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32XXXX	<b>Xylene<sup>(2)</sup></b>	ATP CLP00	<b>5 - &lt;10 %</b>
	Regulation 1272/2008	Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning  	
CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH: 01-2119485493-29XXXX	<b>N-butyl acetate<sup>(2)</sup></b>	ATP CLP00	<b>2,5 - &lt;5 %</b>
	Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning  	
CAS: 108-65-6 EC: 203-603-9 Index: 607-195-00-7 REACH: 01-2119475791-29XXXX	<b>2-methoxy-1-methylethyl acetate<sup>(2)</sup></b>	ATP ATPO	<b>1 - &lt;2,5 %</b>
	Regulation 1272/2008	Flam. Liq. 3: H226 - Warning 	
CAS: 78-93-3 EC: 201-159-0 Index: 606-002-00-3 REACH: 01-2119457290-43XXXX	<b>Butanone<sup>(2)</sup></b>	ATP CLP00	<b>1 - &lt;2,5 %</b>
	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger  	
CAS: 108-94-1 EC: 203-631-1 Index: 606-010-00-7 REACH: 01-2119453616-35XXXX	<b>Cyclohexanone<sup>(2)</sup></b>	ATP CLP00	<b>0,25 - &lt;1 %</b>
	Regulation 1272/2008	Acute Tox. 4: H332; Flam. Liq. 3: H226 - Warning  	

<sup>(1)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

<sup>(2)</sup> Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

**SECTION 4: FIRST AID MEASURES**

**4.1 Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product. **By inhalation:**

- CONTINUED ON NEXT PAGE -

**Maston - Zinc Cold Galvanized, Zinc Aluminium  
400171, 400172****SECTION 4: FIRST AID MEASURES (continued)**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance. **By skin contact:**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection. **By eye contact:**

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

**By ingestion/aspiration:**

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

**4.2 Most important symptoms and effects, both acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of any immediate medical attention and special treatment needed:** Non-applicable**SECTION 5: FIREFIGHTING MEASURES****5.1 Extinguishing media:****Suitable extinguishing media:**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO<sub>2</sub>).

**Unsuitable extinguishing media:**

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

**5.2 Special hazards arising from the substance or mixture:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Advice for firefighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC. **Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

**SECTION 6: ACCIDENTAL RELEASE MEASURES****6.1 Personal precautions, protective equipment and emergency procedures:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8).

Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

**6.2 Environmental precautions:**

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

**6.3 Methods and material for containment and cleaning up:**

It is recommended:

- CONTINUED ON NEXT PAGE -

**Maston - Zinc Cold Galvanized, Zinc Aluminium  
400171, 400172**

**SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)**

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

**6.4 Reference to other sections:** See sections 8 and 13.

**SECTION 7: HANDLING AND STORAGE**

**7.1 Precautions for safe handling:** A.-

Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

**7.2 Conditions for safe storage, including any incompatibilities:**

A.- Technical measures for storage

- Minimum Temp.: 5 °C
- Maximum Temp.: 50 °C
- Maximum time: 60 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
	IOELV (8h)		
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	IOELV (8h)	50 ppm	241 mg/m <sup>3</sup>
	IOELV (STEL)	150 ppm	723 mg/m <sup>3</sup>
acetone CAS: 67-64-1 EC: 200-662-2	IOELV (8h)	500 ppm	1210 mg/m <sup>3</sup>
	IOELV (STEL)		
Xylene CAS: 1330-20-7 EC: 215-535-7	IOELV (8h)	50 ppm	221 mg/m <sup>3</sup>
	IOELV (STEL)	100 ppm	442 mg/m <sup>3</sup>
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	IOELV (8h)	50 ppm	275 mg/m <sup>3</sup>
	IOELV (STEL)	100 ppm	550 mg/m <sup>3</sup>
Butanone CAS: 78-93-3 EC: 201-159-0	IOELV (8h)	200 ppm	600 mg/m <sup>3</sup>
	IOELV (STEL)	300 ppm	900 mg/m <sup>3</sup>
Cyclohexanone CAS: 108-94-1 EC: 203-631-1	IOELV (8h)	10 ppm	40,8 mg/m <sup>3</sup>
	IOELV (STEL)	20 ppm	81,6 mg/m <sup>3</sup>

- CONTINUED ON NEXT PAGE -

**Maston - Zinc Cold Galvanized, Zinc Aluminium  
400171, 400172**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

**DNEL (Workers):**

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Zinc powder - zinc dust (stabilised) CAS: 7440-66-6 EC: 231-175-3	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	5 mg/m <sup>3</sup>	Non-applicable
acetone CAS: 67-64-1 EC: 200-662-2	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	186 mg/kg	Non-applicable
	Inhalation	Non-applicable	2420 mg/m <sup>3</sup>	1210 mg/m <sup>3</sup>	Non-applicable
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	212 mg/kg	Non-applicable
	Inhalation	442 mg/m <sup>3</sup>	442 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	11 mg/kg	Non-applicable	11 mg/kg	Non-applicable
	Inhalation	600 mg/m <sup>3</sup>	600 mg/m <sup>3</sup>	300 mg/m <sup>3</sup>	300 mg/m <sup>3</sup>
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	796 mg/kg	Non-applicable
	Inhalation	Non-applicable	550 mg/m <sup>3</sup>	275 mg/m <sup>3</sup>	Non-applicable
Butanone CAS: 78-93-3 EC: 201-159-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	1161 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	600 mg/m <sup>3</sup>	Non-applicable
Cyclohexanone CAS: 108-94-1 EC: 203-631-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	4 mg/kg	Non-applicable	4 mg/kg	Non-applicable
	Inhalation	80 mg/m <sup>3</sup>	80 mg/m <sup>3</sup>	40 mg/m <sup>3</sup>	40 mg/m <sup>3</sup>

**DNEL (General population):**

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Zinc powder - zinc dust (stabilised) CAS: 7440-66-6 EC: 231-175-3	Oral	Non-applicable	Non-applicable	0,83 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	2,5 mg/m <sup>3</sup>	Non-applicable
acetone CAS: 67-64-1 EC: 200-662-2	Oral	Non-applicable	Non-applicable	62 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	62 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	200 mg/m <sup>3</sup>	Non-applicable
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	125 mg/kg	Non-applicable
	Inhalation	260 mg/m <sup>3</sup>	260 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	2 mg/kg	Non-applicable	2 mg/kg	Non-applicable
	Dermal	6 mg/kg	Non-applicable	6 mg/kg	Non-applicable
	Inhalation	300 mg/m <sup>3</sup>	300 mg/m <sup>3</sup>	35,7 mg/m <sup>3</sup>	35,7 mg/m <sup>3</sup>
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Oral	Non-applicable	Non-applicable	36 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	320 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	33 mg/m <sup>3</sup>	33 mg/m <sup>3</sup>
Butanone CAS: 78-93-3	Oral	Non-applicable	Non-applicable	31 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	412 mg/kg	Non-applicable

- CONTINUED ON NEXT PAGE -

**Maston - Zinc Cold Galvanized, Zinc Aluminium  
400171, 400172**

EC: 201-159-0	Inhalation	Non-applicable	Non-applicable	106 mg/m <sup>3</sup>	Non-applicable
Cyclohexanone CAS: 108-94-1 EC: 203-631-1	Oral	1,5 mg/kg	Non-applicable	1,5 mg/kg	Non-applicable
	Dermal	1 mg/kg	Non-applicable	1 mg/kg	Non-applicable
	Inhalation	20 mg/m <sup>3</sup>	40 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	20 mg/m <sup>3</sup>

**PNEC:**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

- CONTINUED ON NEXT PAGE -



**Maston - Zinc Cold Galvanized, Zinc Aluminium  
400171, 400172**

Identification				
Zinc powder - zinc dust (stabilised) CAS: 7440-66-6 EC: 231-175-3	STP	0,1 mg/L	Fresh water	0,0206 mg/L
	Soil	106,8 mg/kg	Marine water	0,0061 mg/L
	Intermittent	Non-applicable	Sediment (Fresh water)	235,6 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	121 mg/kg
acetone CAS: 67-64-1 EC: 200-662-2	STP	100 mg/L	Fresh water	10,6 mg/L
	Soil	29,5 mg/kg	Marine water	1,06 mg/L
	Intermittent	21 mg/L	Sediment (Fresh water)	30,4 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	3,04 mg/kg
Xylene CAS: 1330-20-7 EC: 215-535-7	STP	6,58 mg/L	Fresh water	0,327 mg/L
	Soil	2,31 mg/kg	Marine water	0,327 mg/L
	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	STP	35,6 mg/L	Fresh water	0,18 mg/L
	Soil	0,09 mg/kg	Marine water	0,018 mg/L
	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,098 mg/kg
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	STP	100 mg/L	Fresh water	0,635 mg/L
	Soil	0,29 mg/kg	Marine water	0,064 mg/L
	Intermittent	6,35 mg/L	Sediment (Fresh water)	3,29 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,329 mg/kg
Butanone CAS: 78-93-3 EC: 201-159-0	STP	709 mg/L	Fresh water	55,8 mg/L
	Soil	22,5 mg/kg	Marine water	55,8 mg/L
	Intermittent	55,8 mg/L	Sediment (Fresh water)	284,74 mg/kg
	Oral	1 g/kg	Sediment (Marine water)	284,7 mg/kg
Cyclohexanone CAS: 108-94-1 EC: 203-631-1	STP	10 mg/L	Fresh water	0,033 mg/L
	Soil	0,03 mg/kg	Marine water	0,003 mg/L
	Intermittent	0,329 mg/L	Sediment (Fresh water)	0,249 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,025 mg/kg



**8.2 Exposure controls:**

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal. B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases, vapours and particles		EN 149:2001+A1:2009 EN 405:2002+A1:2010	Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	NON-disposable chemical protective gloves		EN ISO 374-1:2016+A1:2018 EN 16523-1:2015+A1:2018 EN 420:2004+A1:2010	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

- CONTINUED ON NEXT PAGE -

**Maston - Zinc Cold Galvanized, Zinc Aluminium  
400171, 400172**

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.



D.- Ocular and facial protection

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**





- CONTINUED ON NEXT PAGE -





**Maston - Zinc Cold Galvanized, Zinc Aluminium  
400171, 400172**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Face shield		EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer 's instructions. Use if there is a risk of splashing.

**E.- Body protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 139821:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer 's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties		EN ISO 13287:2013 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

**F.- Additional emergency measures**

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

**Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D **Volatile organic compounds:**

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	67,61 % weight
V.O.C. density at 20 °C:	626,07 kg/m <sup>3</sup> (626,07 g/L)
Average carbon number:	4,63
Average molecular weight:	79,49 g/mol

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 Information on basic physical and chemical properties:**

For complete information see the product datasheet. **Appearance:**

Physical state at 20 °C:	Aerosol		
Appearance:	Not available	Colour:	Not available
Odour threshold:	Non-applicable *		

**Volatility:**

Boiling point at atmospheric pressure:	-42 - 908 °C (Propellant)
Vapour pressure at 20 °C:	359970 Pa
Vapour pressure at 50 °C:	<300000 Pa (300 kPa)
Evaporation rate at 20 °C:	Non-applicable *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)**

- CONTINUED ON NEXT PAGE -

**Maston - Zinc Cold Galvanized, Zinc Aluminium  
400171, 400172**

**Product description:**

Density at 20 °C:	926 kg/m <sup>3</sup>
Relative density at 20 °C:	0,93
Dynamic viscosity at 20 °C:	Non-applicable * Kinematic viscosity at 20 °C:
	Non-applicable *
Kinematic viscosity at 40 °C:	Non-applicable *
Concentration:	Non-applicable * pH: Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	
Solubility properties:	Non-applicable * Decomposition temperature: Non-applicable * Melting point/freezing point: Non-applicable *
Recipient pressure:	359970 Pa (3,6 bar)
Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *

**Flammability:**

Flash Point:	-60 °C (Propellant)
Heat of combustion:	Non-applicable * Flammability (solid, gas): Non-applicable *
Autoignition temperature:	365 °C (Propellant)
Lower flammability limit:	0,8 % Volume
Upper flammability limit:	12 % Volume

**Explosive:**

Lower explosive limit:	Non-applicable *
Upper explosive limit:	Non-applicable *

**9.2 Other information:**

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

**SECTION 10: STABILITY AND REACTIVITY**

**10.1 Reactivity:**

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

**10.2 Chemical stability:**

Chemically stable under the conditions of storage, handling and use.

**10.3 Possibility of hazardous reactions:**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4 Conditions to avoid:**

Applicable for handling and storage at room temperature:

**Maston - Zinc Cold Galvanized, Zinc Aluminium  
400171, 400172**

**10.5**

Shock and friction	<input type="checkbox"/> Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	<input type="checkbox"/> Not applicable	Risk of combustion	Avoid direct impact	Not applicable

**Incompatible materials:**

Acids	<input type="checkbox"/> Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	<input type="checkbox"/> Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

**SECTION 10: STABILITY AND REACTIVITY (continued)**

**10.6 Hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

**SECTION 11: TOXICOLOGICAL INFORMATION**

**Maston - Zinc Cold Galvanized, Zinc Aluminium  
400171, 400172****11.1 Information on toxicological effects:**

The experimental information related to the toxicological properties of the product itself is not available **Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure: A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3. B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.

- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3. C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for skin contact. For more information see section 3. - Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.

IARC: Xylene (3); Cyclohexanone (3)

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3. E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.

- Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3. F- Specific target organ toxicity (STOT) - single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness. G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3. - Skin: Repeated exposure may cause skin dryness or cracking H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3. **Other information:** Non-applicable

**Specific toxicology information on the substances:****SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

- CONTINUED ON NEXT PAGE -

**Maston - Zinc Cold Galvanized, Zinc Aluminium  
400171, 400172**

Identification	Acute toxicity		Genus
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LD50 oral	12789 mg/kg	Rat
	LD50 dermal	14112 mg/kg	Rabbit
	LC50 inhalation	23,4 mg/L (4 h)	Rat
acetone CAS: 67-64-1 EC: 200-662-2	LD50 oral	5800 mg/kg	Rat
	LD50 dermal	7426 mg/kg	Rabbit
	LC50 inhalation	76 mg/L (4 h)	Rat
Xylene CAS: 1330-20-7 EC: 215-535-7	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg	Rat
	LC50 inhalation	11 mg/L (4 h) (ATEi)	
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	LD50 oral	8532 mg/kg	Rat
	LD50 dermal	5100 mg/kg	Rat
	LC50 inhalation	30 mg/L (4 h)	Rat
Butanone CAS: 78-93-3 EC: 201-159-0	LD50 oral	4000 mg/kg	Rat
	LD50 dermal	6400 mg/kg	Rabbit
	LC50 inhalation	23,5 mg/L (4 h)	Rat
Butane CAS: 106-97-8 EC: 203-448-7	LD50 oral	Non-applicable	
	LD50 dermal	Non-applicable	
	LC50 inhalation	658 mg/L (4 h)	Rat
Cyclohexanone CAS: 108-94-1 EC: 203-631-1	LD50 oral	2650 mg/kg	Rat
	LD50 dermal	3160 mg/kg	Rabbit
	LC50 inhalation	6,2 mg/L (4 h)	Rat

**SECTION 12: ECOLOGICAL INFORMATION**

- CONTINUED ON NEXT PAGE -

**Maston - Zinc Cold Galvanized, Zinc Aluminium  
400171, 400172**

The experimental information related to the eco-toxicological properties of the product itself is not available

**12.1 Toxicity:**

Identification	Acute toxicity		Species	Genus
	LC50	EC50		
Zinc powder - zinc dust (stabilised) CAS: 7440-66-6 EC: 231-175-3	LC50	0.31 mg/L (96 h)	N/A	Fish
	EC50	1.22 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	Non-applicable		
acetone CAS: 67-64-1 EC: 200-662-2	LC50	5540 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	8800 mg/L (48 h)	Daphnia pulex	Crustacean
	EC50	3400 mg/L (48 h)	Chlorella pyrenoidosa	Algae
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LC50	Non-applicable		
	EC50	Non-applicable		
	EC50	675 mg/L (72 h)	Scenedesmus subspicatus	Algae
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	LC50	161 mg/L (96 h)	Pimephales promelas	Fish
	EC50	481 mg/L (48 h)	Daphnia sp.	Crustacean
	EC50	Non-applicable		
Butanone CAS: 78-93-3 EC: 201-159-0	LC50	3220 mg/L (96 h)	Pimephales promelas	Fish
	EC50	5091 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	4300 mg/L (168 h)	Scenedesmus quadricauda	Algae
Cyclohexanone CAS: 108-94-1 EC: 203-631-1	LC50	527 mg/L (96 h)	Pimephales promelas	Fish
	EC50	800 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	370 mg/L (192 h)	Scenedesmus quadricauda	Algae

**12.2 Persistence and degradability:**

Identification	Degradability		Biodegradability	
	BOD5	COD	Concentration	Period
acetone CAS: 67-64-1 EC: 200-662-2	BOD5	Non-applicable	100 mg/L	
	COD	Non-applicable		28 days
	BOD5/COD	Non-applicable	% Biodegradable	96 %

**SECTION 12: ECOLOGICAL INFORMATION (continued)**

- CONTINUED ON NEXT PAGE -

**Maston - Zinc Cold Galvanized, Zinc Aluminium  
400171, 400172**

Identification	Degradability		Biodegradability	
			Concentration	Period
Xylene CAS: 1330-20-7 EC: 215-535-7	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	88 %
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	5 days
	BOD5/COD	Non-applicable	% Biodegradable	84 %
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	BOD5	Non-applicable	Concentration	785 mg/L
	COD	Non-applicable	Period	8 days
	BOD5/COD	Non-applicable	% Biodegradable	100 %
Butanone CAS: 78-93-3 EC: 201-159-0	BOD5	2,03 g O2/g	Concentration	Non-applicable
	COD	2,31 g O2/g	Period	20 days
	BOD5/COD	0,88	% Biodegradable	89 %
Cyclohexanone CAS: 108-94-1 EC: 203-631-1	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	87 %

**12.3 Bioaccumulative potential:**

Identification	Bioaccumulation potential	
	BCF	Pow Log
acetone CAS: 67-64-1 EC: 200-662-2	1	-0.24
	Low	
Butane CAS: 106-97-8 EC: 203-448-7	33	2.89
	Moderate	
Propane CAS: 74-98-6 EC: 200-827-9	13	2.86
	Low	
Xylene CAS: 1330-20-7 EC: 215-535-7	9	2.77
	Low	
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	4	1.78
	Low	
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	1	0.43
	Low	
Butanone CAS: 78-93-3 EC: 201-159-0	3	0.29
	Low	
Cyclohexanone CAS: 108-94-1	2	0.81

- CONTINUED ON NEXT PAGE -

**Maston - Zinc Cold Galvanized, Zinc Aluminium  
400171, 400172**

EC: 203-631-1

Potential

Low

**12.4 Mobility in soil:**

Identification	Absorption/desorption		Volatility	
acetone CAS: 67-64-1 EC: 200-662-2	Koc	1	Henry	2,93 Pa·m <sup>3</sup> /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2,304E-2 N/m (25 °C)	Moist soil	Yes
Butane CAS: 106-97-8 EC: 203-448-7	Koc	900	Henry	96258,75 Pa·m <sup>3</sup> /mol
	Conclusion	Low	Dry soil	Yes
	Surface tension	1,187E-2 N/m (25 °C)	Moist soil	Yes
Propane CAS: 74-98-6 EC: 200-827-9	Koc	460	Henry	71636,78 Pa·m <sup>3</sup> /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	7,02E-3 N/m (25 °C)	Moist soil	Yes

**SECTION 12: ECOLOGICAL INFORMATION (continued)**

- CONTINUED ON NEXT PAGE -



**Maston - Zinc Cold Galvanized, Zinc Aluminium  
400171, 400172**

Identification	Absorption/desorption		Volatility	
Xylene CAS: 1330-20-7 EC: 215-535-7	Koc	202	Henry	<input type="text"/> 524,86 Pa·m <sup>3</sup> /mol
	Conclusion	Moderate	Dry soil	<input type="text"/> Yes
	Surface tension	Non-applicable	Moist soil	<input type="text"/> Yes
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Koc	Non-applicable	Henry	<input type="text"/> Non-applicable
	Conclusion	Non-applicable	Dry soil	<input type="text"/> Non-applicable
	Surface tension	2,478E-2 N/m (25 °C)	Moist soil	<input type="text"/> Non-applicable
Butanone CAS: 78-93-3 EC: 201-159-0	Koc	30	Henry	<input type="text"/> 5,77 Pa·m <sup>3</sup> /mol
	Conclusion	Very High	Dry soil	<input type="text"/> Yes
	Surface tension	2,396E-2 N/m (25 °C)	Moist soil	<input type="text"/> Yes
Cyclohexanone CAS: 108-94-1 EC: 203-631-1	Koc	17	Henry	<input type="text"/> 9,119E-1 Pa·m <sup>3</sup> /mol
	Conclusion	Very High	Dry soil	<input type="text"/> Yes
	Surface tension	3,437E-2 N/m (25 °C)	Moist soil	<input type="text"/> Yes

**12.5 Results of PBT and vPvB assessment:**

Product fails to meet PBT/vPvB criteria

**12.6 Other adverse effects:**

Not described

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods:**

Code	Description	Waste class (Regulation (EU) No 1357/2014)
16 05 04*	gases in pressure containers (including halons) containing hazardous substances	Dangerous

**Type of waste (Regulation (EU) No 1357/2014):**

HP14 Ecotoxic, HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP4 Irritant — skin irritation and eye damage

**Waste management (disposal and evaluation):**

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue.

We do not recommended disposal down the drain. See paragraph 6.2. **Regulations**

**related to waste management:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

**SECTION 14: TRANSPORT INFORMATION**

**Transport of dangerous goods by land:** With regard to ADR 2021 and RID 2021:

**SECTION 14: TRANSPORT INFORMATION (continued)**

**Maston - Zinc Cold Galvanized, Zinc Aluminium  
400171, 400172**



**14.1 UN number:** UN1950  
**14.2 UN proper shipping name:** AEROSOLS, flammable  
**14.3 Transport hazard class(es):** 2  
 Labels: 2.1  
**14.4 Packing group:** N/A  
**14.5 Environmental hazards:** Yes  
**14.6 Special precautions for user**  
 Special regulations: 190, 327, 344, 625  
 Tunnel restriction code: D  
 Physico-Chemical properties: see section 9  
 Limited quantities: 1 L  
**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

**Transport of dangerous goods by sea:**

With regard to IMDG 39-18:



**14.1 UN number:** UN1950  
**14.2 UN proper shipping name:** AEROSOLS, flammable  
**14.3 Transport hazard class(es):** UN1950  
 Labels: AEROSOLS, flammable  
**14.4 Packing group:** 2  
**14.5 Marine pollutant:** 2.1  
**14.6 Special precautions for user** N/A  
 Special regulations: Yes  
 EmS Codes:  
 Physico-Chemical properties: 63, 959, 190, 277, 327, 344  
 Limited quantities: F-D, S-U see section 9  
 Segregation group: section 9  
**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** 1 L  
 Non-applicable  
 Non-applicable

**Transport of dangerous goods by air:**

With regard to IATA/ICAO 2021:



**14.1 UN number:** UN1950  
**14.2 UN proper shipping name:** AEROSOLS, flammable  
**14.3 Transport hazard class(es):** 2  
 Labels: 2.1  
**14.4 Packing group:** N/A  
**14.5 Environmental hazards:** Yes  
**14.6 Special precautions for user**  
 Physico-Chemical properties: see section 9 Non-applicable  
**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:**

**SECTION 15: REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable  
 Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable  
 Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable  
 Article 95, REGULATION (EU) No 528/2012: Non-applicable  
 REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

**SECTION 15: REGULATORY INFORMATION (continued)**

- CONTINUED ON NEXT PAGE -

**Maston - Zinc Cold Galvanized, Zinc Aluminium  
400171, 400172**

**Seveso III:**

Section	Description	Lower-tier requirements	Upper-tier requirements
P3a	FLAMMABLE AEROSOLS	150	500
E1	ENVIRONMENTAL HAZARDS	100	200

**Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):**

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors: Contains acetone. Product under the provisions of Article 9.

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

**Specific provisions in terms of protecting people or the environment:**

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

**Other legislation:**

The product could be affected by sectorial legislation

**15.2 Chemical safety assessment:**

The supplier has not carried out evaluation of chemical safety.

**SECTION 16: OTHER INFORMATION**

**Legislation related to safety data sheets:**

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830).

**Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:**

Non-applicable

**Texts of the legislative phrases mentioned in section 2:**

- H336: May cause drowsiness or dizziness.
- H400: Very toxic to aquatic life.
- H410: Very toxic to aquatic life with long lasting effects.
- H229: Pressurised container: May burst if heated.
- H222: Extremely flammable aerosol.
- H319: Causes serious eye irritation.

**Texts of the legislative phrases mentioned in section 3:**

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3 **CLP Regulation (EC) No 1272/2008:**

- Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.
- Acute Tox. 4: H332 - Harmful if inhaled.
- Aquatic Acute 1: H400 - Very toxic to aquatic life.
- Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.
- Eye Irrit. 2: H319 - Causes serious eye irritation.
- Flam. Gas 1A: H220 - Extremely flammable gas.
- Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
- Flam. Liq. 3: H226 - Flammable liquid and vapour.
- Press. Gas: H280 - Contains gas under pressure, may explode if heated.
- Skin Irrit. 2: H315 - Causes skin irritation.
- STOT SE 3: H336 - May cause drowsiness or dizziness.

**Classification procedure:**

**Maston - Zinc Cold Galvanized, Zinc Aluminium**  
**400171, 400172****SECTION 16: OTHER INFORMATION (continued)**

STOT SE 3: Calculation method  
Aquatic Acute 1: Calculation method  
Aquatic Chronic 1: Calculation method  
Aerosol 1: Calculation method  
Aerosol 1: Calculation method  
Eye Irrit. 2: Calculation method

**Advice related to training:**

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. **Principal**

**bibliographical sources:** <http://echa.europa.eu> <http://eur-lex.europa.eu>

**Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road  
IMDG: International maritime dangerous goods code  
IATA: International Air Transport Association  
ICAO: International Civil Aviation Organisation  
COD: Chemical Oxygen Demand  
BOD5: 5-day biochemical oxygen demand  
BCF: Bioconcentration factor  
LD50: Lethal Dose 50  
LC50: Lethal Concentration 50  
EC50: Effective concentration 50  
Log-POW: Octanol-water partition coefficient  
Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -