



**CAR-REP - Heat resistant spray paint 250C-650C -
Kuumakestomaali Spray
cr01113, cr01090, cr01091, cr01092, cr01093**

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 **Product identifier:** CAR-REP - Heat resistant spray paint 250C-650C -
Kuumakestomaali Spray cr01113, cr01090, cr01091, cr01092, cr01093

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Paint

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Spray Shop Supplies Pty Ltd
38 Cyber Loop, Dandenong South,
Victoria, Australia.

Phone.: +61 3 9799 2007

Fax: +61 9799 6568

orders@sprayshopsupplies.com.au
www.sprayshopsupplies.com.au

1.4 Emergency telephone number: (8:00-16:00)+61 3 9799 2007

SECTION 2: HAZARDS IDENTIFICATION **

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aerosol 1: Pressurised container: May burst if heated., H229

Aerosol 1: Flammable aerosols, Category 1, H222

Eye Irrit. 2: Eye irritation, Category 2, H319

STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger



Hazard statements:

Aerosol 1: H229 - Pressurised container: May burst if heated

Aerosol 1: H222 - Extremely flammable aerosol

Eye Irrit. 2: H319 - Causes serious eye irritation

STOT SE 3: H336 - May cause drowsiness or dizziness

Precautionary statements: P102: Keep out of reach of children

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P211: Do not spray on an open flame or other ignition source

P251: Do not pierce or burn, even after use

P260: Do not breathe spray

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F

Supplementary information:

EUH066: Repeated exposure may cause skin dryness or cracking **Substances that contribute to the classification** acetone (CAS: 67-64-1); N-butyl acetate (CAS: 123-86-4); naphtha (petroleum), hydrodesulphurized heavy, < 0.1 % EC 200753-7 (CAS: 64742-82-1)

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria
DK Mal-code 4-1

** Changes with regards to the previous version

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

- CONTINUED ON NEXT PAGE -

**CAR-REP - Heat resistant spray paint 250C-650C -
Kuumakestomaali Spray
cr01113, cr01090, cr01091, cr01092, cr01093**

3.1 Substance:







Non-applicable

3.2 Mixture:

Chemical description: Aerosol

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 67-64-1 EC: 200-662-2 Index: 606-001-00-8 REACH: 01-2119471330-49XXXX	acetone⁽¹⁾ ATP CLP00	30 - <50 %
	Regulation 1272/2008 Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger 	
CAS: 106-97-8 EC: 203-448-7 Index: 601-004-00-0 REACH: 01-2119474691-32XXXX	Butane⁽¹⁾ ATP CLP00	10 - <20 %
	Regulation 1272/2008 Flam. Gas 1A: H220; Press. Gas: H280 - Danger 	
CAS: 74-98-6 EC: 200-827-9 Index: 601-003-00-5 REACH: 01-2119486944-21XXXX	Propane⁽¹⁾ ATP CLP00	10 - <20 %
	Regulation 1272/2008 Flam. Gas 1A: H220; Press. Gas: H280 - Danger 	
CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH: 01-2119485493-29XXXX	N-butyl acetate⁽¹⁾ ATP CLP00	5 - <10 %
	Regulation 1272/2008 Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning 	
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32XXXX	Xylene⁽¹⁾ ATP CLP00	5 - <10 %
	Regulation 1272/2008 Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning 	
CAS: 64742-82-1 EC: 265-185-4 Index: 649-330-00-2 REACH: 01-2119490979-12XXXX	naphtha (petroleum), hydrodesulphurized heavy, < 0.1 % EC 200-753-7⁽¹⁾ ATP ATP0	1 - <2,5 %
	Regulation 1272/2008 Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Danger 	

⁽¹⁾ Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product. **By inhalation:**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance. **By skin contact:**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection. **By eye contact:**

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

- CONTINUED ON NEXT PAGE -



**CAR-REP - Heat resistant spray paint 250C-650C -
Kuumakestomaali Spray
cr01113, cr01090, cr01091, cr01092, cr01093**

SECTION 4: FIRST AID MEASURES (continued)

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed: Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂).

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC. **Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8).

Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

Avoid spillage into the aquatic environment as it contains substances potentially dangerous for this. Contain the product absorbed in hermetically sealed containers. In the case of serious spillage into the aquatic environment notify the relevant authority.

6.3 Methods and material for containment and cleaning up: It is

recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections: See

sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling: A.-

Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Avoid splashes and pulverizations. Consult section 10 for conditions and materials that should be avoided.

- CONTINUED ON NEXT PAGE -

**CAR-REP - Heat resistant spray paint 250C-650C -
Kuumakestomaali Spray
cr01113, cr01090, cr01091, cr01092, cr01093**

SECTION 7: HANDLING AND STORAGE (continued)

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

- Minimum Temp.: 5 °C
- Maximum Temp.: 50 °C
- Maximum time: 60 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace

Identification		Occupational exposure limits		
acetone CAS: 67-64-1 EC: 200-662-2	IOELV (8h)	500 ppm	1210 mg/m ³	
	IOELV (STEL)			
Xylene CAS: 1330-20-7 EC: 215-535-7	IOELV (8h)	50 ppm	221 mg/m ³	
	IOELV (STEL)	100 ppm	442 mg/m ³	

DNEL (Workers):

Identification		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
acetone CAS: 67-64-1 EC: 200-662-2	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	186 mg/kg	Non-applicable
	Inhalation	Non-applicable	2420 mg/m ³	1210 mg/m ³	Non-applicable
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	960 mg/m ³	960 mg/m ³	480 mg/m ³	480 mg/m ³
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
	Inhalation	289 mg/m ³	289 mg/m ³	77 mg/m ³	Non-applicable

DNEL (General population):

Identification		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
acetone CAS: 67-64-1 EC: 200-662-2	Oral	Non-applicable	Non-applicable	62 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	62 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	200 mg/m ³	Non-applicable
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	859,7 mg/m ³	859,7 mg/m ³	102,34 mg/m ³	102,34 mg/m ³

- CONTINUED ON NEXT PAGE -



**CAR-REP - Heat resistant spray paint 250C-650C -
Kuumakestomaali Spray
cr01113, cr01090, cr01091, cr01092, cr01093**

Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	108 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	14,8 mg/m ³	Non-applicable

PNEC:

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

- CONTINUED ON NEXT PAGE -



**CAR-REP - Heat resistant spray paint 250C-650C -
Kuumakestomaali Spray
cr01113, cr01090, cr01091, cr01092, cr01093**

Identification				
acetone CAS: 67-64-1 EC: 200-662-2	STP	100 mg/L	Fresh water	10,6 mg/L
	Soil	29,5 mg/kg	Marine water	1,06 mg/L
	Intermittent	21 mg/L	Sediment (Fresh water)	30,4 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	3,04 mg/kg
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	STP	35,6 mg/L	Fresh water	0,18 mg/L
	Soil	0,0903 mg/kg	Marine water	0,018 mg/L
	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,0981 mg/kg
Xylene CAS: 1330-20-7 EC: 215-535-7	STP	6,58 mg/L	Fresh water	0,327 mg/L
	Soil	2,31 mg/kg	Marine water	0,327 mg/L
	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg

8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands Non-applicable

D.- Ocular and facial protection Non-applicable

E.- Body protection Non-applicable

F.- Additional emergency measures

It is not necessary to take additional emergency measures.

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D **Volatile organic compounds:**

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	87,73 % weight
V.O.C. density at 20 °C:	629,9 kg/m ³ (629,9 g/L)
Average carbon number:	4,11
Average molecular weight:	72,6 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C: Aerosol

Appearance: Not available

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

- CONTINUED ON NEXT PAGE -



**CAR-REP - Heat resistant spray paint 250C-650C -
Kuumakestomaali Spray
cr01113, cr01090, cr01091, cr01092, cr01093**

Colour:	Not available	Odour:	Not available
Odour threshold:	Non-applicable *		
Volatility:			
Boiling point at atmospheric pressure:	-42 - 150 °C (Propellant)		
Vapour pressure at 20 °C:	359970 Pa		
Vapour pressure at 50 °C:	<300000 Pa (300 kPa)		
Evaporation rate at 20 °C:	Non-applicable *		
Product description:			
Density at 20 °C:	718 kg/m ³		
Relative density at 20 °C:	0,72		
Dynamic viscosity at 20 °C:	Non-applicable *	Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	Non-applicable *		
Concentration:	Non-applicable *	pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *		
Partition coefficient n-octanol/water 20 °C:	Non-applicable *		
Solubility in water at 20 °C:	Non-applicable *	Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *		
Melting point/freezing point:	Non-applicable *		
Recipient pressure:	359970 Pa (3,6 bar)		
Explosive properties:	Non-applicable *		
Oxidising properties:	Non-applicable *		
Flammability:			
Flash Point:	-60 °C (Propellant)		
Flammability (solid, gas):	Non-applicable *		
Autoignition temperature:	365 °C (Propellant)		
Lower flammability limit:	0,8 % Volume		
Upper flammability limit:	12 % Volume		
Explosive:			
Lower explosive limit:	Non-applicable *		
Upper explosive limit:	Non-applicable *		
9.2 Other information:			
Surface tension at 20 °C:	Non-applicable *		
Refraction index:	Non-applicable *		

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

SECTION 10: STABILITY AND REACTIVITY (continued)

- CONTINUED ON NEXT PAGE -



**CAR-REP - Heat resistant spray paint 250C-650C -
Kuumakestomaali Spray
cr01113, cr01090, cr01091, cr01092, cr01093**

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

10.5	Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
	Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

Incompatible materials:

10.6 Haz	Acids	Water	Oxidising materials	Combustible materials	Others
	Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available **Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure: A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3. B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.

- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3. C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for skin contact. For more information see section 3. - Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.

IARC: Xylene (3)

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3. E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.

- Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3. F- Specific target organ toxicity (STOT) - single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- CONTINUED ON NEXT PAGE -

**CAR-REP - Heat resistant spray paint 250C-650C -
Kuumakestomaali Spray
cr01113, cr01090, cr01091, cr01092, cr01093**

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3. - Skin: Repeated exposure may cause skin dryness or cracking H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3. **Other information:** Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
	Route	Dose	
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LD50 oral	12789 mg/kg	Rat
	LD50 dermal	14112 mg/kg	Rabbit
	LC50 inhalation	23,4 mg/L (4 h)	Rat
acetone CAS: 67-64-1 EC: 200-662-2	LD50 oral	5800 mg/kg	Rat
	LD50 dermal	7426 mg/kg	Rabbit
	LC50 inhalation	76 mg/L (4 h)	Rat
Xylene CAS: 1330-20-7 EC: 215-535-7	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg (ATEi)	Rat
	LC50 inhalation	11 mg/L (4 h) (ATEi)	
naphtha (petroleum), hydrodesulphurized heavy , < 0.1 % EC 200-753-7 CAS: 64742-82-1 EC: 265-185-4	LD50 oral	5100 mg/kg	Rat
	LD50 dermal	3160 mg/kg	Rabbit
	LC50 inhalation	12 mg/L (4 h)	Rat
Butane CAS: 106-97-8 EC: 203-448-7	LD50 oral	Non-applicable	
	LD50 dermal	Non-applicable	
	LC50 inhalation	658 mg/L (4 h)	Rat

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Identification	Route	Acute toxicity	Species	Genus
acetone CAS: 67-64-1 EC: 200-662-2	LC50	5540 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	23.5 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	3400 mg/L (48 h)	Chlorella pyrenoidosa	Algae
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LC50	62 mg/L (96 h)	Leuciscus idus	Fish
	EC50	73 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	675 mg/L (72 h)	Scenedesmus subspicatus	Algae
Xylene CAS: 1330-20-7 EC: 215-535-7	LC50	13.5 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	3.4 mg/L (48 h)	Ceriodaphnia dubia	Crustacean
	EC50	10 mg/L (72 h)	Skeletonema costatum	Algae
naphtha (petroleum), hydrodesulphurized heavy , < 0.1 % EC 200-753-7 CAS: 64742-82-1 EC: 265-185-4	LC50	Non-applicable		
	EC50	4.3 mg/L (96 h)	Crangon crangon	Crustacean
	EC50	Non-applicable		

12.2 Persistence and degradability:

Identification	Degradability	Biodegradability

- CONTINUED ON NEXT PAGE -



**CAR-REP - Heat resistant spray paint 250C-650C -
Kuumakestomaali Spray
cr01113, cr01090, cr01091, cr01092, cr01093**

acetone CAS: 67-64- 1 EC: 200-662-2	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	0.96	% Biodegradable	96 %

SECTION 12: ECOLOGICAL INFORMATION (continued)

- CONTINUED ON NEXT PAGE -

**CAR-REP - Heat resistant spray paint 250C-650C -
Kuumakestomaali Spray
cr01113, cr01090, cr01091, cr01092, cr01093**

Identification	Degradability		Biodegradability	
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	5 days
	BOD5/COD	0.79	% Biodegradable	84 %
Xylene CAS: 1330-20-7 EC: 215-535-7	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	88 %

12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential	
acetone CAS: 67-64-1 EC: 200-662-2	BCF	1
	Pow Log	-0.24
	Potential	Low
Butane CAS: 106-97-8 EC: 203-448-7	BCF	33
	Pow Log	2.89
	Potential	Moderate
Propane CAS: 74-98-6 EC: 200-827-9	BCF	13
	Pow Log	2.86
	Potential	Low
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	BCF	4
	Pow Log	1.78
	Potential	Low
Xylene CAS: 1330-20-7 EC: 215-535-7	BCF	9
	Pow Log	2.77
	Potential	Low
naphtha (petroleum), hydrodesulphurized heavy, < 0.1 % EC 200-753-7 CAS: 64742-82-1 EC: 265-185-4	BCF	645
	Pow Log	4
	Potential	High

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
acetone CAS: 67-64-1 EC: 200-662-2	Koc	1	Henry	2,93 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2,304E-2 N/m (25 °C)	Moist soil	Yes
Butane CAS: 106-97-8 EC: 203-448-7	Koc	900	Henry	96258,75 Pa·m ³ /mol
	Conclusion	Low	Dry soil	Yes
	Surface tension	1,187E-2 N/m (25 °C)	Moist soil	Yes
Propane CAS: 74-98-6 EC: 200-827-9	Koc	460	Henry	71636,78 Pa·m ³ /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	7,02E-3 N/m (25 °C)	Moist soil	Yes
N-butyl acetate	Koc	Non-applicable	Henry	Non-applicable

- CONTINUED ON NEXT PAGE -



**CAR-REP - Heat resistant spray paint 250C-650C -
Kuumakestomaali Spray
cr01113, cr01090, cr01091, cr01092, cr01093**

CAS: 123-86-4 EC: 204-658-1	Conclusion	Non-applicable	Dry soil <input type="checkbox"/>	Non-applicable
	Surface tension	2,478E-2 N/m (25 °C)	Moist soil <input type="checkbox"/>	Non-applicable
Xylene CAS: 1330-20-7 EC: 215-535-7	Koc	202	Henry <input type="checkbox"/>	524,86 Pa·m ³ /mol
	Conclusion	Moderate	Dry soil <input type="checkbox"/>	Yes
	Surface tension	Non-applicable	Moist soil <input type="checkbox"/>	Yes

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

- CONTINUED ON NEXT PAGE -

**CAR-REP - Heat resistant spray paint 250C-650C -
Kuumakestomaali Spray
cr01113, cr01090, cr01091, cr01092, cr01093**

SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Code	Description	Waste class (Regulation (EU) No 1357/2014)
16 05 04*	gases in pressure containers (including halons) containing hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP4 Irritant — skin irritation and eye damage **Waste management (disposal and evaluation):**

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2. **Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2019 and RID 2019:



14.1 UN number:

14.2 UN proper shipping name:

14.3 Transport hazard class(es):

Labels:

14.4 Packing group:

14.5 Environmental hazards:

14.6 Special precautions for user Special regulations:

Tunnel restriction code:

Physico-Chemical properties:

Limited quantities:

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:

UN1950

AEROSOLS, flammable

2

2.1

N/A

No

190, 327, 344, 625

D

see section 9

1 L

Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 39-18:



14.1 UN number:

14.2 UN proper shipping name:

14.3 Transport hazard class(es):

Labels:

14.4 Packing group:

14.5 Environmental hazards:

14.6 Special precautions for user Special regulations:

EmS Codes:

Physico-Chemical properties:

Limited quantities:

Segregation group:

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:

UN1950

AEROSOLS, flammable

2

2.1

N/A

No

63, 959, 190, 277, 327, 344

F-D, S-U see

section 9

1 L

Non-applicable

Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2020:

- CONTINUED ON NEXT PAGE -

**CAR-REP - Heat resistant spray paint 250C-650C -
Kuumakestomaali Spray
cr01113, cr01090, cr01091, cr01092, cr01093**

SECTION 14: TRANSPORT INFORMATION (continued)



14.1 UN number:	UN1950
14.2 UN proper shipping name:	AEROSOLS, flammable
14.3 Transport hazard class(es):	2
Labels:	2.1
14.4 Packing group:	N/A
	No
14.5 Environmental hazards:	
14.6 Special precautions for user	see section 9 Non-
Physico-Chemical properties:	applicable
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:	

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable
Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable
Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable
Article 95, REGULATION (EU) No 528/2012: Non-applicable
REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable **Seveso III:**

Section	Description	Lower-tier requirements	Upper-tier requirements
P3a		150	500

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Regulation (EU) No 98/2013 of the European Parliament and of the Council of 15 January 2013 on the marketing and use of explosives precursors: Contains acetone. Product under the provisions of Article 9 Shall not be used in:
—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
—tricks and jokes,
—games for one or more participants, or any article intended to be used as such, even with ornamental aspects. **Specific provisions in terms of protecting people or the environment:**

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.: CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- Precautionary statements

Texts of the legislative phrases mentioned in section 2:



**CAR-REP - Heat resistant spray paint 250C-650C -
Kuumakestomaali Spray
cr01113, cr01090, cr01091, cr01092, cr01093**

SECTION 16: OTHER INFORMATION (continued)

H336: May cause drowsiness or dizziness
H229: Pressurised container: May burst if heated
H222: Extremely flammable aerosol
H319: Causes serious eye irritation

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3 **CLP Regulation (EC) No 1272/2008:**

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways
Eye Irrit. 2: H319 - Causes serious eye irritation
Flam. Gas 1A: H220 - Extremely flammable gas
Flam. Liq. 2: H225 - Highly flammable liquid and vapour
Flam. Liq. 3: H226 - Flammable liquid and vapour
Press. Gas: H280 - Contains gas under pressure, may explode if heated
Skin Irrit. 2: H315 - Causes skin irritation
STOT SE 3: H336 - May cause drowsiness or dizziness

Classification procedure:

STOT SE 3: Calculation method
Aerosol 1: Calculation method
Aerosol 1: Calculation method
Eye Irrit. 2: Calculation method

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. **Principal**

bibliographical sources: <http://echa.europa.eu> <http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5-day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
Log-POW: Octanol-water partition coefficient
Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -