

V2018 ULTIMATE RAPID DRYING HS 4:1
V2018 ANTICORROSIVE RAPID DRYING HS 5:1


Date of compilation:02.08.2017 Date
of revision: 14.11.2018
Version:2

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** V2018 ULTIMATE RAPID DRYING HS 4:1
V2018 ANTICORROSIVE RAPID DRYING HS 5:1
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Car repair. For professional user only.
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
Spray Shop Supplies Pty Ltd
38 Cyber Loop,
Dandenong South, Victoria, 3175, Australia.
Ph: +61 3 9799 2007
Email: orders@autorepairsdirect.com.au
- 1.4 Emergency telephone number:** +61 3 9799 2007 (8am-4:30pm)

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
CLP Regulation (EC) No 1272/2008:
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412
Flam. Liq. 3: Flammable liquids, Category 3, H226
- 2.2 Label elements:**
CLP Regulation (EC) No 1272/2008:
Warning



V2018 ULTIMATE RAPID DRYING HS 4:1
V2018 ANTICORROSIVE RAPID DRYING HS 5:1

Hazard statements:

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects

Flam. Liq. 3: H226 - Flammable liquid and vapour

Precautionary statements:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P260: Do not breathe dust/fume/gas/mist/vapours/spray

P271: Use only outdoors or in a well-ventilated area

P280: Wear protective gloves/protective clothing/eye protection/face protection

P302+P352: IF ON SKIN: Wash with plenty of water

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively

Supplementary information:

EUH208: Contains Dibutyltin Dilaurate. May produce an allergic reaction

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of chemical products


Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Safety data sheet
According to 1907/2006/EC (REACH), 2015/830/EU

V2018 ULTIMATE RAPID DRYING HS 4:1
V2018 ANTICORROSIVE RAPID DRYING HS 5:1



- CONTINUED ON NEXT PAGE -

V2018 ULTIMATE RAPID DRYING HS 4:1
V2018 ANTICORROSIVE RAPID DRYING HS 5:1

Identification	Chemical name/Classification	Concentration
CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH:01-2119485493-29-XXXX	N-butyl acetate⁽¹⁾ ATP CLP03	5 - <10 %
	Regulation 1272/2008 Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning	
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH:01-2119488216-32-XXXX	Xylene⁽¹⁾ Self-classified c	5 - <10 %
	Regulation 1272/2008 Acute Tox. 4: H312+H332; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	
CAS: 108-65-6 EC: 203-603-9 Index: 607-195-00-7 REACH:01-2119475791-29-XXXX	2-methoxy-1-methyl ethyl acetate⁽²⁾ ATP (TP01)	5 - <10 %
	Regulation 1272/2008 Flam. Liq. 3: H226 - Warning	
CAS: 78-93-3 EC: 201-159-0 Index: 606-002-00-3 REACH:01-2119457290-43-XXXX	2-butanone⁽¹⁾ ATP (LP0)	1 - <2 %
	Regulation 1272/2008 Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	
CAS: 7779-90-0 EC: 231-944-3 Index: Non-applicable REACH:01-2119485044-40-XXXX	Triethyl phosphate⁽¹⁾ ATP CLP03	<1 %
	Regulation 1272/2008 Aquatic Acute 1: H400; Aquatic Chronic 1: H410 - Warning	

- CONTINUED ON NEXT PAGE -

V2018 ULTIMATE RAPID DRYING HS 4:1
V2018 ANTICORROSIVE RAPID DRYING HS 5:1

CAS: 77-58-7 EC: 201-039-8 Index: 050-030-00-3 REACH:01-2119496068-27-	Dibutyltin Dilaurate⁽¹⁾	Self-classified	<1 %
	Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Muta. 2: H341; Repr. 1B: H360; Skin Corr. 1C: H314; Skin Sens. 1: H317; STOT RE 1: H372; STOT SE 1: H370 - Danger	

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830 exposure limit

⁽²⁾ Substance with a Union workplace

To obtain more information on the hazards of the substances consult sections 8, 11, 12, 15 and 16.

SECTION 4: FIRST AID MEASURES

4.1

Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2


Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

V2018 ULTIMATE RAPID DRYING HS 4:1
V2018 ANTICORROSIVE RAPID DRYING HS 5:1



SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

SECTION 5: FIREFIGHTING MEASURES (continued)

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂). IT IS RECOMMENDED NOT to use tap water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use

full protective clothing and self-contained breathing apparatus

(SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

V2018 ULTIMATE RAPID DRYING HS 4:1
V2018 ANTICORROSIVE RAPID DRYING HS 5:1

6.1 Personal precautions, protective equipment and emergency procedures:	Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.
6.2 Environmental precautions:	Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.
6.3 Methods and material for containment and cleaning up:	It is recommended:
	Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.
6.4 Reference to other sections:	See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:	A.- Precautions for safe manipulation
	Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.
	B.- Technical recommendations for the prevention of fires and explosions
	Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 94/9/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.
	C.- Technical recommendations to prevent ergonomic and toxicological risks
	Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.
	D.- Technical recommendations to prevent environmental risks
	Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.
7.2 Conditions for safe storage, including any incompatibilities:	

SECTION 7: HANDLING AND STORAGE (continued)

	A.- Technical measures for storage
Minimum Temp.:	15 °C
Maximum Temp.:	25 °C
Maximum time:	12 Months
	B.- General conditions for storage
	Avoid sources of heat, radiation, static electricity and contact with food.
For additional information see subsection 10.5	
7.3 Specific end use(s):	

Safety data sheet

According to 1907/2006/EC (REACH), 2015/830/EU

V2018 ULTIMATE RAPID DRYING HS 4:1
V2018 ANTICORROSIVE RAPID DRYING HS 5:1

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace

Identification	Environmental limits		
2-butanone CAS: 78-93-3 EC: 201-159-0	IOELV (8h)	200 ppm	600 mg/m ³
	IOELV (STEL)	300 ppm	900 mg/m ³
Dibutyltin Dilaurate CAS: 77-58-7 EC: 201-039-8	IOELV (8h)		
	IOELV (STEL)		
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	IOELV (8h)	50 ppm	275 mg/m ³
	IOELV (STEL)	100 ppm	550 mg/m ³
Xylene CAS: 1330-20-7 EC: 215-535-7	IOELV (8h)	50 ppm	221 mg/m ³
	IOELV (STEL)	100 ppm	442 mg/m ³

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	945 - 975 mg/m ³	945 - 975 mg/m ³	465 - 495 mg/m ³	465 - 495 mg/m ³
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	165 - 195 mg/kg	Non-applicable
	Inhalation	274 - 304 mg/m ³	274 - 304 mg/m ³	62 - 92 mg/m ³	Non-applicable
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	138,5 - 168,5 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	260 - 290 mg/m ³	Non-applicable
2-butanone CAS: 78-93-3 EC: 201-159-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	1146 - 1176 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	585 - 615 mg/m ³	Non-applicable
trizinc bis(orthophosphate) CAS: 7779-90-0 EC: 231-944-3	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	68 - 98 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	-10 - 20 mg/m ³	Non-applicable
Dibutyltin Dilaurate CAS: 77-58-7 EC: 201-039-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	-14 - 16 mg/kg	Non-applicable	-14,8 - 15,2 mg/kg	Non-applicable
	Inhalation	-14,93 - 15,07 mg/m ³	Non-applicable	-14,99 - 15,01 mg/m ³	Non-applicable

DNEL (General population):

V2018 ULTIMATE RAPID DRYING HS 4:1
V2018 ANTICORROSIVE RAPID DRYING HS 5:1

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	844,7 - 874,7 mg/m ³	844,7 - 874,7 mg/m ³	87,34 - 117,34 mg/m ³	87,34 - 117,34 mg/m ³

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Safety data sheet

According to 1907/2006/EC (REACH), 2015/830/EU

V2018 ULTIMATE RAPID DRYING HS 4:1
V2018 ANTICORROSIVE RAPID DRYING HS 5:1

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	-13,4 - 16,6 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	93 - 123 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	-0,2 - 29,8 mg/m ³	Non-applicable
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Oral	Non-applicable	Non-applicable	-13,33 - 16,67 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	39,8 - 69,8 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	18 - 48 mg/m ³	Non-applicable
2-butanone CAS: 78-93-3 EC: 201-159-0	Oral	Non-applicable	Non-applicable	16 - 46 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	397 - 427 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	91 - 121 mg/m ³	Non-applicable
trizinc bis(orthophosphate) CAS: 7779-90-0 EC: 231-944-3	Oral	Non-applicable	Non-applicable	-14,17 - 15,83 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	68 - 98 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	-12,5 - 17,5 mg/m ³	Non-applicable
Dibutyltin Dilaurate CAS: 77-58-7 EC: 201-039-8	Oral	-14,99 - 15,01 mg/kg	Non-applicable	-15 - 15 mg/kg	Non-applicable
	Dermal	-14,5 - 15,5 mg/kg	Non-applicable	-14,92 - 15,08 mg/kg	Non-applicable
	Inhalation	-14,98 - 15,02 mg/m ³	Non-applicable	-15 - 15 mg/m ³	Non-applicable

PNEC:

Identification					
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	STP	20,6 - 50,6 mg/L	Fresh water	-14,82 - 15,18 mg/L	
	Soil	-14,91 - 15,09 mg/kg	Marine water	-14,98 - 15,02 mg/L	
	Intermittent	-14,64 - 15,36 mg/L	Sediment (Fresh water)	-14,02 - 15,98 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	-14,9 - 15,1 mg/kg	
Xylene CAS: 1330-20-7 EC: 215-535-7	STP	-8,42 - 21,58 mg/L	Fresh water	-14,67 - 15,33 mg/L	
	Soil	-12,69 - 17,31 mg/kg	Marine water	-14,67 - 15,33 mg/L	
	Intermittent	-14,67 - 15,33 mg/L	Sediment (Fresh water)	-2,54 - 27,46 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	-2,54 - 27,46 mg/kg	
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	STP	85 - 115 mg/L	Fresh water	-14,37 - 15,64 mg/L	
	Soil	-14,71 - 15,29 mg/kg	Marine water	-14,94 - 15,06 mg/L	
	Intermittent	-8,65 - 21,35 mg/L	Sediment (Fresh water)	-11,71 - 18,29 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	-14,67 - 15,33 mg/kg	
2-butanone CAS: 78-93-3 EC: 201-159-0	STP	694 - 724 mg/L	Fresh water	40,8 - 70,8 mg/L	
	Soil	7,5 - 37,5 mg/kg	Marine water	40,8 - 70,8 mg/L	
	Intermittent	40,8 - 70,8 mg/L	Sediment (Fresh water)	269,74 - 299,74 mg/kg	
	Oral	985 - 1015 g/kg	Sediment (Marine water)	269,7 - 299,7 mg/kg	
trizinc bis(orthophosphate) CAS: 7779-90-0 EC: 231-944-3	STP	-14,9 - 15,1 mg/L	Fresh water	-14,98 - 15,02 mg/L	
	Soil	20,6 - 50,6 mg/kg	Marine water	-14,99 - 15,01 mg/L	
	Intermittent	Non-applicable	Sediment (Fresh water)	102,8 - 132,8 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	41,5 - 71,5 mg/kg	
Dibutyltin Dilaurate CAS: 77-58-7 EC: 201-039-8	STP	85 - 115 mg/L	Fresh water	-15 - 15 mg/L	
	Soil	Non-applicable	Marine water	-15 - 15 mg/L	
	Intermittent	-15 - 15 mg/L	Sediment (Fresh water)	Non-applicable	
	Oral	-14,8 - 15,2 g/kg	Sediment (Marine water)	Non-applicable	

- CONTINUED ON NEXT PAGE -

V2018 ULTIMATE RAPID DRYING HS 4:1
V2018 ANTICORROSIVE RAPID DRYING HS 5:1**8.2 Exposure controls:**

A.- General security and hygiene measures in the work place

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

- CONTINUED ON NEXT PAGE -

Safety data sheet







































According to 1907/2006/EC (REACH), 2015/830/EU

V2018 ULTIMATE RAPID DRYING HS 4:1
V2018 ANTICORROSIVE RAPID DRYING HS 5:1




















As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours (A)	                                      	EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	NON-disposable chemical protective gloves (NBR), Breakthrough Time 480 min, thickness 0.4 mm	                   	EN 374-1:2003 EN 374-3:2003/AC:2006 EN 420:2003+A1:2009	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

V2018 ULTIMATE RAPID DRYING HS 4:1
V2018 ANTICORROSIVE RAPID DRYING HS 5:1


--	--	--	--	--	--

"As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"


D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Panoramic glasses against splash/projections.		EN 166:2001 EN ISO 4007:2012	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.
Mandatory face protection				

V2018 ULTIMATE RAPID DRYING HS 4:1
V2018 ANTICORROSIVE RAPID DRYING HS 5:1

					
--	--	--	---	--	--

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties		EN 13287:2008 EN ISO 20345:2011 EN 13832-1:2006	Replace boots at any sign of deterioration.
Mandatory foot protection				

V2018 ULTIMATE RAPID DRYING HS 4:1
V2018 ANTICORROSIVE RAPID DRYING HS 5:1

--	--	--	--	--

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
	ANSI Z358-1 ISO 3864-1:2002		DIN 12 899 ISO 3864-1:2002
Emergency shower		Eyewash stations	

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	25,69 % weight
V.O.C. density at 20 °C:	420 kg/m ³ (420 g/L)
Average carbon number:	6,49
Average molecular weight:	115,52 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

V2018 ULTIMATE RAPID DRYING HS 4:1
V2018 ANTICORROSIVE RAPID DRYING HS 5:1

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C: Liquid

Appearance: Viscous

Colour: According to the markings on the package

Odour: Characteristic

Odour threshold: Non-applicable *

Volatility:

Boiling point at atmospheric pressure: 131 °C

Vapour pressure at 20 °C: 1569 Pa

Vapour pressure at 50 °C: 52,46 (6,99 kPa)

Evaporation rate at 20 °C: Non-applicable *

Product description:

Density at 20 °C: 1634 kg/m³

Relative density at 20 °C: Non-applicable *

Dynamic viscosity at 20 °C: Non-applicable *

Kinematic viscosity at 20 °C: Non-applicable *

Kinematic viscosity at 40 °C: >20,5 cSt applicable * Concentration: Non-applicable * pH: Non-

Vapour density at 20 °C: Non-applicable *

Partition coefficient n-octanol/water 20 °C: Non-applicable *

Solubility in water at 20 °C: Non-applicable *

Solubility properties: Non-applicable *

Decomposition temperature: Non-applicable *

Melting point/freezing point: Non-applicable *

Explosive properties: Non-applicable *

Oxidising properties: Non-applicable *

Flammability:

Flash Point: 27 °C

Flammability (solid, gas): Non-applicable *

V2018 ULTIMATE RAPID DRYING HS 4:1
V2018 ANTICORROSIVE RAPID DRYING HS 5:1

Autoignition temperature: 315 °C

Lower flammability limit: Not available

Upper flammability limit: Not available

Explosive:

Lower explosive limit: Non-applicable *

Upper explosive limit: Non-applicable *

9.2 Other information:

Surface tension at 20 °C: Non-applicable *

Refraction index: Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

SECTION 10: STABILITY AND REACTIVITY (continued)

V2018 ULTIMATE RAPID DRYING HS 4:1
V2018 ANTICORROSIVE RAPID DRYING HS 5:1

under recommended storage conditions. See section 7. No hazardous reactions are expected because the product is stable

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

Incompatible materials:

10.5

Acids	Water	Combustive materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for skin contact. For more information see section 3.
- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
IARC: Titanium dioxide (2B); Silicon dioxide (RCS < 1%) (3); Carbon black (2B); Quartz (1 % < RCS < 10%) (1); Talc (3); Xylene (3)
- Mutagenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with mutagenic effects. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

Safety data sheet

According to 1907/2006/EC (REACH), 2015/830/EU

V2018 ULTIMATE RAPID DRYING HS 4:1
V2018 ANTICORROSIVE RAPID DRYING HS 5:1

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous as a result of a single exposure. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- Skin: Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LD50 oral	12789 mg/kg	Rat
	LD50 dermal	14112 mg/kg	Rabbit
	LC50 inhalation	23,4 mg/L (4 h)	Rat
2-butanone CAS: 78-93-3 EC: 201-159-0	LD50 oral	4000 mg/kg	Rat
	LD50 dermal	6400 mg/kg	Rabbit
	LC50 inhalation	23,5 mg/L (4 h)	Rat
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	LD50 oral	8532 mg/kg	Rat
	LD50 dermal	5100 mg/kg	Rat
	LC50 inhalation	30 mg/L (4 h)	Rat
Xylene CAS: 1330-20-7 EC: 215-535-7	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg (ATEi)	Rat
	LC50 inhalation	11 mg/L (4 h) (ATEi)	
trizinc bis(orthophosphate) CAS: 7779-90-0 EC: 231-944-3	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>5 mg/L	
Dibutyltin Dilaurate CAS: 77-58-7 EC: 201-039-8	LD50 oral	175 mg/kg	Rat
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>20 mg/L	

SECTION 12: ECOLOGICAL INFORMATION

V2018 ULTIMATE RAPID DRYING HS 4:1
V2018 ANTICORROSIVE RAPID DRYING HS 5:1

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Identification	Acute toxicity		Species	Genus
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LC50	62 mg/L (96 h)	Leuciscus idus	Fish
	EC50	73 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	675 mg/L (72 h)	Scenedesmus subspicatus	Algae
Xylene CAS: 1330-20-7 EC: 215-535-7	LC50	13.5 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	3.4 mg/L (48 h)	Ceriodaphnia dubia	Crustacean
	EC50	10 mg/L (72 h)	Skeletonema costatum	Algae

SECTION 12: ECOLOGICAL INFORMATION (continued)

Safety data sheet

According to 1907/2006/EC (REACH), 2015/830/EU

V2018 ULTIMATE RAPID DRYING HS 4:1
V2018 ANTICORROSIVE RAPID DRYING HS 5:1

Identification	Acute toxicity		Species	Genus
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	LC50	161 mg/L (96 h)	Pimephales promelas	Fish
	EC50	481 mg/L (48 h)	Daphnia sp.	Crustacean
	EC50	Non-applicable		
2-butanone CAS: 78-93-3 EC: 201-159-0	LC50	3220 mg/L (96 h)	Pimephales promelas	Fish
	EC50	5091 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	4300 mg/L (168 h)	Scenedesmus quadricauda	Algae
trizinc bis(orthophosphate) CAS: 7779-90-0 EC: 231-944-3	LC50	0.1 - 1 mg/L (96 h)		Fish
	EC50	0.1 - 1 mg/L		Crustacean
	EC50	0.1 - 1 mg/L		Algae
Dibutyltin Dilaurate CAS: 77-58-7 EC: 201-039-8	LC50	0.1 - 1 mg/L (96 h)		Fish
	EC50	0.1 - 1 mg/L		Crustacean
	EC50	0.1 - 1 mg/L		Algae

12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
	Parameter	Value	Parameter	Value
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	5 days
	BOD5/COD	0.79	% Biodegradable	84 %
Xylene CAS: 1330-20-7 EC: 215-535-7	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	88 %
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	BOD5	Non-applicable	Concentration	785 mg/L
	COD	Non-applicable	Period	8 days
	BOD5/COD	Non-applicable	% Biodegradable	100 %
2-butanone CAS: 78-93-3 EC: 201-159-0	BOD5	2.03 g O2/g	Concentration	Non-applicable
	COD	2.31 g O2/g	Period	20 days
	BOD5/COD	0.88	% Biodegradable	89 %
Dibutyltin Dilaurate CAS: 77-58-7 EC: 201-039-8	BOD5	0.00054 g O2/g	Concentration	100 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	50 %

12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential	
	Parameter	Value
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	BCF	4
	Pow Log	1.78
	Potential	Low
Xylene CAS: 1330-20-7 EC: 215-535-7	BCF	9
	Pow Log	2.77
	Potential	Low
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	BCF	1
	Pow Log	0.43
	Potential	Low
2-butanone CAS: 78-93-3 EC: 201-159-0	BCF	3
	Pow Log	0.29
	Potential	Low

- CONTINUED ON NEXT PAGE -

V2018 ULTIMATE RAPID DRYING HS 4:1
V2018 ANTICORROSIVE RAPID DRYING HS 5:1

Dibutyltin Dilaurate CAS: 77-58-7 EC: 201-039-8	BCF	31
	Pow Log	3.12
	Potential	Moderate

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2,478E-2 N/m (25 °C)	Moist soil	Non-applicable

V2018 ULTIMATE RAPID DRYING HS 4:1
V2018 ANTICORROSIVE RAPID DRYING HS 5:1

Identification	Absorption/desorption		Volatility	
Xylene CAS: 1330-20-7 EC: 215-535-7	Koc	202	Henry	524,86 Pa·m ³ /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	Non-applicable	Moist soil	Yes
2-butanone CAS: 78-93-3 EC: 201-159-0	Koc	30	Henry	5,77 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2,396E-2 N/m (25 °C)	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommend disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2017 and RID 2017:

14.1 UN number: UN1263

14.2 UN proper shipping name: PAINT

14.3 Transport hazard class(es): 3
Labels: 3

14.4 Packing group: III

14.5 Environmental hazards: No

14.6 Special precautions for user

Special regulations: 163, 367, 650
Tunnel restriction code: D/E
Physico-Chemical properties: see section 9
Limited quantities: 5 L

V2018 ULTIMATE RAPID DRYING HS 4:1
V2018 ANTICORROSIVE RAPID DRYING HS 5:1

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 38-16:

SECTION 14: TRANSPORT INFORMATION (continued)

14.1 UN number: UN1263

14.2 UN proper shipping name: PAINT

14.3 Transport hazard class(es): 3

Labels: 3

14.4 Packing group: III

14.5 Environmental hazards: No

14.6 Special precautions for user

Special regulations: 163, 223, 367, 955

EmS Codes: F-E, S-E

Physico-Chemical properties: see section 9

Limited quantities: 5 L

Segregation group: Non-applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2018:

14.1 UN number: UN1263

14.2 UN proper shipping name: PAINT

14.3 Transport hazard class(es): 3

V2018 ULTIMATE RAPID DRYING HS 4:1
V2018 ANTICORROSIVE RAPID DRYING HS 5:1

Labels: 3

14.4 Packing group: III

14.5 Environmental hazards: No

14.6 Special precautions for user

Physico-Chemical properties: see section 9

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture: Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable Article 95, REGULATION (EU) No 528/2012: Non-applicable REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Contains Dibutyltin Dilaurate

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c		5000	50000

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Non-applicable

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

V2018 ULTIMATE RAPID DRYING HS 4:1
V2018 ANTICORROSIVE RAPID DRYING HS 5:1

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

V2018 ULTIMATE RAPID DRYING HS 4:1
V2018 ANTICORROSIVE RAPID DRYING HS 5:1

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

Texts of the legislative phrases mentioned in section 2:

H412: Harmful to aquatic life with long lasting effects

H226: Flammable liquid and vapour

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled

Aquatic Acute 1: H400 - Very toxic to aquatic life

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways

Eye Irrit. 2: H319 - Causes serious eye irritation

Flam. Liq. 2: H225 - Highly flammable liquid and vapour

Flam. Liq. 3: H226 - Flammable liquid and vapour

Muta. 2: H341 - Suspected of causing genetic defects

Repr. 1B: H360 - May damage fertility or the unborn child

Skin Corr. 1C: H314 - Causes severe skin burns and eye damage

Skin Irrit. 2: H315 - Causes skin irritation

Skin Sens. 1: H317 - May cause an allergic skin reaction

STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure. (Oral)

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral)

STOT SE 1: H370 - Causes damage to organs

STOT SE 3: H335 - May cause respiratory irritation

STOT SE 3: H336 - May cause drowsiness or dizziness

Classification procedure:

Aquatic Chronic 3: Calculation method

Flam. Liq. 3: Calculation method (2.6.4.3)

Advice related to training: Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources: <http://echa.europa.eu> <http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation COD:

Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor LD50:

Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient Koc:

Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -