

# Merrychef Advanced High Speed Cook Oven Cikon<sup>°</sup> e3 HP



#### **Standard Features**


- Oven cavity to suit up to 297mm x 321mm / 11" x 12.7" tray size
- 2 rack positions
- Up to 5 times faster than a convection oven
- Advanced Cooking Technology® combines two heat technologies: microwave and convection heat
- Ventless cooking capabilities through built in catalytic converter
- Colour easyTouch<sup>®</sup> icon driven touch screen control panel with
- the capability of storing up to 1,024 multi-stage recipe programs • Each program offers up to six (6) stages with programmable
- Each program ones up to six (o) stages with programmable cooking times, microwave power setting and user instructions for each stage
- 3 cooking levels for power saving yet faster cooking and baking
- Quick preheat function
- Includes turntable for even browning
- Easy menu updates or data transfer via USB
- MenuConnectTM ethernet connection for remote menu updating and diagnostics
- Precise temperature setting range from 100°C 275°C
- Self-diagnostics capability to monitor components
- Cool to touch door exterior
- Stainless steel construction
- Easy to clean interior
- Easy access to front facing air filter
- Multi-languages available

#### Includes

- Cast turntable tray coated (2)
- Handle
- Turntable disk
- Cool down pan
- Cleaning care package, consisting of:
  - 1x oven cleaner (bottle)
  - 1x oven protector (bottle)

### Accessories

- Cook liners
- Trays
- Disk
- Racks
- Handles




#### Airflow (side view)

Air in the oven cavity is cleaned by being drawn through the catalytic converter\* (1) by the convection fan (2) and then passes over the heating element and is circulated into the oven cavity (3) at the set temperature.



## Merrychef Advanced High Speed Cook Oven **eikon**<sup>°</sup> e3 HP



DIMENSIONS

PACKED DIMENSIONS

Weight (including cleaning system)

INSTALLATION REQUIREMENTS

INSTALLATION REQUIREMENTS

units installation manual

400-415V, 50Hz (2P+N+E)

Rated power consumption

ELECTRICAL SUPPLY

Rated current

20A 5 pin plug

all installations.

For precise installation instructions please refer to the

Width

Depth Height

Weight


Width

Depth

Height

Rear Right

Left



POWER OUTPUT (APPROX.)

Microwave

Convected heat

### MOFFRI

Australia moffat.com.au

New Zealand moffat.co.nz

#### Australia Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Ph 03-9518 3888 Fax 03-9518 3833 vsales@moffat.com.au www.moffat.com.au

New South Wales Ph 02-8833 4111 nswsales@moffat.com.au

South Australia Ph 03-9518 3888 vsales@moffat.com.au

Queensland Ph 07-3630 8600 qldsales@moffat.com.au

Western Australia Ph 08-9413 2400 wasales@moffat.com.au

#### New Zealand Moffat Limited

1 kW

3 kW

Christchurch 45 Illinois Drive Izone Business Hub Rolleston 7675 New Zealand Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz

Auckland Ph +64 9-574 3150 sales@moffat.co.nz

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice

© Copyright Moffat Ltd AN.MC.1707



4.7 kW 20A All Merrychef ovens require a type D circuit breaker for

590 mm

559 mm

551 mm

62.5 kg

770 mm

860 mm

760 mm

71 kg

50 mm

50 mm

an Ali Group Company

