

- Digital temperature display and analog controller
- Static cooling system
- Sliding curved glass doors with lock
- Powder coated steel exterior dan interior
- LED light on canopy
- Climate rating: ST


SD235S2 Model Gross volume (L) 235 Exterior dimensions in mm 836w x 838d x 1245h Energy consumption in 24h 1.8 kWh ≤-18°C Temperature Number 5L tubs 4 Tubs yes, stainless steel Castors yes Refrigerant R134a Insulation 70mm Gross/net weight 82/108 kg Frequency/voltage 50 Hz/220-240 V



SD325S2
325
1080w x 838d x 1245h
2.3 kWh
≤-18°C
6
yes, stainless steel
yes
R134a
70mm
109/138 kg
50 Hz/220-240 V

Rear door for easy storage access





- Sliding curved glass doors with lock
- · Powder coated steel exterior dan interior
- LED light on canopy
- Climate rating: ST

Model	SD415S2
Gross volume (L)	415
Exterior dimensions in mm	1350w x 838d x 1245h
Energy consumption in 24h	1.8 kWh
Temperature	≤-18°C
Number 5L tubs	9
Tubs material	yes, stainless steel
Castors	yes
Refrigerant	R134a
Insulation	70mm
Gross/net weight	123/162 kg
Frequency/voltage	50 Hz/220-240 V







SD575S2

575 1720w x 838d x 1245h 2.3 kWh ≤-18°C 12 yes, stainless steel yes R404a 70mm 152/199 kg 50 Hz/220-240 V