G32D4

# TECHNICAL DATA SHEET FOR G32D4 ON THE SK32 STAND

## Full Size Digital / Gas Convection Oven on a Stainless Steel Stand

#### STANDARD FEATURES

- 4 18" x 26" / 460 x 660 full size sheet pan capacity
- 4 600 x 400 tray capacity
- 110mm tray spacing
- Compact 735mm width
- 10A plug-in cordset fitted
- Digital display Time and Temperature controls
- Large easy view 20mm high displays
- Electronic thermostat control
- Electronic burner ignition and safety control system
- Electronic timer with countdown or time count modes
- Programmable for up to 20 programs
- · Water injection mode
- · Bi-directional fan motor
- 35 MJ/hr patented Infrared burner system
- Safe-Touch vented side hinged door (standard LH hinge). Optional RH hinge (field convertible)
- Stay-Cool door handle
- · Vitreous enamel oven chamber
- Plug-in continuous oven door seal
- Dual halogen oven lamps
- Anti-skid 50mm dia. 102mm high adjustable stainless steel feet
- 4 oven wire racks supplied
- 100% recyclable packaging

#### **ACCESSORIES**

• Turbofan SK32 Oven Stand



#### G32D4

Unit shall be a Moffat gas heated Turbofan convection oven. The oven shall have a one piece vitreous enamel oven chamber, stainless top and sides and safe touch vented easy clean side hinged door that offers field reversible hinging. Oven shall have capacity for four full size sheet pans. The oven shall be controlled by an electronic control having separate digital displays and adjusting knobs for time and temperature functions. The oven control shall allow both manual and programmed operating modes and have separate control keys for water injection, oven light function and timer operation. The unit shall include dual halogen oven lamps. Oven shall be able to be bench mounted on 76mm feet or mounted on oven stand model SK32. Unit shall be supplied in 100% recyclable shipping packaging.

Unit shall be a Moffat Turbofan stainless steel oven stand. The stand shall be constructed from stainless steel tube with castors, with front castors having dual swivel and wheel locks. It shall be fitted with 6 tray runners suitable for up to 12 half size sheet pans or 6 full size sheet pans. The stand shall be fully compatible with, and support, Turbofan Convection Oven models E32D and G32D. Unit shall be supplied in 100% recyclable shipping packaging.







#### G32D4 Full Size Digital / Gas Convection Oven on a Stainless Steel Stand

#### CONSTRUCTION

Vitreous enamel fully welded oven chamber Stainless steel front, sides and top exterior Stainless steel oven fan baffle and oven vent Removable 4 position stainless steel side racks Oven racks chrome plated wire (4 supplied)

Stainless steel frame side hinged door

5mm thick door outer glass

5mm thick low energy loss door inner glass Full stainless steel welded door handle

Stainless steel control panel

Aluminised coated steel base and rear panels

#### CONTROLS

Electronic controls with Digital Time and Temperature display, Manual or Program modes

Large 20mm high LED displays

Two individual time and temperature setting control knobs

6 function kevs ON/OFF key

Oven Lamp key (toggle or auto-time off mode settings)

Timer Start/Stop key
Water Injection key (manual shot or timed shot mode settings)

Programs select key

Actual temperature display key

Adjustable buzzer/alarm volume

Thermostat range 50-260°C

Timer range from 180 minutes in countdown mode

Timer range up to 999 minutes in time count mode for holding. slow cooking

Direct burner ignition control flame failure safety control Over-temperature safety cut-out

#### CLEANING

Stainless steel top and side exterior panels

Vitreous enamel oven chamber

Fully removable stainless steel oven side racks

Removable stainless steel oven fan baffle Easy clean door system with hinge out door inner glass (no

tools required)

Removable plug-in oven door seal (no tools required)

76mm high stainless steel feet for easy access underside

#### SPECIFICATIONS

**Electrical Requirements** 

230-240V, 50/60Hz, 1P+N+E, 0.5A

10A cordset fitted

#### Gas Requirements

35MJ/hr burner rating

Natural, LPG models

Unit supplied complete with gas type conversion kit

Gas Connection

1/2" BSPT male

Water Requirements (optional)

Cold water connection 3/4" BSP male

80psi maximum inlet pressure / 20psi minimum inlet pressure

External Dimensions

Width 735mm

Height 910mm including 102mm feet

Depth 810mm

Oven Internal Dimensions Width 465mm

515mm Height Depth 700mm Volume 0.17m3

Oven Rack Dimensions

Width 460mm Depth 660mm

Nett Weight (G32D4)

113kg

Packing Data (G32D4)

289lbs / 131kg 25ft3 / 0.71m3

Width 760mm Height 1010mm 925mm Depth

#### SK32 Stainless Steel Stand

All stainless steel welded frame oven stand for Turbofan E32D and G32D Series ovens

6 position tray runners standard

76mm diameter wheel swivel castors standard with 2 front castors with dual swivel and wheel

Welded 38mm and 32mm square tube front and rear frames Welded rack supports/side frames

4 dia. 76mm swivel castors with 2 front castors dual wheel and

swivel lock Top frame oven supports suit Turbofan E32D and G32D Series

oven mounting

Supplied CKD for assembly on site

External Dimensions (SK32 Oven Stand)

735mm Width 880mm Height 650mm Depth

Nett Weight (SK32 Oven Stand)

18.5kg

Packing Data (SK32 Oven Stand)

23kg 0.1m3

Width 830mm 900mm Height Depth 152mm

### MOFFAT

Australia www.moffat.com.au New Zealand www.moffat.co.nz www.turbofanoven.com

#### Australia Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Telephone 03-9518 3888 Facsimile 03-9518 3833 vsales@moffat.com.au

New South Wales Telephone 02-8833 4111 nswsales@moffat.com.au

South Australia Telephone 03-9518 3888 vsales@moffat.com.au

Queensland Telephone 07-3630 8600 qldsales@moffat.com.au


Western Australia Telephone 08-9202 6820 bgarcia@moffat.com.au


#### New Zealand Moffat Limited


Christchurch 16 Osborne Street Christchurch 8011 Telephone 03-389 1007 Facsimile 03-389 1276 sales@moffat.co.nz

Auckland Telephone 09-574 3150 sales@moffat.co.nz











IS09001 Quality Management Standard

Designed and manufactured by



ISO9001

All Turbofan products are designed and manufactured by Moffat using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice

© Copyright Moffat Ltd

