

Technical data sheet for

VEE RAY SINGLE PAN GAS FRYER 600mm

GT60E

- High performance single pan fish fryer
- Patented infra-red burner system
- Digital display temperature control with 3 product timers
- Easy clean stainless steel open pan with 10 year limited warranty
- 31L oil tank capacity
- 2 large or 3 standard basket capacity
- Large capacity cool zone
- 32mm (1 ¹/₄") drain valve
- Rear rollers
- Stainless steel exterior
- Easy service
- Fully modular



Overall Construction

- Stainless steel pan with 10 year limited warranty
- Bull nose welded 1.5mm 304 stainless steel
- Splashback 1.2mm 304 stainless steel
- Side panels 1.2mm 304 stainless steel
- Double skin door with 0.9mm 304 stainless exterior
- $32mm \left(1 \frac{1}{4}\right) drain valve$
- 63mm dia. heavy-duty 1.2mm 304 stainless steel adjustable legs at front and two rollers at rear
- 3 standard baskets and stainless steel lid supplied standard

Controls

- Digital display electronic thermostat
- Thermostat range 88-193°C
- 3 programmable product timers with countdown display and alarms
- Straight or temperature compensating cook time control
- Heating and basket drop displays
- Programmable melt cycles
- Over-temperature safety cut-out
- Flame failure protection on each pilot
- Piezo ignition to standing pilot burners

Cleaning and Servicing

- Open stainless steel pans for easy clean
- Easy clean basket support bar
- 32mm (1 $^{1}/_{4}$ ") drain valve for effective draining
- Easy clean stainless steel exterior
- Access to all parts from front of unit



Technical data sheet for

VEE RAY SINGLE PAN GAS FRYER 600mm

Specifications

Production rate

31kg/hr

Pan Size

Width 515mm Length 380mm Oil frying depth 95mm

Oil capacity 31L (46.5lbs shortening)

Baskets

3 chrome plated wire baskets 140mm W x 335mm D x 145mm H Optional 2 chrome plated large wire baskets 210mm W x 335mm D x 145mm H Stainless steel perforated basket support plate

2 x 45MJ/hr infra-red burners

Gas Power

90MJ/hr, 25kW

Gas connection

R 3/4 (BSP) male Optional rear connection (refer specification drawing)

Flectrical Connection

230-240 Vac, 1P+N+E, 50/60Hz, 0.5A 3 pin 10A plug cordset fitted

Dimensions

Width Annmm Depth 812mm Height 915mm Incl. splashback 1085mm

Nett weight

95kg

Packing data


0.70m3, 143kg Width 870mm Depth 645mm Height 1255mm


Gas types

Available in Natural gas and LP gas, please specify when ordering Units supplied complete with gas type conversion kits Other gas types on request

Adjustable feet at rear Filtamax Filtration System Fish plates Extra standard baskets Large baskets Side splash guards Joining caps Castors

GT60E





MOFFRT.

Australia www.moffat.com.au New Zealand www.moffat.co.nz

www.bluesealevolution.com

Australia **Moffat Pty Limited**

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Telephone 03-9518 3888 Facsimile 03-9518 3833 vsales@moffat.com.au

New South Wales Telephone 02-8833 4111 nswsales@moffat.com.au

South Australia Telephone 03-9518 3888 vsales@moffat.com.au

Queensland Telephone 07-3630 8600 qldsales@moffat.com.au

Western Australia Telephone 08-9202 6802 bgarcia@moffat.com.au

New Zealand **Moffat Limited**

Christchurch 16 Osborne Street Christchurch 8011 Telephone 03-389 1007 Facsimile 03-389 1276 sales@moffat.co.nz

Auckland Telephone 09-574 3150 sales@moffat.co.nz



IS09001 Quality Management Standard

MOFFET

ISO9001 All Blue Seal products are designed and manufactured by Moffat using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.



In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and

Printed in China © Copyright Moffat Ltd Moffat/4825/BH/2.5M/12.06





