Waldorf

Twin Pan Electric Multi Pan

JUMP 101D - 80 LITRE



Overall Construction

- Base frame with 3mm 304 grade stainless steel
- Frame cover with 304 grade stainless steel
- Tray with 3mm 316 grade stainless steel
- Special sandwich design pan base
- Stainless steel SUPER BLOCK JPX 17 full area heat distribution system
- Robust double insulated cover with automatic lifting function
- Excessive steam exhaust on cover
- Integrated 230V / 16A socket
- Retractable switchboard panel on right pillar allowing integration of multiple pans in a single block

Controls

- Fast base preheating
- Temperature range from 30°C-250°C
- Accurate sensory measurement of temperature
- Liquid level gauge
- Integrated drainage in the tray bottom with automatic closure
- Preset technological procedures

- 2 x 40 litre pan capacity
- 2 x 1/1 GN pan size
- 2 x 22dm² cooking surface
- 220mm depth pan
- Multi pan for cooking, frying, braising, grilling, searing, broiling and sous-vide cooking
- Automatic basket lifting
- Automatic water filling system with accuracy of 1 decilitre
- Electromechanical tray tilting at variable speed
- 10" colour touch screen for intuitive operation and cook progress display
- Automatic and manual meal preparation mode with memory for 350 programs with 20 steps
- Four point core temperature probe
- Integrated retractable hand shower
- Automatic extension of baskets allows operation with cover closed
- Safety sensor for basket arm detection
- Fault messages shown on display
- Water pressure controller
- HACCP recording

USB port for data backup

Cleaning and Servicing

- Easy clean stainless steel surface
- Easy services access from front and top sides
- Technical and service information on display





Twin Pan Electric Multi Pan JUMP 101D - 80 LITRE

Specifications

Dimensions

Width 1546mm Depth 850mm Height 1030mm


Capacity 80 litre

Nett weight

475kg

Packing data 583kg Width 1650mm Depth 1080mm

Depth 1080mm Height 1220mm




Electrical rating


400-415V, 3P+N+E, 50Hz, 32A Energy consumption: 23.3kW

Water connection requirements Inlet connection: R ¾ Water outlet connection: Ø 50

Installation conditions (for precise installation instructions please refer to our installation manual)







Copyright Moffat Ltd. AN.WJ.2021

an Ali Group Company





moffat.com.au moffat.co.nz

Australia moffat.com.au

Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Telephone +613-9518 3888 Facsimile +613-9518 3833 vsales@moffat.com.au

New South Wales Telephone +612-8833 4111 nswsales@moffat.com.au

South Australia Telephone +613-9518 3888 vsales@moffat.com.au

Queensland Telephone +617-3630 8600 qldsales@moffat.com.au

Western Australia Telephone +618-9413 2400 wasales@moffat.com.au

New Zealand moffat.co.nz

Moffat Limited Rolleston 45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz Auckland

Telephone +64 9-574 3150 sales@moffat.co.nz