MRFvd 4011





Int. dimensions in mm (w/d/h) 475/423/1659 Energy consumption in 365 days / 24 hours 810 / 2.22 Climate rating 5 Ambient temperature range +10°C to +43°C¹ Refrigerant R 600a Connection Rating 2.0 A Frequency / Voltage 50 Hz / 220-240 V~ Cooling system forced-air Defrosting automatic Temperature range +1°C to +15°C Housing material/colour steel/grey Door material Insulated glazed door Liner Material moulded polystyrol white Type of Control analgoue controls Temperature display external digital Interior light LED Adjustable Shelving 5 Loading capacity 0.5L PET/facings 0.5L PET 253/7 Loading capacity 0.33L can/facings 0.33L can 506/7 Lock fitted Self-closing door yes Door hinges right, reversible	Gross/net capacity	400/286 litre
Energy consumption in 365 days / 24 hours Climate rating 5 Ambient temperature range **10°C to *43°C¹ Refrigerant R 600a Connection Rating 2.0 A Frequency / Voltage 50 Hz / 220-240 V~ Cooling system forced-air Defrosting automatic Temperature range **1°C to *15°C Housing material/colour Door material Insulated glazed door Liner Material moulded polystyrol white Type of Control analgoue controls Temperature display external digital Interior light LED Adjustable Shelving 5 Loading capacity 0.5L PET/facings 0.5L PET Loading capacity 0.33L can/facings 0.33L can 506/7 Lock fitted Self-closing door yes Door hinges right, reversible Insulation 50/45 mm Gross/net weight 85/78 kg	Ext. dimensions in mm (w/d/h)	597/654/1884
Climate rating 5 Ambient temperature range +10°C to +43°C¹ Refrigerant R 600a Connection Rating 2.0 A Frequency / Voltage 50 Hz / 220-240 V- Cooling system forced-air Defrosting automatic Temperature range +1°C to +15°C Housing material/colour steel/grey Door material Insulated glazed door Liner Material moulded polystyrol white Type of Control analgoue controls Temperature display external digital Interior light LED Adjustable Shelving 5 Loading capacity 0.51 PET/facings 0.51 PET 253/7 Loading capacity 0.53L can/facings 0.33L can 506/7 Lock fitted Self-closing door yes Door hinges right, reversible Insulation 50/45 mm Gross/net weight 85/78 kg	Int. dimensions in mm (w/d/h)	475/423/1659
Ambient temperature range +10°C to +43°C¹ Refrigerant R 600a Connection Rating 2.0 A Frequency / Voltage 50 Hz / 220-240 V~Cooling system forced-air Defrosting automatic Temperature range +1°C to +15°C Housing material/colour steel/grey Door material Insulated glazed door Liner Material moulded polystyrol white Type of Control analgoue controls Temperature display external digital Interior light LED Adjustable Shelving 50.5L PET 253/7 Loading capacity 0.5L PET/facings 0.5L PET 253/7 Loading capacity 0.33L can/facings 0.33L can 506/7 Lock fitted Self-closing door yes Door hinges right, reversible Insulation 50/45 mm Gross/net weight 85/78 kg	Energy consumption in 365 days / 24 hours	810 / 2.22
Refrigerant R 600a Connection Rating 2.0 A Frequency / Voltage 50 Hz / 220-240 V- Cooling system forced-air Defrosting automatic Temperature range +1°C to +15°C Housing material/colour steel/grey Door material Insulated glazed door Liner Material moulded polystyrol white Type of Control analgoue controls Temperature display external digital Interior light LED Adjustable Shelving 5 Loading capacity 0.5L PET/facings 0.5L PET 253/7 Loading capacity 0.33L can/facings 0.33L can 506/7 Lock fitted Self-closing door yes Door hinges right, reversible Insulation 50/45 mm Gross/net weight 85/78 kg	Climate rating	5
Connection Rating 2.0 A Frequency / Voltage 50 Hz / 220-240 V~ Cooling system forced-air Defrosting automatic Temperature range +1°C to +15°C Housing material/colour steel/grey Door material Insulated glazed door Liner Material moulded polystyrol white Type of Control analgoue controls Temperature display external digital Interior light LED Adjustable Shelving 5 Loading capacity 0.5L PET/facings 0.5L PET 253/7 Loading capacity 0.33L can/facings 0.33L can 506/7 Lock fitted Self-closing door yes Door hinges right, reversible Insulation 50/45 mm Gross/net weight 85/78 kg	Ambient temperature range	+10°C to +43°C 1
Frequency / Voltage 50 Hz / 220-240 V~ Cooling system forced-air Defrosting automatic Temperature range +1°C to +15°C Housing material/colour steel/grey Door material Insulated glazed door Liner Material moulded polystyrol white Type of Control analgoue controls Temperature display external digital Interior light LED Adjustable Shelving 5 Loading capacity 0.5L PET/facings 0.5L PET Loading capacity 0.33L can/facings 0.33L can 506/7 Lock fitted Self-closing door yes Door hinges right, reversible Insulation 50/45 mm Gross/net weight 85/78 kg	Refrigerant	R 600a
Cooling system forced-air Defrosting automatic Temperature range +1°C to +15°C Housing material/colour steel/grey Door material Insulated glazed door Liner Material moulded polystyrol white Type of Control analgoue controls Temperature display external digital Interior light LED Adjustable Shelving 5 Loading capacity 0.5L PET/facings 0.5L PET Loading capacity 0.5L PET/facings 0.33L can Sob/7 Lock fitted Self-closing door yes Door hinges right, reversible Insulation 50/45 mm Gross/net weight 85778 kg	Connection Rating	2.0 A
Defrosting automatic Temperature range +1°C to +15°C Housing material/colour steel/grey Door material Insulated glazed door Liner Material moulded polystyrol white Type of Control analgoue controls Temperature display external digital Interior light LED Adjustable Shelving 5 Loading capacity 0.5L PET/facings 0.5L PET Loading capacity 0.33L can/facings 0.33L can 506/7 Lock fitted Self-closing door yes Door hinges right, reversible Insulation 50/45 mm Gross/net weight 85elving 15°C to +15°C	Frequency / Voltage	50 Hz / 220-240 V~
Temperature range +1°C to +15°C Housing material/colour steel/grey Door material Insulated glazed door Liner Material moulded polystyrol white Type of Control analgoue controls Temperature display external digital Interior light LED Adjustable Shelving 5 Loading capacity 0.5L PET/facings 0.5L PET 253/7 Loading capacity 0.33L can/facings 0.33L can 506/7 Lock fitted Self-closing door yes Door hinges right, reversible Insulation 50/45 mm Gross/net weight 85/78 kg	Cooling system	forced-air
Housing material/colour steel/grey Door material Insulated glazed door Liner Material moulded polystyrol white Type of Control analgoue controls Temperature display external digital Interior light LED Adjustable Shelving 5 Loading capacity 0.5L PET/facings 0.5L PET 253/7 Loading capacity 0.33L can/facings 0.33L can 506/7 Lock fitted Self-closing door yes Door hinges right, reversible Insulation 50/45 mm Gross/net weight 885/78 kg	Defrosting	automatic
Door material Insulated glazed door Liner Material moulded polystyrol white Type of Control analgoue controls Temperature display external digital Interior light LED Adjustable Shelving 5 Loading capacity 0.5L PET/facings 0.5L PET 253/7 Loading capacity 0.33L can/facings 0.33L can 506/7 Lock fitted Self-closing door yes Door hinges right, reversible Insulation 50/45 mm Gross/net weight 85/78 kg	Temperature range	+1°C to +15°C
Liner Material moulded polystyrol white Type of Control analgoue controls Temperature display external digital Interior light LED Adjustable Shelving 5 Loading capacity 0.5L PET/facings 0.5L PET 253/7 Loading capacity 0.33L can/facings 0.33L can 506/7 Lock fitted Self-closing door yes Door hinges right, reversible Insulation 50/45 mm Gross/net weight 85/78 kg	Housing material/colour	steel/grey
Type of Control analgoue controls Temperature display external digital Interior light LED Adjustable Shelving 5 Loading capacity 0.5L PET/facings 0.5L PET 253/7 Loading capacity 0.33L can/facings 0.33L can 506/7 Lock fitted Self-closing door yes Door hinges right, reversible Insulation 50/45 mm Gross/net weight 85/78 kg	Door material	Insulated glazed door
Temperature display external digital Interior light LED Adjustable Shelving 5 Loading capacity 0.5L PET/facings 0.5L PET 253/7 Loading capacity 0.33L can/facings 0.33L can 506/7 Lock fitted Self-closing door yes Door hinges right, reversible Insulation 50/45 mm Gross/net weight 85/78 kg	Liner Material	moulded polystyrol white
Interior light LED Adjustable Shelving 5 Loading capacity 0.5L PET/facings 0.5L PET 253/7 Loading capacity 0.33L can/facings 0.33L can 506/7 Lock fitted Self-closing door yes Door hinges right, reversible Insulation 50/45 mm Gross/net weight 85/78 kg	Type of Control	analgoue controls
Adjustable Shelving 5 Loading capacity 0.5L PET/facings 0.5L PET 253/7 Loading capacity 0.33L can/facings 0.33L can 506/7 Lock fitted Self-closing door yes Door hinges right, reversible Insulation 50/45 mm Gross/net weight 85/78 kg	Temperature display	external digital
Loading capacity 0.5L PET/facings 0.5L PET 253/7 Loading capacity 0.33L can/facings 0.33L can 506/7 Lock fitted Self-closing door yes Door hinges right, reversible Insulation 50/45 mm Gross/net weight 85/78 kg	Interior light	LED
Loading capacity 0.33L can/facings 0.33L can506/7LockfittedSelf-closing dooryesDoor hingesright, reversibleInsulation50/45 mmGross/net weight85/78 kg	Adjustable Shelving	5
LockfittedSelf-closing dooryesDoor hingesright, reversibleInsulation50/45 mmGross/net weight85/78 kg	Loading capacity 0.5L PET/facings 0.5L PET	253/7
Self-closing dooryesDoor hingesright, reversibleInsulation50/45 mmGross/net weight85/78 kg	Loading capacity 0.33L can/facings 0.33L can	506/7
Door hingesright, reversibleInsulation50/45 mmGross/net weight85/78 kg	Lock	fitted
Insulation 50/45 mm Gross/net weight 85/78 kg	Self-closing door	yes
Gross/net weight 85/78 kg	Door hinges	right, reversible
	Insulation	50/45 mm
EAN-Nr. 9005382232439	Gross/net weight	85/78 kg
	EAN-Nr.	9005382232439





 $^{^{\}mbox{\tiny 1}}$ Indicates the ambient temperature at which the device can be operated safely.