



# MX55ATS Reach-in Blast Chiller / Freezer

#### Standard Features

- · Free standing unit on legs
- Ergonomic touch screen controls integrated into the door
- 5 function home screen
- Manual use Soft Chill, Hard Chill, Soft Freeze, Hard Freeze and Self Adaptive I-Chilling
- 99 program cycles
- Favourites key shortcuts to the last 9 programs used
- Pre-chilling cycle key to maximise efficiency
- Multi-point core temperature probe
- Timer mode or continuous run
- Integrated door latch to keep door open when not in use
- Automatic fan stop when opening the door
- Operator selectable de-icing cycle
- External and internal finish made of 304 stainless steel
- Front frame with anti-condensation system
- Injected polyurethane foam insulation 60mm thick




## Please refer to Moffat price list for options and accessories

## Technical data

Tray capacity	15 x 1/1GN trays
Tray clearance	70mm
External dimensions	W 770mm x D 790mm x H 1925mm
Load capacity	55kg*
Electrical connections	1P+N+E, 230-240V, 50/60Hz, 15A, 2.5kW
Nett weight	150kg
Waste	Provide for a water runoff with trap
Air-cooled condensing unit - Refrigerant type R452A	
Ambient temperature requirement +15°C — +32°C	

<sup>\*</sup> Note – Load capacities may vary depending on the thermal conductivity of the food being chilled, the thickness of product and container used

#### Dimensions



(M1) MX55ATS

(A) Electrical supply

(B) De-icing waste

(CU) Useful (MIN) Minimum

N
ΤŢ
;




Disclaimer: All unit capacities are based on subjective testing. Moffat accepts no liability for production values.

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd

AN-FRI-S-1801



385 (B)

