



## NU Series Self Contained Dice Ice Machines – up to 100kg **NU 220 AS** Full dice cube 10g, 22mm x 22mm x 22mm



Full dice cube 10 g W 22 x D 22 x H 22 mm



Note: Ice production rate is measured with the water temperature at 10°C and an ambient temperature of 21°C.

- Up to 100kg daily production rate
- 37kg storage bin capacity
- Air cooled version
- Agion Technology resists the growth of microbes and the development of unpleasant odours
- Vertical evaporator spray-system technology
- Front-in and front-out air flow designed for placement in tight spaces
- Ergonomic access to ice with sliding disappearing door
- One touch cleaning for time and labour saving
- Resistant stainless steel exterior
- Easy access front condenser air filter
- Routine maintenance visible alarm light on front panel
- Includes removable air filter, ice scoop, water and drain hose




















# NU Series Self Contained Dice Ice Machines — up to 100kg

## **NU 220 AS**









#### moffat.com.au

Australia Moffat Pty Limited

#### Victoria/Tasmania

740 Springvale Road Mulgrave, Victoria 3170 Telephone 03-9518 3888 Facsimile 03-9518 3833 vsales@moffat.com.au

#### New South Wales

Telephone 02-8833 4111 nswsales@moffat.com.au

#### South Australia


Telephone 03-9518 3888 vsales@moffat.com.au

#### Queensland

Telephone 07-3630 8600 qldsales@moffat.com.au

#### Western Australia

Telephone 08-9413 2400 wasales@moffat.com.au



UNIT OF MEASUREMENT: mm

#### Ice production per 24 hours

Ambient temperature / Water temperature

	10°C / 10°C	21°C / 10°C	32°C / 21°C
NW 100 AS	109	100	70

### Dimensions

Width: 651mm Depth: 690mm

Height: 870mm (including legs)

Nett weight: 61kg Packed weight: 73kg

#### Water consumption

Air cooled version: 5 litres per hour

#### Electrical rating

Air cooled version: 230-240V, 1P+N+E, 50Hz, 600W,

10A cordset supplied

No. Circuit wire: 3 Compressor: 1300W Energy consumption: 15.6kW/hr

#### Refrigerant type

R404a

Installation distance from wall Rear 100mm

Sides 10mm Operating requirement air temperature 10-43°C

#### Water connection requirements

Inlet connection: R ¾"
Cold water: 5-38°C
Pressure: 100-500kPa
Water outlet connection: Ø ¾"

Important Notice:

Models and specifications are subject to change without notice. This spec sheet is meant for commercial purpose only. For technical documentation please refer to our service manuals.



© Copyright Moffat Ltd