



NW Series Modular Dice Ice Machines — up to 199kg

NW 507 AS Dice cube 10g, 22mm x 22mm x 22mm x 22mm **NWH 507 AS** Half dice cube 6g, 10mm x 22mm x 28mm **NWL 507 AS** Large dice cube 15g, 29mm x 22mm x 29mm

Dice cube 10 g W 22 x D 22 x H 22 mm



Half dice cube 6 g W 10 x D 22 x H 28 mm



Large dice cube 15 g W 29 x D 22 x H 29 mm



Scotsman

Cont

Note: Ice production rate is measured with the water temperature at 10°C and an ambient temperature of 21°C.

- Up to 199kg daily production rate
- Head only ice maker requires a separate storage bin to store the ice produced
- Air cooled version
- · Hydrocarbons R290 refrigerant gas
- · Vertical evaporator spray-system technology
- Top air discharge suitable for narrow space installation
- Agion Technology resists the growth of microbes and T304 grade stainless steel exterior
- Auto-alert indicator lights to show operation status and maintenance
- One touch cleaning for time and labour saving
- Front evaporator access for easy servicing
- · Includes air filter, water and drain hose

Recommended storage bins

- NB 193 129kg storage capacity
- NB 393 with CBT 30 EMCD cover 178kg storage capacity
- NB 530 with CBT 30 EMCD cover 243kg storage capacity












NW Series Modular Dice Ice Machines – up to 199kg

NW 507 AS, NWH 507 AS, NWL 507 AS





moffat.com.au

Australia Moffat Pty Limited

Victoria/Tasmania

740 Springvale Road Mulgrave, Victoria 3170 Telephone 03-9518 3888 Facsimile 03-9518 3833 vsales@moffat.com.au

New South Wales

Telephone 02-8833 4111 nswsales@moffat.com.au

South Australia

Telephone 03-9518 3888 vsales@moffat.com.au

Queensland

Telephone 07-3630 8600 qldsales@moffat.com.au

Western Australia

Telephone 08-9413 2400 wasales@moffat.com.au

Ice production per 24 hours

Ambient temperature / Water temperature

	10°C / 10°C	21°C / 10°C	32°C / 21°C
NW 507 AS	210	199	145
NWH 507 AS	201	192	141
NWL 507 AS	203	194	143

Dimensions

Width: 560mm
Depth: 610mm
Height: 662mm
Nett weight: 67kg
Packed weight: 77kg

Water consumption Air cooled version:

NW 507 AS: 10.7 litres per hour NWH 507 AS: 10.0 litres per hour NWL 507 AS: 10.5 litres per hour

Electrical rating

Air cooled version: 230-240V, 1P+N+E, 50Hz, 1210W,

10A cordset supplied

No. Circuit wire: 3

Compressor: 2941W

Energy consumption:

NW 507 AS: 21.1kW/hr NWH 507 AS: 20.2kW/hr NWL 507 AS: 19.9kW/hr

Refrigerant type

R290

Installation distance from wall Rear 100mm

Top 400mm

Operating requirement air temperature 10-43°C

Water connection requirements

Inlet connection: R ¾"

Cold water: 5-38°C

Pressure: 100-500kPa

Water outlet connection: Ø 20mm

Important Notice:

Models and specifications are subject to change without notice. This spec sheet is meant for commercial purpose only. For technical documentation please refer to our service manuals.



© Copyright Moffat Ltd AU.SM.1908

an Ali Group Company

