



NW Series Modular Dice Ice Machines – up to 630kg

NW 1408 AS Full dice cube 10g, 22mm x 22mm x 22mm **NWH 1408 AS** Half dice cube 6g, 10mm x 22mm x 28mm



Full dice cube 10 g W 22 x D 22 x H 22 mm



Half dice cube 6 g W 10 x D 22 x H 28 mm



Note: Ice production rate is measured with the water temperature at 10°C and an ambient temperature of 21°C.

- Up to 630kg daily production rate
- Head only ice maker requires a separate storage bin to store the ice produced
- Air cooled version
- Vertical evaporator spray-system technology
- Agion Technology resists the growth of microbes and the development of unpleasant odours
- T304 grade stainless steel exterior
- Auto-alert indicator lights to show operation status and maintenance
- One touch cleaning for time and labour saving
- Front evaporator access for easy servicing
- Includes removable air filter, water and drain hose

Recommended storage bins

- NB 530 243kg storage capacity
- NB 948 with CBT 48 EAMCD cover 406kg storage capacity
- UBH 1100 Upright storage bin with 553kg storage capacity




















NW Series Modular Dice Ice Machines – up to 630kg

NW 1408 AS, NWH 1408 AS









moffat.com.au

Australia Moffat Pty Limited

Victoria/Tasmania

740 Springvale Road Mulgrave, Victoria 3170 Telephone 03-9518 3888 Facsimile 03-9518 3833 vsales@moffat.com.au

New South Wales

Telephone 02-8833 4111 nswsales@moffat.com.au

South Australia


Telephone 03-9518 3888 vsales@moffat.com.au

Queensland

Telephone 07-3630 8600 qldsales@moffat.com.au

Western Australia

Telephone 08-9413 2400 wasales@moffat.com.au



UNIT OF MEASUREMENT: **mm**

- 1. Ø 20 mm WATER DRAIN
- 2. 3/4" WATER INLET
- 3. CORD SET

Ice production per 24 hours

Ambient temperature / Water temperature

	10°C / 10°C	21°C / 10°C	32°C / 21°C
NW 1408 AS	650	630	520
NWH 1408 AS	680	650	530

Dimensions

Width: 760mm
Depth: 620mm
Height: 1001mm
Nett weight: 130kg
Packed weight: 145kg

Water consumption

Air cooled version: 29.5 litres per hour (NW 1408 AS)

31.0 litres per hour (NWH 1408 AS)

Electrical rating

Air cooled version: 230-240V, 1P+N+E, 50Hz, 2100W,

20A cordset supplied

No. Circuit wire: 5

Compressor: 9300W

Energy consumption: 68kW/hr (NW 1408 AS) 60.8kW/hr (NWH 1408 AS)

Refrigerant type

R404a

Installation distance from wall

Rear 100mm Sides 150mm

Operating requirement air temperature 10-43°C

Water connection requirements

Inlet connection: R ¾"
Cold water: 5-38°C
Pressure: 100-500kPa
Water outlet connection: Ø 20mm

Important Notice:

Models and specifications are subject to change without notice. This spec sheet is meant for commercial purpose only. For technical documentation please refer to our service manuals.



© Copyright Moffat Ltd

an Ali Group Company

