specifications

Refrigeration

Dimensional tolerances

95mm high swivel castors

OD1100-2

CABINET DIMENSIONS Open Deck Fridge (LED) **External** Internal Height 2015-2195mm* 1375mm 1285 Width 1285mm 1180mm 830mm 545mm Depth 1.05m² Floor area **Gross volume** 1020L 830 Total height with standard 155mm sign is 2015mm. 155mm LED illuminated Total height with optional 335mm high sign is 2195mm. sign (optional 335mm high sign also available) 55

Before installing this cabinet allow the following dimensional tolerances: 030 Internal opening LED illuminated -Overall cabinet Linear interior dimensions Less than 1 metre ±5mm More than 1 metre | -5mm to +10mm Pull-down night blind Length of multiple cabinets At each joint At each end wall +15mm Removable spill -5mm to +10mm +15mm trays -735 Bottom mounted Power cord refrigeration unit CAREL ir33 95 electronic controller

CABINET SPECIFICATIONS

Doors n.a

Internal opening size 1140mm wide x 1030mm high

Shelves 4 x adjustable height, angled shelves (2 shelves 1150mm x 350mm and 2

shelves 1150mm x 390mm) and 1 x fixed in place, angled bottom tray (1150mm

x 400mm).

Weight 282 kg

Electrical safety climate class 3

Internal lighting1 x horizontal top light: 24W T7 LED tube (1150mm)Sign lighting1 x horizontal sign light: 20W T7 LED tube (1150mm)

Power cord2.5m flexible power cord with 3-pin plugElectrical220-240 Volts a.c. 50 Hz, Chiller: 5.8 Amps

Temperature range 0°C to +5°C

GEMS class M1

GEMS energy consumption 18.31 kWh/24h

GEMS annual running cost \$2,006 p.a. (@ \$0.30/kWh)

Refrigeration system Bottom mount removable refrigeration unit with electronic controller (UB80AFD)

Electronic controller CAREL ir33 electronic controller

Refrigerant R452A / 1100g
Nominal compressor capacity 2090 Watts

Insulation 50mm thick, high density cyclo-isopentane polyurethane foam

SKOPE Industries Limited reserve the right to alter specifications without notice. Copyright © 2017 SKOPE Industries Limited



PSS0507 Rev. 1.3 Mar. 2021





