



MODEL

Q70FRI/G415

#### CODE

CR1014839

## **1 BASIN GAS DEEP FAT FRYER 15 LT**

## QUEEN7

- 15/10 worktop thickness
- Stainless steel, Scotch-Brite finish
- · Sturdy and powerful with compact design
- Depth of 700 mm means it will fit the most common configurations
- Catalogue offers more than 300 standard models
- Worktop, base cabinet and oven Versions
- Twin-piece knobs prevent the infiltration of dirt and are watertight
- Gas kitchens having burners with various configurations and power ratings: 3.5 kW - 5.7 kW - 7.0 Kw
- Wide range of accessories



# Technical / functional characteristics

- Fully moulded top, obtained from a single large stainless steel plate.
- · Large capacity shaped cooking pots, with wide vertical expansion zone to avoid depositing of foam during loading.
- Automatic temperature adjustment thermostat up to 190°C.
- Fire-proof safety thermostat (230°C).
- Oil drain valves.
- Support for baskets and lids.
- Steel tubolar burners outside the tank.
- Oil drain tap.
- Pilot burner piezo ignition.

	. <u>.</u>
DIMENSIONS	
Width (mm)	400
Depth (mm)	700
Height (mm)	900
Gas connection (Ø)	1/2"
Electric connection (V/~/Hz)	
Cold water connection (Ø)	
Hot water connection (Ø)	

SCOTS ICE AUSTRALIA

Cold soft water connection (Ø)	
Drain (Ø)	
Gas power (Mj/hr)	50
Electric power (kW)	
Plate dimensions (mm)	
Tank capacity (L)	
Tank dimensions (mm)	
Internal oven dimensions (mm)	

Scots Ice Australia Foodservice Equipment 5/175 James Ruse Drive, Rosehill NSW 2142 - Free Call: 1800 222 460 Email: info@scotsice.com.au - Website: www.scotsice.com.au






### MODEL Q70FRI/G415

CODE CR1014839

### MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm- MESURES EN cm MEDIDAS EN cm - MATEN IN cm - DIMENSIONES EN cm



	Legenda - Legende - Key - Légende - Leyenda - Legenda - Legenda			
E	Pressacavo entrata linea elettrica - Stopfbuchse - Electric cable stress relief - Presse étoupe de câble él - Pisacable - Elektrische kabelwartel - Entrada cabo eléctrico	G	Arrivo gas - Gasanschluss - Gas connection - Arrivée gaz - Union de gas - Gasaansluiting - Ligação gás EN 10226-1 R 1/2; EN ISO 228-1 G 1/2 (DK)	
s	Attacco scarico acqua - Wasserablauf - Water outlet - Vidange de l'eau - Desaguadero - Wateraftapaansluiting - Junção descarga água	H20	eau - Union de agua - Wateraansluiting - Junção	
S1	Scarico vasca - Wannenabflussrohr - Pan outlet - Vidange du bac - Descarga cuba - Water toevoer - Descarga da cuba		alimentação água Calda - Heiss - Warm - Chaude - Caliente - Warm - Morno Fredda - Kalt - Cold - Froid - Fria - Koude - Frio	
S2	Valvola di depressione - Anti-depression valve - Unterdruck ventil - Soupape de dépression - Válvula de dépresión - Onderdrukklep - Válvula de depressão			
S3	Scarico acqua intercapedine - Wasserablauf Zwischenraum - Jacket water drain Evacuation eau double envelope - Descarga de agua			
	intersticios - Afvoer water tussenruimte - Descarga de água na marmita com Sistema de aquecimento indirecto	L	Rubinetto di livello - Level tap - Wasserhahn - Robinet de niveau - Grifo de nivel - Niveaukraan - Torneira de nível	
S4	Scarico - Abflussrohr - Drain - Tuyau d'évacuation - Tubo de drenaje - Aftapbuis - Tubulação de dreno			