

## Sapiens

# Blue Seal Electric Combi Steamer **SAPIENS** E21SDW 20 x 1/1 GN



- Manual controls
- Direct steam injection system
- Multi-point core temperature probe
- High visibility display
- Two speed fan
- 90 preset recipe programs
- 99 free programs with 4 cycles, automatic sequence
- Multiprogram keypad for quick, "press and go" program selection with nine positions
- Electronic thermostat 30° 300°C
- Auto-reversing fan rotation
- Autoclima with automatic vent
- Fast-Dry, quick dehumidification of the cooking chamber
- Built-in retractable hand shower with tap
- LM automatic cleaning system with separate container for CombiClean liquid detergent
- 4 LED's to indicate actual cooking cycle in programme mode
- ECOVAPOR automatic control of the steam saturation in the cooking chamber
- ECOSPEED oven optimises and controls the delivery of energy to maintain correct cooking temperature
- USB connection

#### GENERAL FEATURES

- INCOLOY 800 type heating elements
- Stainless steel construction
- Perfectly smooth, water tight chamber
- Pivoting fan suction panel
- Front removable control panel for easy servicing
- Hygienic plug-in door seal for easy to remove day-to-day cleaning
- Adjustable door hinges
- Self draining door condensate drip tray
- Door with 3 locking points
- Halogen oven light









FAST-DR

- Oven door handle mechanism allows either left or right operation
- Cool to touch door with double tempered glass with air chamber and interior heat-reflective glass
- Hinged inner glass for easy cleaning
- Constant self-diagnosis for error recognition
- IPX5 spray-proof and hose proof.
- Rack runners for GN loading

#### OPTIONAL FEATURES

- Right hinged door
- Trolley for  $600 \times 400 \text{ trays}$
- Configuration for connection to extraction hood



## Sapiens

# Blue Seal Electric Combi Steamer **SAPIENS** E21SDW 20 x 1/1 GN

#### **Dimensions**

Width 960mm Depth 825mm Height 1810mm Weight 260kg

#### **Packed Dimensions**

Width 1130mm Depth 1050mm Height 2060mm Weight 370kg

#### Shelves

1/1 GN 20 Shelf Spacings 63mm

#### Installation requirements

(for precise installation instructions, please refer to the unit's installation manual).

### Power connection requirements

Multi pole circuit breaker and all pole disconnection isolator switch installed near the appliance. Supply line voltage

400-415V ~ 50Hz, 3P+N+E Special voltage options available on request.

#### **Power Connection**

Total (kW) 31.8 Convection power (kW) 30 Rated Current (A) (400V) 46

#### Installation clearances

- rear 25mm - right 500mm\* - left 50mm

\*Clearance required on fixed installations for service accessibility.

If heat sources are located near the RH side of the Sapiens combi, ensure that a minimum distance of 400mm is maintained. Install in accordance with local body regulations only on horizontal surfaces and not against combustible walls.

### Water connection requirements

- cold water
- flow pressure (200-500kPa)
- soft water connection\*
- shut-off valve with return flow inhibitor and dirt filter
- water supply R3/4
- R50 waste water

(\*Water softener may be required. Please refer to installation manual for water treatment values.)



Australia www.moffat.com.au

New Zealand www.moffat.co.nz

#### Australia Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Ph 03-9518 3888 Fax 03-9518 3833 vsales@moffat.com.au www.moffat.com.au

New South Wales Ph 02-8833 4111 nswsales@moffat.com.au

South Australia Ph 03-9518 3888 vsales@moffat.com.au


Queensland Ph 07-3630 8600 qldsales@moffat.com.au


Western Australia Ph 08-9202 6820 bgarcia@moffat.com.au

#### New Zealand Moffat Limited

Christchurch 16 Osborne Street Christchurch 8011 Ph +64 3-389 1007 Fax +64 3-389 1276 sales@moffat.co.nz

Auckland Ph +64 9-574 3150 sales@moffat.co.nz









Electric power supply cable inlet



Air extraction



inlet



Steam vent and chamber pressure drop safety device



Normal water inlet



Liquid outlet

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd Moffat 7.14 / 1413



