

Sapiens

Blue Seal Gas Combi Steamer SAPIENS G7SDW 7 x 1/1 GN



- Manual controls
- Multi-point core temperature probe
- High visibility display
- Two speed fan
- 90 preset recipe programs
- 99 free programs with 4 cycles, automatic sequence
- Multiprogram keypad for guick, "press and go" program selection with nine positions
- Electronic thermostat 30° 300°C
- Auto-reversing fan rotation
- Autoclima with automatic vent
- Built-in retractable hand shower with tap
- SCS (Solid Clean System) automatic cleaning system with built in tank and automatic detergent dispenser
- 4 LED's to indicate actual cooking cycle in programme mode
- ECOVAPOR automatic control of the steam saturation in the cooking chamber
- ECOSPEED oven optimises and controls the delivery of energy to maintain correct cooking temperature
- Fast-Dry, quick dehumidification of the cooking chamber
- USB connection

GENERAL FEATURES:

- Direct steam injection system
- High efficiency heat exchanger and gas burner system
- Stainless steel construction
- Perfectly smooth, water tight chamber
- Adjustable door hinge for optimal seal
- Halogen oven light
- Oven door handle mechanism allows either left or right _ operation
- Cool to touch door with double tempered glass with air chamber and interior heat-reflective glass

- Hinged inner glass for easy cleaning
- Constant self-diagnosis for error recognition
- IPX5 spray-proof and hose proof
- Rack runners for GN loading

OPTIONAL FEATURES

- Right hinged door
- Side runners for 600 x 400 trays
- Configuration for connection to extraction hood











FCOVAPOR

GREEN FINE

SOLID CLEAN



Sapiens

Blue Seal Gas Combi Steamer SAPIENS G7SDW 7 x 1/1 GN

Dimensions

Width	875mm
Depth	825mm
Height	820mm
Weight	125kg

Packed Dimensions

Width	950mm
Depth	990mm
Height	1000mm
Weight	142kg
Shelves	
1/1 GN	7

1/1 GN

70mm Shelf Spacings

Installation requirements (for precise installation

instructions, please refer to the unit's installation manual).

Power connection requirements

230-240V, 50Hz, 1P+N+E Supply line voltage: 0.5 kW Electrical power: 2.2 A Rated current: 3 pin plug (10A) cordset fitted

Gas Connection

Nominal gas consumption: 38 MJ/hr Gas connection size: R1/2 Exhaust connection to ventilation system with safety switch. Observe regulations for gas

suppliers.

Installation clearances 25mm - rear 500mm* - right - left 50mm *Clearance required on

fixed installations for service accessibility. If heat sources are located near the RH side of the Sapiens combi, ensure that a minimum distance of 400mm is maintained.

Install in accordance with local body regulations only on horizontal surfaces and not against combustible walls

Water connection requirements

- cold water flow pressure
- (200-500kPa)
- soft water connection* shut-off valve with return
- flow inhibitor and dirt filter
- water supply R¾
- connection

required. Please refer to installation manual for water treatment values.)

R50 waste water

(*Water softener may be

Australia www.moffat.com.au

> New Zealand www.moffat.co.nz

Australia Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Ph 03-9518 3888 Fax 03-9518 3833 vsales@moffat.com.au www.moffat.com.au

New South Wales Ph 02-8833 4111 nswsales@moffat.com.au

South Australia Ph 03-9518 3888 vsales@moffat.com.au

Queensland Ph 07-3630 8600 gldsales@moffat.com.au

Western Australia Ph 08-9202 6820 bgarcia@moffat.com.au

New Zealand Moffat Limited

Christchurch 16 Osborne Street Christchurch 8011 Ph +64 3-389 1007 Fax +64 3-389 1276 sales@moffat.co.nz

Auckland Ph +64 9-574 3150 sales@moffat.co.nz

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd Moffat 7.14 / 1413



