



SL860V Bonvue Chilled Food Display

Quick Overview

- 1800 mm Wide
- 4 Display Levels
- Black Trim & Shelving
- Triple Glazed Front With Heated Wire Filaments To Stop Condensation
- Danfoss Or Aspera Compressors
- German Ëbm-Pabst Fans
- Lighting Over Each Level
- Self Evaporating Drainage
- Digital Temp. Control & Read-Out
- Sliding Rear Glass Doors
- Very High Humidity
- Easy To Clean
- 3 Levels Of Wired Shelving Plus Floor

Description

Bonvue Chilled Food Display - SL860V

Chilled Square Stainless Steel Food Display

This powerful deluxe display from catering equipment giant, Bonvue, is an ideal cake display fridge necessary for any bakery or cafe wanting to gain the competitive edge. This large unit aims to provide an impressive view for showcasing pastries, cakes, wraps, sandwiches and light meals within a cooled environment.

The sl860v features a larger capacity and a formidable engine that makes it almost twice as powerfully efficient in comparison to the smaller models within this series.

This deluxe cake display has three adjustable shelves, powerful secop compressors for functionality, a stainless-steel frame for sturdiness, LED lighting to ease interior viewing, digital temperature control and a triple glazed front with heated filaments.

Ambient 40°c & 90% Rh

Refrigerated 2 to 8°C

- 1800 mm Wide
- 4 Display Levels
- Black Trim & Shelving
- Triple Glazed Front With Heated Wire Filaments To Stop Condensation
- Danfoss Or Aspera Compressors
- German Ëbm-Pabst Fans
- Lighting Over Each Level
- Self Evaporating Drainage
- Digital Temp. Control & Read-Out
- Sliding Rear Glass Doors
- Very High Humidity
- Easy To Clean
- 3 Levels Of Wired Shelving Plus Floor

- * Subject To 2nd & 3rd Year Service And Inspection
- * Also Subject To The Terms In The Warranty Section Of Our Terms & Conditions

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration

Your Shipping Specifications

Net Weight (Kg)	350
Width (mm)	1800
Depth (mm)	740
Height (mm)	1350
Packing Width (mm)	815
Packing Depth (mm)	1850
Packing Height (mm)	1520
Power	240V; 1056W