



SL880V Bonvue Chilled Food Display

Quick Overview

2400 mm wide Chilled Square Stainless Steel Food Display TEMPERATE thermaster

4 Display Levels

Black Trim & Shelving

- triple glazed front with heated wire filaments to stop condensation
- Ambient 40°C & 90% RH
- 2 to 8°C
- Danfoss or Aspera compressors
- German ËBM-Pabst fans
- illuminated front panel
- lighting over each level
- self evaporating drainage
- digital temp. control & read-out
- sliding rear glass doors
- very High Humidity
- easy to clean
- 3 levels of wired shelving plus floor

Description

Chilled Square Stainless Steel Food Display - SL880V

The SL880V is massive in size and provides plenty of coverage for café and bakery owners who want to present their freshest, most popular foods for the entire world to see.

Part of Bonvue's reputable collection of high-end deluxe display cases, the SL880V is the biggest, most expansive unit available in this series.

The SL880V offers an eye-catching display for your light meals including sandwiches, wraps, salads, pastries, yogurts and cakes.

The biggest within Bonvue's collection, this prized display is made for larger-scale business selling a vast range of snacks, sweets and fresh foods, and contains great interior lights, triple glazed glass, temp controls, quality compressors and fans.

Practical, reliable and a relentless worker, the SL880V is a dream display for any business owner wanting to get the best presentation of their menu possible.

TEMPERATE thermaster PREMIUM

4 Display Levels

2400 mm wide

- Black Trim & Shelving
- triple glazed front with heated wire filaments to stop condensation
- Ambient 40°C & 90% RH
- 2 to 8°C
- Danfoss or Aspera compressors
- German ËBM-Pabst fans
- illuminated front panel
- lighting over each level
- self evaporating drainage
- digital temp. control & read-out
- sliding rear glass doors
- very High Humidity
- easy to clean
- 3 levels of wired shelving plus floor

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration

Your Shipping Specifications

Net Weight (Kg)	440
Width (mm)	2400
Depth (mm)	740
Height (mm)	1350
Packing Width (mm)	815
Packing Depth (mm)	2450
Packing Height (mm)	1520
Power	240V; 1313W