



TECHNICAL INFORMATION	
Dimensions	550w x 605d x 830-860h
Rack Dimension	500 x 500
Clear Entry Height	343
Rinse Water Consumption	3.0L Per Cycle
WATER CONNECTIONS	
Connection Point	3/4 inch (19mm)
Inlet Temperature	55c Max
Flow Rate	11 L/Min
Flow Pressure	2 bar
ELECTRICAL	
Single Phase	240v 1N - 15amp (TCL 3.18Kw)
GENERAL DATA	
Weight (Net/Gross)	44Kg / 57Kg
Tank Capacity	14.5L
Tank Capacity Noise Emission	14.5L 70dB(A)
Noise Emission	70dB(A)
Noise Emission Cycle Times	70dB(A) 1.5 / 3.0 / 5.0 Minute
Noise Emission Cycle Times Theoretical Capacity	70dB(A) 1.5 / 3.0 / 5.0 Minute
Noise Emission Cycle Times Theoretical Capacity STANDARD INCLUSIONS	70dB(A) 1.5 / 3.0 / 5.0 Minute 720 plates per hour
Noise Emission Cycle Times Theoretical Capacity STANDARD INCLUSIONS 1x 15amp Plug and Lead	70dB(A) 1.5 / 3.0 / 5.0 Minute 720 plates per hour
Noise Emission Cycle Times Theoretical Capacity STANDARD INCLUSIONS 1x 15amp Plug and Lead 1x 1M Flexible Water Conne	70dB(A) 1.5 / 3.0 / 5.0 Minute 720 plates per hour ection Hose
Noise Emission Cycle Times Theoretical Capacity STANDARD INCLUSIONS 1x 15amp Plug and Lead 1x 1M Flexible Water Connection 1x 1M Flexible Waste Hose	70dB(A) 1.5 / 3.0 / 5.0 Minute 720 plates per hour ection Hose

STANDARD FEATURES

- LCD control with digital temperature display
- Drain pump
- Integrated chemical pumps
- Dual filtration
- Insulated door
- Anti-block wash arms, lightweight and easy to remove for cleaning
- Made in UK
- Watermark approved

