



HOSHIZAKI REFRIGERATION

HFE-70B Upright Reach in Freezer

Product Features

- Operating ambient 5°C to 43°C (tropical conditions)
- Cabinet temperature microprocessor controlled and adjustable from -27°C to -7°C
- DC evaporator fans, 80% more energy efficient than AC fans
- 76mm lockable castors
- Energy saving computer controlled frame heater eliminating condensation on exterior
- Stainless steel interior and exterior
- Removable door gaskets for easy cleaning
- GASTRONORM specification standard
- Integral Refrigeration
- HRE-70 and HFE-70 standard with 4 shelves
- HRE-140 and HFE-140 standard with 8 shelves
- 2 years parts and labour warranty



Range

- HRE-70B
- HRE-140B
- HFE-70B
- HFE-140B





HFE-70B Upright Reach in Freezer

Product Specifications

- **Dimensions**
Width: 700 mm
Depth: 850 mm
Height: 2015 mm
- **Inside Dimensions**
Width: 596 mm
Depth: 678 mm
Height: 1484 mm
- **Packed Dimensions**
Carton (Wooden Pallet)
Width: 750 mm
Depth: 940 mm
Height: 2100 mm
- **Weight**
Net: 116kg
Packed: 131kg
- **AC Supply Voltage**
220-240/50/1
- **Electric Circuit Protection**
Earth Wire, Circuit Breaker
- **Exterior**
Stainless Steel, Galvanized Steel
(Rear, Bottom)
- **Interior**
Stainless Steel
- **Amperage**
3.51A
- **Refrigeration System**
Forced Air Circulation Interior Fan
DC12V 4W x 2
- **Defrost System**
Heater
- **Temperature Control**
Microprocessor (Digital temp. indication)
Adjustable from -25°C to -7°C
- **Defrost Control**
Microprocessor
- **Drain Evaporator Pan**
Stainless steel, 170W
- **Castor**
Urethane (76mm DIA, 115mm High)
- **Effective Capacity**
Approx. 631L
- **Insulation**
Polyurethane foam
- **Refrigerant**
R404a
- **Heat Rejection**
735W
- **Operating Conditions**
Ambient temperature: 5 – 43°C

