



HOSHIZAKI
REFRIGERATION

HRE-70B

Upright Reach in Refrigerator

Product Features

- Operating ambient 5°C to 43°C (tropical conditions)
- Cabinet temperature microprocessor controlled and adjustable from 0°C to 16°C
- DC evaporator fans, 80% more energy efficient than AC fans
- 76mm lockable castors
- Energy saving computer controlled frame heater eliminating condensation on exterior
- Stainless steel interior and exterior
- Removable door gaskets for easy cleaning
- GASTRONORM specification standard
- Integral Refrigeration
- HRE-70 and HFE-70 standard with 4 shelves
- HRE-140 and HFE-140 standard with 8 shelves
- 2 years parts and labour warranty



Range

- HRE-70B
- HRE-140B
- HFE-70B
- HFE-140B



HRE-70B Upright Reach in Refrigerator



HOSHIZAKI
REFRIGERATION

Product Specifications

- Dimensions**
 Width: 700 mm
 Depth: 850 mm
 Height: 2015 mm
- Inside Dimensions**
 Width: 596 mm
 Depth: 678 mm
 Height: 1484 mm
- Packed Dimensions**
 Carton (Wooden Pallet)
 Width: 750 mm
 Depth: 940 mm
 Height: 2100 mm
- Weight**
 Net: 116kg
 Packed: 131kg
- AC Supply Voltage**
 220-240/50/1
- Electric Circuit Protection**
 Earth Wire, Circuit Breaker
- Exterior**
 Stainless Steel, Galvanized Steel
 (Rear, Bottom)
- Interior**
 Stainless Steel
- Amperage**
 2.06
- Refrigeration System**
 Forced Air Circulation Interior Fan
 DC12V 4W x 1
- Defrost System**
 Off-Cycle
- Temperature Control**
 Microprocessor (Digital temp. indication)
 Adjustable from 0°C to 16°C
- Defrost Control**
 Microprocessor
- Drain Evaporator Pan**
 Stainless steel, 170W
- Castor**
 Urethane (76mm DIA, 115mm High)
- Effective Capacity**
 Approx. 631L
- Insulation**
 Polyurethane foam
- Refrigerant**
 R134a
- Heat Rejection**
 535W at 43°C ambient
- Operating Conditions**
 Ambient temperature: 5 – 43°C

