



# HOSHIZAKI REFRIGERATION

## HRE-140B Upright Reach in Refrigerator

### Product Features

- Operating ambient 5°C to 43°C (tropical conditions)
- Cabinet temperature microprocessor controlled and adjustable from 0°C to 16°C
- DC evaporator fans, 80% more energy efficient than AC fans
- 76mm lockable castors
- Energy saving computer controlled frame heater eliminating condensation on exterior
- Stainless steel interior and exterior
- Removable door gaskets for easy cleaning
- GASTRONORM specification standard
- Integral Refrigeration
- Rated for 43°C Ambient (Tropical conditions)
- HRE-70 and HFE-70 standard with 4 shelves
- HRE-140 and HFE-140 standard with 8 shelves
- 2 years parts and labour warranty



### Range

- HRE-70B
- HRE-140B
- HFE-70B
- HFE-140B





## HRE-140B Upright Reach in Refrigerator

### Product Specifications

- **Dimensions**  
Width: 1400 mm  
Depth: 850 mm  
Height: 2015 mm
- **Inside Dimensions**  
Width: 1296 mm  
Depth: 678 mm  
Height: 1484 mm
- **Packed Dimensions**  
Carton (Wooden Pallet)  
Width: 1450 mm  
Depth: 940 mm  
Height: 2100 mm
- **Weight**  
Net: 164kg  
Packed: 189kg
- **AC Supply Voltage**  
220-240/50/1
- **Electric Circuit Protection**  
Earth Wire, Circuit Breaker
- **Exterior**  
Stainless Steel, Galvanized Steel  
(Rear, Bottom)
- **Interior**  
Stainless Steel
- **Amperage**  
2.89
- **Refrigeration System**  
Forced Air Circulation Interior Fan  
DC12V 4W x 1
- **Defrost System**  
Off-Cycle
- **Temperature Control**  
Microprocessor (Digital temp. indication)  
Adjustable from 0°C to 16°C
- **Defrost Control**  
Microprocessor
- **Drain Evaporator Pan**  
Stainless steel, 170W
- **Castor**  
Urethane (76mm DIA, 115mm High)
- **Effective Capacity**  
Approx. 1379L
- **Insulation**  
Polyurethane foam
- **Refrigerant**  
R134a
- **Heat Rejection**  
940W at 43°C ambient
- **Operating Conditions**  
Ambient temperature: 5 – 43°C

