

### Product Information:

- High performance XL hood-type dishwasher with pre-fitted, easy to install energy savings device (ESD)
- **E-Management:** intuitive and advanced electronic interface
- **PRS System:** break tank, 316 atmospheric boiler, rinse booster pump
- **HD System:** for maximum uninterrupted performance
- **ES System:** energy savings device (ESD)
- Increased capacity with 600x500mm baskets (500x500mm compatible)
- XL Filters robust and additional upper tank scrap filters in stainless steel
- Larger HP vertical self-draining wash pump
- Larger HI FLOW stainless steel wash and rinse arms
- Larger elements in wash tank and boiler
- Four wash cycles 90/120/180 seconds, and 9 minute deep clean
- Green standby function that reduces energy consumption when idle
- Low water consumption of 2.5 litres per cycle, minimising water, energy and detergent use
- Pressed wash tank with rounded corners, for increased hygiene
- Manual lift with fully enclosed rear, 3 spring support
- Automatic drain pump with self-cleaning function
- Built in thermostop, ensures correct rinse temperatures
- Built in detergent and rinse-aid injection
- **18-months parts and labour warranty**



### Included Accessories:

- 1 x glass rack 500x600mm
- 2 x plate rack 500x600mm
- 2 x cutlery basket
- 1 x water inlet hose (length 1.5m)
- 1 x drain hose (length 2m)
- Fitted with 150mm adjustable legs

### Optional Accessories:

- Twin hood system
- Remote interface
- Inlet and outlet benches
- Additional baskets

### Specifications:

Model	AH60.42EES
W x D x H (mm)	657 x 793 x 2294
Note: Dimensions do not include handle. Hood open	
Weight	179kg
Packed Dimensions (mm)	770 x 930 x 2254
Packed Weight	198kg
Total Connected Load	14.8kW / 25A circuit L1 = 21A / L2 = 21A / L3 = 21A
- Convertible to: (Low Power Option)	10.3kW / 15A Circuit L1 = 15A / L2 = 15A / L3 = 15A
Note: Unit can be converted to low power option on site by a qualified electrician. This may affect the output of the unit.	
Electrical Connection	3Ø+N+E 415VAC / 50Hz (Lead fitted, on-site connection)
Water Quantity Per Cycle	2.5 Litres
Water Connection	1.5m Hose / 3/4" BSP
Water Inlet Pressure	100 - 500KPA
Tempered water supply	10°C - 25°C
Waste Connection	2m Hose / ø20.5mm

### Legend:

A Electrical Connection	D Detergent Line
B Water Connection	E Rinse-Aid Line
C Drain Connection	

