

BA14M-SM

OSMOSIS TREATMENT UNIT - 10 AMP



WASHING WITH WATER FREE OF MINERAL SALTS

- No need to polish glasses and cutlery by hand
- Lower concentration of detergent and rinse aid
- No encrustation of scale in any part of the glass/dishwasher
- Easy access for service maintenance
- 12 months parts and labour warranty

PRODUCT FEATURES

- **Compact reverse osmosis unit that is compatible with any Smeg underbench glasswasher or dishwasher**
- Connected glasswasher can be 15 Amp single phase or three phase
Connected dishwasher needs to be three phase
- **Hourly production (1): 120 lt/hr**
- **Product performance and water quality data are visible live via the smartphone app and bluetooth**
- Inlet water pre-treatment: active carbon filter
- Inlet water maximum temperature: 35°C
- Low water pressure alarm
- Anti-flooding alarm with automatic stop
- Automatic membrane flushing during prolonged inactivity
- Hour counter and litres counter
- Adjustment and display of permeate salinity
- Filters depletion alarm
- **10 Amp plug**
- **12 months parts and labour warranty**

BA14M-SM

OSMOSIS TREATMENT UNIT - 10 AMP

TECHNICAL SPECIFICATIONS

Dimensions (mm) (WxDxH)	160x480x540
Type of interface	Electronic
Supplied water temperature (°C)	From cold to 35°
Hourly production (lt/hr) (1)	120lt
Power supply/total power installed	230V 1N 50Hz/10 amp plug
Recovery rate	50:50
Inlet water pressure (min)	1.0 bar / 100 kPa
Inlet water pressure (max)	6.0 bar / 600 kPa
Minimum inlet flow rate	10 lt / min
Water quality	Municipal potable water feed only

