

SKOPE®

BACKBAR X™

Combining great looks with the latest energy savings and cooling performance technology, BackBar X cabinets make a stylish addition to any bar.



**Refreshed.
Reworked.
Redesigned.**

Bar refrigeration has never looked so good

The BackBar series has undergone a facelift. The newly designed BackBar X features a sharper, seamless louvre blade design, while the doors have been upgraded to energy efficient, frameless glass, featuring new anti-condensation technology, and are equipped with sleek easy grip handles.

BackBar X offers far more than cosmetic changes. In addition to quieter operation, the range offers unrivalled energy savings and advanced design features to deliver optimal cooling performance.

BACKBAR X



Ultra-modern
look



Quieter
operation



Cheaper to run



Easy servicing



Long-life
LED lights

An Exciting New Look

Ultra-Modern Look

Frameless glass doors with superior energy efficient anti-condensation technology, louvre blade design, and a new easy grip handle.

Long-Life Reliability

Solid engineering, quality materials and industrial grade powder coat finish, ensures your cabinet maintains its appearance, product durability and high performance.

Easy Servicing

BackBar X has been designed for trouble-free operation; our easy service design allows quick access for cleaning and maintenance, minimising disruption.

Maximum Cooling Performance

Serve your customers a perfectly cold beverage every time due to our cleverly designed internal airflow system.

Quieter Operation

Create a comfortable service environment with our integrated hush kit.

Long-Life LED Lights

Premium quality LED lights for effective merchandising.

Storage

More internal space for product storage, reducing re-stocking time and increasing your selling time.



With SKOPE's Adaptive Design, you get greater flexibility to reflect an individual look.

SKOPE makes it easy to integrate bar refrigeration into your establishment with many customisable options available, including LED lighting options, wall or plinth mounting, a wide range of Dulux powder coated colour finishes, pass through, or specific dimensions that can maximise your available space to boost sales.

24%*

Energy Savings

BackBar X models now provide you with a quicker rate of return, saving up to \$200 per year.

*24% less energy than the previous model. Based on 30 cents per kW, calculated using BB380X TEC - 5,811kW/24h

Significant Energy Savings



BB380X

Uses 24% less energy than the previous model

Saving \$200*
per year



BB580X

Uses 22% less energy than the previous model

Saving \$235*
per year



BB780X

Uses 14% less energy than the previous model

Saving \$197*
per year

*Based on 30 cents per kW.

BackBar X Product Range

Model No.	Description	Dimensions (mm)	Electrical Information	
		(HxWxD)	KW	Amps
Standard - Integral				
BB380X-2SW	2 door integral	920 x 1500 x 590	0.82	3.4
BB580X-3SW	3 door integral	920 x 2060 x 590	0.86	3.6
BB780X-4SW	4 door integral	920 x 2620 x 590	1.08	4.5
Tropical - Integral				
BB380XT-2SW	2 door integral	920 x 1500 x 590	0.82	3.4
BB580XT-3SW	3 door integral	920 x 2060 x 590	0.86	3.6
BB780XT-4SW	4 door integral	920 x 2620 x 590	1.08	4.5
Standard - Remote				
BB380Xr-2SW	2 door remote	920 x 1355 x 590	0.17	0.7
BB580Xr-3SW	3 door remote	920 x 1915 x 590	0.22	0.9
BB780Xr-4SW	4 door remote	920 x 2475 x 590	0.34	1.4
Tropical - Remote				
BB380XTr-2SW	2 door remote	920 x 1355 x 590	0.17	0.7
BB580XTr-3SW	3 door remote	920 x 1915 x 590	0.22	0.9
BB780XTr-4SW	4 door remote	920 x 2475 x 590	0.34	1.4

BackBar X is available in 2, 3, 4 swing door models. Available in tropical, integral and remoted, black, stainless steel and powder coated finishes. Sliding door currently not available.

BACKBAR X SERIES

Premium Range

Display / Beverage

Combining great looks with the latest energy savings and cooling performance technology, these cabinets make a stylish addition to any bar concept. The BackBar X range is designed to maximise beverage sales as well as being reliable, durable and aesthetically unique.

- Options**
- R/H Services
 - S/S Countertop
 - Additional shelves
 - Door lock kit
 - Tropical swing door
 - Pass through (rear loading)
 - Light dimmers



Significantly More Energy Efficient
than previous swing door models, saving you up to \$200 per year

Ultra-Modern Look
Frameless glass doors, new louvre blade design, and easy grip handle

Long-Life Reliability

- Updated controller with manual light switch
- Full length, LED horizontal light
- Quality materials and powder coated finish

Performance and Maintenance

- Redesigned airflow and fan blade design ensures beverages are chilled quickly and evenly
- New louvre design provides quick and easy maintenance

Integrated Hush Kit
for quieter operation, reduced by 5 dB when compared to previous model

Available In
black, white and stainless steel (additional cost applies on S/S)


Adjustable Legs and Castors
for easy installation, positioning and relocation

Castor and Leg Height
1015 - 1035mm with castors
1070 - 1100 with legs
920mm without


Specifications

BackBar X Series


Display / Beverage




Integral top view




Integral front elevation




Remote front elevation




Integral top view




Integral front elevation




Remote front elevation



Integral top view



Integral front elevation



Remote front elevation

BB380X - SWING/GLASS DOORS

Model	Weight (kg)	Integral/Remote	Chiller/Freezer	
BB380X-2SW	150	Integral	Chiller	Gross Volume 380 litres Total Shelf Area 1.41m ² (including floor) Floor Area 0.89m ² (integral sw.) 0.80m ² (remote sw.)
BB380Xr-2SW	120	Remote	Chiller	
		Integral External (mm)	Remote External (mm)	Internal (mm)
Height*		920	920	758
Width		1500	1355	1020
Depth		590	590	530

- 9.709 MEPS (kWh/24h/m²)
- BB380Xr 2SW remote refrigeration duty 480 Watts at -5°C SST
- +1°C to +4°C in 40°C ambient



BB380X
2 DOOR

BB580X - SWING/GLASS DOORS

Model	Weight (kg)	Integral/Remote	Chiller/Freezer	
BB580X-3SW	190	Integral	Chiller	Gross Volume 580 litres Total Shelf Area 2.20m ² (including floor) Floor Area 1.22m ² (integral sw.) 1.13m ² (remote sw.)
BB580Xr-3SW	160	Remote	Chiller	
		Integral External (mm)	Remote External (mm)	Internal (mm)
Height*		920	920	758
Width		2060	1915	1580
Depth		590	590	530

- 11.175 MEPS (kWh/24h/m²)
- BB580Xr 3SW remote refrigeration duty 580 Watts at -5°C SST
- +1°C to +4°C in 40°C ambient



BB580X
3 DOOR

BB780X - SWING/GLASS DOORS

Model	Weight (kg)	Integral/Remote	Chiller/Freezer	
BB780X-4SW	230	Integral	Chiller	Gross Volume 780 litres Total Shelf Area 2.98m ² (including floor) Floor Area 1.55m ² (integral sw.) 1.46m ² (remote sw.)
BB780Xr-4SW	200	Remote	Chiller	
		Integral External (mm)	Remote External (mm)	Internal (mm)
Height*		920	920	758
Width		2620	2475	2140
Depth		590	590	530

- 8.8 MEPS (kWh/24h/m²)
- BB780Xr 4SW remote refrigeration duty 750 Watts at -5°C SST
- +1°C to +4°C in 40°C ambient



BB780X
4 DOOR



*Height excludes castors (95-110mm) or legs (150-180mm)



Ideal for



Restaurants & cafes



Clubs, pubs & bars



Quick service restaurants



Venues

Australia

Freephone 1800 121 535

Facsimile 1800 121 533

Email enquiry@skope.com.au**New Zealand**

0800 947 5673

+64 (3) 983 3896

enquiry@skope.co.nz

For SKOPE terms and conditions of sale visit skope.com

© 2016 SKOPE Industries Ltd. All rights reserved.

® SKOPE and the SKOPE logo are registered trade marks of SKOPE Industries Ltd.

BackBar X and the BackBar X logo are trademarks of SKOPE Industries Ltd.

SKOPE Industries Ltd. Reserves the right to alter specifications without notice.

Visit skope.com for the most recent specifications.