

Product Information

- High efficiency cooktops with heavy duty electronic components and thick, high-impact Schott Ceran glass-ceramic top, engineered for use in commercial kitchens
 - Easy control via the Helios Standard interface
 - Temperature range from 29°C - 218°C
 - Automatic pan detection for instant energy transmission to the pan & almost no energy consumption when the pan is not present
 - Microprocessor monitors vital components to check for overheating and power supply issues
 - Automatic shut-off feature prohibits overheating
 - Drop-in units feature Stainless steel edging, aluminium housing and control box
 - Integral grease filter and air baffle to ensure cleaner and cooler air intake for optimum reliability
 - 1.2mm thick 304 stainless steel bench top
 - 3mm zinc anneal steel reinforced backing to work top
 - 38mm diameter round stainless steel tube legs, 1.2mm thick
 - Adjustable stainless steel disk feet fitted as standard
 - 1.2mm thick stainless steel under-shelf with top hat stiffening
- 24-month parts and 12-months labour warranty



Specifications

| | | |
|------------------------------|---|---|
| Model | HRD.9500.FB25.4.0900 | HRD.9500.FB35.4.0900 |
| W x D x H (mm) | 900 x 805 x 1050 | 900 x 805 x 1050 |
| Weight | 66kg | 66kg |
| Total Connected Load | 4.8kW x2 | 7kW x2 |
| Electrical Connection | 1Ø + N + E 240VAC / 50Hz 20A plug & lead (1.8m) x2 | 1Ø + N + E 415VAC / 50Hz Lead only (1.8m) 32A plug required x2 |
| Shipping | 1000 x 830 x 1200 / 71kg | 1000 x 830 x 1200 / 71kg |

