

### Product Information

- High efficiency cooktops with heavy duty electronic components and thick, high-impact Schott Ceran glass-ceramic top, engineered for use in commercial kitchens
- Easy control via the Helios Standard interface
- Temperature range from 29°C - 218°C
- Automatic pan detection for instant energy transmission to the pan & almost no energy consumption when the pan is not present
- Microprocessor monitors vital components to check for overheating and power supply issues
- Automatic shut-off feature prohibits overheating
- Drop-in units feature Stainless steel edging, aluminium housing and control box
- Integral grease filter and air baffle to ensure cleaner and cooler air intake for optimum reliability
- **24-month parts and 12-months labour warranty**



### Specifications

<b>Model</b>	HRD.9500.SS25.4	HRD.9500.SS35.4
<b>W x D x H (mm)</b>	692 x 343 x 95	692 x 343 x 95
<b>Weight</b>	14kg	14kg
<b>Total Connected Load</b>	4.8kW	7kW
<b>Electrical Connection</b>	1Ø + N + E 240VAC / 50Hz 20A plug & lead (1.8m)	1Ø + N + E 415VAC / 50Hz Lead only (1.8m) 32A plug required
<b>Cut Out Size (mm)</b>	683w x 334d	683w x 334d
<b>Shipping</b>	813 x 584 x 279 / 19kg	813 x 584 x 279 / 19kg

### Legend

**A** Electrical Connection

