



The spray system produces clear and transparent ice cubes and the patented **Bright Cube** shape grants a longer lasting cube for you to enjoy your cold drinks

Self contained ice maker.

Up to 90kg production per 24/hr of medium ice cube.  
42kg storage bin.


Complete with legs, water & drain hoses + 1 ice scoop.  
10 AMP power supply.

291 mm drain height including legs to finished floor.




## ICE PRODUCTION



### Air Cooled Unit

Air Temp.	Water Temperature			
				
°C	32°	21°	15°	10°
°F	90°	70°	60°	50°
10°	<b>82</b>	<b>85</b>	<b>87</b>	<b>89</b>
50°	181	187	192	196
21°	<b>75</b>	<b>78</b>	<b>80</b>	<b>82</b>
70°	165	172	176	181
32°	<b>62</b>	<b>65</b>	<b>67</b>	<b>69</b>
90°	137	143	148	152
38°	<b>51</b>	<b>54</b>	<b>56</b>	<b>58</b>
100°	112	119	123	128

### Water Cooled Unit

Air Temp.	Water Temperature			
				
°C	32°	21°	15°	10°
°F	90°	70°	60°	50°
10°	<b>82</b>	<b>85</b>	<b>87</b>	<b>89</b>
50°	181	187	192	196
21°	<b>78</b>	<b>82</b>	<b>84</b>	<b>86</b>
70°	172	181	185	190
32°	<b>73</b>	<b>76</b>	<b>79</b>	<b>82</b>
90°	161	168	174	181
38°	<b>69</b>	<b>72</b>	<b>75</b>	<b>78</b>
100°	152	159	165	172

## CUBE TYPE



**20g weight**  
**BRIGHT CUBE**  
32mm x 35mm x 37mm

The Bright Ice Cube, appreciated for its versatility, is perfect for use in ice buckets, whiskey on the rocks, cocktails and appetisers. The crystal clear appearance of the Bright Cube makes it essential when a high quality is required.

## CONTROL PANEL



Switch On/Off


Ice size regulation screw


## BIN CAPACITY

42 kg - 93 lbs | 2100 pcs

## DIMENSIONS

W x D x H (mm)

 700 x 580 x 910/1030

 760 x 630 x 1070

## OPERATING REQUIREMENTS

Rejected Heat 2865 W





Air Volume 450 m<sup>3</sup>/h
















220-240/50/1



R134a GWP = 1430

MIN		MAX
10°C (50°F)		40°C (104°F)
5°C (41°F)		35°C (95°F)
- 10 %		+ 10 %
1 Bar (14 psi)		5 Bar (70 psi)

## SPECIFICATIONS

	 cond	 comp. W	 ABS. W	 Fuse	 kWh/100kg	 L / hr	 kg	 lbs	 kg	 lbs	 Ton CO2 equiv.
<b>CS90 A</b>		1910	980	10	28.2	7.45	61	134	73	161	0.50
<b>CS90 W</b>		1910	820	10	19.7	51.4	61	134	73	161	0.53

