



Description

FED-X S/S Two Door Upright Freezer - XURF650S1V

Quick Overview

- Gross Volume: 650L
- Net Volume: 465L
- Max Ambient Temperature: 43°C; 60%RH
- Temperature Range: -18 to -22°C
- Cooling System: Fan-Forced cooling
- Controller: Dixell
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of 2/1 gastronorm-compatible shelves
- Self-closing lockable doors with heavy-duty magnetic door seals
- 60mm HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User-friendly Digital Controls
- Split door design for rapid recovery and energy-saving
- Integrated door handle for easy cleaning
- The shelf and shelf support are designed to accommodate a 2 x 1/1 GN pan
- EBM-PAPST evaporator and condenser fans
- Heavy-duty castors with front-wheel brakes
- Weight loading per shelf: 40kg
- Refrigerant: R290
- Dimensions (Internal): 624mm W x 702mm D x 1401mm H
- 1/2 split door system can lower yearly running costs by up to 30%

Â

Key Features

- Gross Volume: 650L
- Net Volume: 465L
- Max Ambient Temperature: 43 °C, 60%RH
- Temperature Range: -18 to -22 °C
- Cooling System: Fan-Forced cooling
- Controller: Dixell
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of 2/1 gastronorm-compatible shelves
- Self-closing lockable doors with heavy-duty magnetic door seals
- 60mm HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User-friendly Digital Controls
- Split door design for rapid recovery and energy-saving
- Integrated door handle for easy cleaning
- The shelf and shelf support are designed to accommodate a 2 x 1/1 GN pan
- EBM-PAPST evaporator and condenser fans
- Heavy-duty castors with front-wheel brakes
- Weight loading per shelf: 40kg
- Refrigerant: R290
- Dimensions (Internal): 624mm W x 702mm D x 1401mm H
- 1/2 split door system can lower yearly running costs by up to 30%

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration within 14 Days of Invoice

Your Shipping Specifications

Product Condition	New
Doors	2
Door Type	Hinged Doors
Body	Stainless Steel
Gross Volume	650L
Net Volume	465L
Max Ambient Temperature	43 , 60%RH
Temperature Range	-18 to -22 ° C
Total Energy Consumption	6.81 kWh/24h
Lids	2
Form Factor	Upright
Lid Material	Solid
Net Weight (Kg)	126
Width (mm)	740
Depth (mm)	830
Height (mm)	2000
Packing Width (mm)	765
Packing Depth (mm)	855
Packing Height (mm)	2070
Power	240V, 495W/10A
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice