



FED-X S/S Two Full Glass Door Upright Fridge - XURC1410G2V

Quick Overview

- Gross Volume: 1410L
- Net Volume: 960L
- Max Ambient Temperature: 38°C, 60%RH
- Temperature Range: +2 to +8°C
- Cooling System: Fan-forced cooling
- Controller: Dixell
- Refrigerant: R290
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy-duty magnetic door seals
- Internal LED lighting
- HFCs and CFCs free foam body insulation
- User-friendly Digital controls and internal lighting
- Shelf and shelf support are designed to accommodate 2 x 1/1 GN pan
- Heavy-duty evaporator and condenser fans
- Heavy-duty castors with front-wheel brakes
- Weight loading per shelf: 40kg
- Dimensions (Internal): 1364mm W x 702mm D x 1401mm H

Description

FED-X S/S Two Full Glass Door Upright Fridge - XURC1410G2V

Key Features

- Gross Volume: 1410L
- Net Volume: 960L
- Max Ambient Temperature: 38°C, 60%RH

- Temperature Range: +2 to +8 ° C
- Cooling System: Fan-forced cooling
- Controller: Dixell
- Refrigerant: R290
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy-duty magnetic door seals
- Internal LED lighting
- HFCs and CFCs free foam body insulation
- User-friendly Digital controls and internal lighting
- Shelf and shelf support are designed to accommodate 2 x 1/1 GN pan
- Heavy-duty evaporator and condenser fans
- Heavy-duty castors with front-wheel brakes
- Weight loading per shelf: 40kg
- Dimensions (Internal): 1364mm W x 702mm D x 1401mm H

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration within 14 Days of Invoice

Your Shipping Specifications

Product Condition	New
Doors	2
Door Type	Hinged Doors
Body	Stainless Steel
Gross Volume	1410L
Net Volume	960L
Max Ambient Temperature	38 , 60%RH
Temperature Range	+2 to +8 ° C
Total Energy Consumption	4.356 kWh/24h
Net Weight (Kg)	208
Width (mm)	1480
Depth (mm)	810+50
Height (mm)	2000
Packing Width (mm)	1505
Packing Depth (mm)	855
Packing Height (mm)	2070
Power	240V; 50V; 10A; 415W
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice