



## Description

## FED-X S/S Two half Door Upright Freezer - XURF600S1V

### Quick Overview

- Gross Volume: 618L
- Net Volume: 388L
- Max Ambient Temperature: 43°C; 60%RH
- Temperature Range: -18 to -22°C
- Cooling System: Fan-Forced cooling
- Controller: Dixell
- Refrigerant: R290
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy-duty magnetic door seals
- HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User-friendly Digital Controls
- Split door design for rapid recovery and energy-saving
- Integrated door handle for easy cleaning
- Shelf and shelf support are designed to accommodate 2 x 1/1 GN pan
- Heavy-duty evaporator and condenser fans
- Heavy-duty castors with front-wheel brakes
- Weight loading per shelf: 40kg
- Dimensions (Internal): 564mm W x 682mm D x 1394mm H
- 1/2 split door system can lower yearly running costs by up to 30%

## Key Features

- Gross Volume: 618L
- Net Volume: 388L
- Max Ambient Temperature: 43 °C, 60%RH
- Temperature Range: -18 to -22 °C
- Cooling System: Fan-Forced cooling
- Controller: Dixell
- Refrigerant: R290
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy-duty magnetic door seals
- HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User-friendly Digital Controls
- Split door design for rapid recovery and energy-saving
- Integrated door handle for easy cleaning
- Shelf and shelf support are designed to accommodate 2 x 1/1 GN pan
- Heavy-duty evaporator and condenser fans
- Heavy-duty castors with front-wheel brakes
- Weight loading per shelf: 40kg
- Dimensions (Internal): 564mm W x 682mm D x 1394mm H
- 1/2 split door system can lower yearly running costs by up to 30%

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration within 14 Days of Invoice

## Your Shipping Specifications

Product Condition	New
Doors	2
Door Type	Hinged Doors
Body	Stainless Steel
Gross Volume	618L
Net Volume	388L
Max Ambient Temperature	43 , 60%RH
Temperature Range	-18 to -22 ° C
Total Energy Consumption	7.26 kWh/24h
Lids	2
Form Factor	Upright
Lid Material	Solid
Net Weight (Kg)	117
Width (mm)	680
Depth (mm)	840
Height (mm)	2000
Packing Width (mm)	710
Packing Depth (mm)	855
Packing Height (mm)	2150
Power	240V, 465W/10A
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice