



\*\* Supplied with 150mm adjustable legs

## TECHNICAL DATA

Cycle times (*)	75 / 120 sec. and special cycles
Water consumption	1.9 l/rack
Tank capacity	8 l
Tank heating	0.8kW
Power supply	240/50/1 (415/50/3N)
Booster loading	
Standard	2.8kW (Interlocked)
Alternative	4.2kW
Total loading	
Standard	3.2kW   15amp
Alternative	5.4kW   15amp (3ph)
Wash pump	0.6 kW
Rack size	400 x 400 mm
Loading height	315 mm
Noise level	62 dB (A)
Weight (gross / net)	64 / 58 kg

## CONNECTIONS

① Drain hose	2,000 mm   ID20/OD25
② Supply hose	2,000 mm   R 3/4"
Flow pressure	0.5 (0.8 with softener) - 10 bar
Max. supply water temperature	60 °C
Required flow rate	5 l/min
③ Power cord	2,000 mm
Supply hose for	
④ Detergent	2,500 mm
⑤ Rinse aid	2,500 mm

\* Thermostop guarantees required rinse temperatures. The actual cycle time extends accordingly if the machine is connected to cold water or run on single phase

\* For machine protection water hardness should not exceed 3°dH. If higher we recommend using a water softener - ask your Hobart representative for assistance.

## MADE IN GERMANY

## PRODUCT ADVANTAGES

- **Compact glasswasher**, ideal for narrow places in restaurants, bars, pubs, bistros, etc. Ideal for use with integrable reverse osmosis system HYDROLINE PURE RO-I for undercounter installation. Total height incl. RO-I 400: 820 mm
- **VISIOTRONIC Control**: ensures a simple and intuitive operating with a single button. When the display is activated by a proximity sensor, all the necessary information appears in the large display, in clear text or in the form of symbols
- **Rinsing 1.9 l**: water consumption per cycle of only 1.9 l which results in a reduction of water, chemicals and energy consumption of 35 %
- **CLIP-IN Wash and Rinse Arms**: both the wash and rinse arms can be lifted out of the wash chamber and replaced with one hand and without any tools
- **Compact under counter glass washer**  
Nominal capacity up to 30 racks/h 480 glasses / h.
- 5 automatic cycles: short, standard, intensive, hygiene, cold rinse only (no hot)
- Heat and noise insulated
- Self cleaning program
- Multi setting - 415V standard or 240V
- **Intelligent data documentation**: automatic recording of important operational data and consumptions and indication on the display
- **USB-interface**: comfortable download of operational data in form of a protocol via USB
- **Filter position sensor**: prevents operation without tank strainer
- **GENIUS-X<sup>2</sup> Fine Filter System**: advanced filter system with pre-wash function reduces detergent consumption up to 35%
- **AQUA-PLUS Rinsing**: intensive rinse cycle to wash glasses with critical design with raised fresh-water amount
- **HOT & COLD Rinsing**: the rinse can be switched from hot to cold water so that you get cooler glasses without any loss of time
- **Hygiene Programme**: for removal of calcium carbonate and other deposits from wash chamber
- Ready to install - equipped with: fill/drain hoses, electrical cable (240V), detergent & rinse aid dispensers, rinse pump, drain pump, back flow preventer (Watermark approved)
- Tank, frame, rinse arms & panels are 1.4301 stainless steel
- 1 - 4 row 386x386mm glass rack
- ACCEPTS 17x14" RACKS—stainless steel grid insert to accept all racks up to 386x386mm

## DIMENSIONAL DRAWING

