

Hot Wash Reel and Trigger Valve

Product Code:

T-TWHWR1215SG - Hot Wash Reel and Trigger Valve

T-TWHWR1215 - Hot Wash Reel Only

T- TWSGV65SVL - Trigger Valve Only

The 3monkeez® range of tapware is perfectly suited for commercial kitchens, schools, canteens, bars, cafes, food processing facilities or any area that commercial tapware is required. The range includes Pre Rinse Units, Mixers, Hot Wash Reels, Sensor Taps, Bubblers, Pillar and Bib Taps and more.





Features and Benefits:

- Reel Hose is 12mm Internal Diameter x 15m Length
- Reel has 1/2" FI BSP Inlet
- Reel has 1/2" MI BSP Outlet

• Trigger Valve has 1/2" FI BSP Inlet
Watermarked
T-TWHWR1215:
Maximum Operating Temperature - 85 Degrees Celcius
Maximum Working Pressure - 1600kPa at 30 degrees celcius
Maximum Working Pressure - 1000kPa at 85 degrees celcius
T-TWSGV65SVL:
Maximum Operating Temperature - 95 Degrees Celcius
Maximum Working Pressure - 550kPa
T-TWHWR1215SG:
Maximum Operating Temperature - 85 Degrees Celcius

Maximum Working Pressure - 550kPa