

GKpv 6570

ProfiLine



| | |
|---|---------------------------------|
| Gross/net capacity | 597/465 litre |
| Ext. dimensions in mm (w/d/h) | 700/830/2120 |
| Int. dimensions in mm (w/d/h) | 510/650/1550 |
| Energy consumption in 365 days / 24 hours (kWh) | 405 / 1.11 |
| Ambient temperature range | +10°C to +43°C ¹ |
| Refrigerant | R 290 |
| Connection Rating | 2.0 A |
| Voltage | 220-240 V~ |
| Cooling system | forced-air |
| Defrosting | automatic |
| Temperature range | +1°C to +15°C |
| Gastronorm | 650 x 530 mm |
| Housing material/colour | stainless steel/stainless steel |
| Door material | Stainless steel |
| Liner Material | 304-grade stainless steel |
| Type of Control | electronic controller |
| Temperature display | external digital |
| Fault: warning signal | visual and audible |
| Interface | RS 485 optional |
| Adjustable Shelving | 4 |
| Height of adjustable legs | 120 - 170 mm |
| Lock | fitted |
| Self-closing door | yes |
| Door hinges | right, reversible |
| Insulation | 83-60 mm |
| Gross/net weight | 133/117 kg |
| EAN-Nr. | 9005382195536 |

¹ Indicates the ambient temperature at which the device can be operated safely.



LIEBHERR