YC 750mm Yum Cha Steamer





Technical Specifications for YC-1



ASIAN SERIES

- Powerful Mongolian burner for maximum steam output
- 7 hole steamer plate suitable for bamboo baskets
- Water cooling system to preserve unit longevity
- Cast iron ring with Fiberfrax insulation
- Durable Zinc-aluminum Alloy burner handle
- Laundry arm controlled by quarter turn lever
- 304 grade high quality stainless steel panels
- 15 month 'Platinum Warranty'
- Easy to clean and service





<u>Steamer</u>

- 140mj 32 jet mongolian burner with piezo, pilot & FFD
- Water deck cooling system
- 1.5mm 304 stainless steel 7 hole steamer plate
- 1.2mm 304 stainless steel pot & skirting
- Water deck cooling system
- Quarter turn water control lever
- Rear laundry arm with front panel controls
- Front gutter design for easier cleaning
- Zinc-aluminium Alloy burner handle

Overall Construction

- Welded steel frame construction
- Cast iron ring with Fiberfrax Durablanket insulation
- Double flanged watertight gasket seal
- Rear flue system to aid combustion
- 1.2mm 304 stainless steel deck, front cover & splashback
- 0.7mm 304 stainless steel side panels and undertrays
- 10mm ceramic insulation board under top deck
- 25mm Fibertex Rockwool insulation in fron & side panels
- 38mm stainless steel tube legs with adjustable feet

Dimensions

- 750mm x 950mm x 1300mm H
- Working height 800mm
- Weight 112kg
- Packed dimensions 830mm x 1025mm x 1460mm H
- Packed weight 142kg

Connections

- Gas 3/4" BSP male
- Gas 100mm from left, 50mm from rear, 300mm from floor (regulator connected inside front cover)
- Supplied with gas regulator (specify Nat or LP on order)
- Water inlet 1/2" copper tube
- Water 100mm from right, 100 mm from rear, 200mm floor
- Drain 2" BSP male
- Drain 100mm from right, 130mm from front, 650mm floor

Cleaning & Servicing

• Easy access to all parts & components from front

Options/Accessories

- 4 piece 304 stainless steel steam rack set
- Joining caps & strips
- Rear castors
- Extended warranty



Luus Industries Pty Ltd | (03) 9240 6822 | sales@luus.com.au | www.luus.com.au







