FFFCvg 6501 Perfection (544)

Freestanding freezer with NoFrost

Everything you could need to meet the highest demands and requirements of your everyday professional life. They are made of stainless steel, are available with either solid or glass doors, and feature optimal lighting. Their cooling range spans from -2 +15 °C; their freezers include both the SmartFrost and the NoFrost functions.

ITEM #	
MODEL#	
NAME#	
SIS#	
ΛΙΛ #	



Your benefits

- Low total operating costs from the compressor to the seal, to the lighting and electronics, Liebherr appliances fully utilise the savings potential of every component.
- In the event of an uncontrolled temperature rise, the interior light of the appliance starts flashing.
- The plastic-coated grid shelves allow versatile use of the interior and can support up to 60 kg.
- The self-closing door closes automatically from a 60° opening angle, preventing loss of cold air and ensuring ideal storage conditions for your goods.
- In commercial design, the deep drawn inner liner made of food-safe polystyrene is odour-neutral, very robust, and longlasting.





NoFrost technology

With professional appliances from Liebherr, defrosting is no longer necessary. Any moisture that occurs is combated by the fanassisted cooling, and cyclical defrosting phases remove even the last moisture particles out of the interior. For convenient, safe, and ice-free storage.



Replaceable door seal

Save time and money: Liebherr's plug-in door seals can be easily replaced. If a seal is damaged, you can replace it yourself without any tools



LightAlarm

In case of an uncontrolled temperature rise, if a door has been left open or there were any other problems, the interior light of the appliance will start flashing. In the case of glass-door appliances, this quickly reveals when action is needed. In the case of solid-door appliances, the flashing interior warns to close the door immediately in order to preserve the storage quality.



Suitable for Euronorm boxes (only gastronomy freezer)

Open the door, insert the container, nice and tidy: Professional appliances for the catering industry is specially designed to meet the needs of kitchens and bakeries and is therefore suitable for use with Euronorm boxes.





FFFCvg 6501 Perfection (544)

Freestanding freezer with NoFrost

Specifications

Gross/net capacity	544/3781
Ext. dimensions in mm (w/d/h)	747/769/1993
Int. dimensions in mm (w/d/h)	603/510/1318
Climate class (energy directive)	5
Temperature class (energy directive)	Ll
Climate class (safety standard)	5
Ambient temperature range	+10 °C to +40 °C
Refrigerant	R 290
Connection Rating	2.0 A
Frequency / voltage	50 Hz / 220-240 V~
Cooling system	forced-air
Defrosting	automatic
Temperature range	-9 °C to -26 °C
Housing material/colour	stainless steel
Door material	steel
Liner Material	moulded polystyrol (silver)
Type of Control	monochrome display, touch buttons
Temperature display	external digital
Interior light	LED
Alarm in case of malfunction	visual and audible
Connectivity type	SmartModule
Interface	WLAN/LAN (optional)
Adjustable Shelving	5
Shelf material	wire shelves plastic-coated
Shelf loading	60 kg
Handle	aluminium handle
Castors	2 fixed rear and 2 swivel front castors
Type of lock	mechanical
Self-closing door	yes
Door hinges	right, reversible on site
Defrost water drain	yes
Gross/net weight	109/101 kg
EAN-Nr.	9005382277454

Liebherr reserves the right to make modifications to the products without prior notice. All information are correct at the time of printing. 2024.06.24

The overview represents an excerpt of the most important appliance features. All other features of the appliance and further information are available at:





FFFCvg 6501 Perfection (544)

Technical drawing





