

Three Glass Door Top Mount Upright Fridge

Series: ActiveCore

Dimensions: 1705 mm (W) × 745 mm (D) × 2200 mm (H)

Capacity: 1399 L

Project: _____

Item #: _____



A high-efficiency, top-mounted, heavy duty, 3-door display fridge suitable for front and back-of-house applications including restaurants, cafés, clubs, pubs, bars, quick service restaurants, and more. Made from powder-coated, galvanised steel with colour options, the cabinet comes complete with five plastic-coated wire shelves per door, easily adjustable via SKOPE's unique ezi-clip and numbered shelf supports. The "frameless" glass doors provide maximum product viewing and are designed for condensation protection in most environments via the double-glazed, argon-filled, low-e, insulated panels. The high impact built-in LED lights can be timed to turn on and off according to your opening times via the free SKOPE-connect smartphone app. A non-illuminated sign panel is included, with space to display your own branding. With M1 compliance, the fridge is engineered to store food and drinks at a standard 1°C to 4°C (adjustable up to 15°C). It is certified under GEMS to the mandatory climate class 3 and is fully tested to operate in ambient environments of up to 40°C (climate class 5). The fridge uses R290 natural refrigerant for ultra-low energy consumption, low heat discharge, and low noise output. The top-mounted, fully removable, modular refrigeration cartridge can be easily removed in line with best practice for safe servicing of flammable refrigerants. With the same cartridge being used in both top and bottom-mounted fridges, you achieve the fastest possible servicing times with minimal business disruption. The fridge includes a smart controller that connects to the free SKOPE-connect app, enabling you to set temperatures and alerts, monitor temperatures and energy, and more. The fridge is certified to all Australian and New Zealand refrigeration and electrical safety standards.



Warranty



ActiveCore Technology




Natural Refrigerant



GEMS



SKOPE-connect



Cabinet

Range	TME		
Finish	Powder-coated galvanised steel		
Insulation	Type	PU foam	
	Thickness (mm)	50	
	Blowing Agent	Cyclo-iso pentane (C5H10/C5H12)	
Doors	Type	Glass swing door (double-glazed, single low-e, argon-filled, toughened, safety glass), tab-locking	
	Opening Size	Height (mm)	1570
		Width (mm)	470
Shelving	10 × outer shelf (500W × 470D), 5 × inner shelf (570W × 470D)		
Lighting	Sign	n.a.	
	Interior*	3 × 1400 mm, 15 W LED	

Dimensions†

	External	Internal	Packed
Width (mm)	1705	1605	1720
Depth (mm)	745	555	780
Height (mm)	2200 (castors)	1570	2205
Weight (kg)	282		289
ANSI Volume (L)	1399		
Footprint (m²)	1.27		

Ventilation (mm)

Top	300	Sides	Not required	Rear	Not required
-----	-----	-------	--------------	------	--------------

Product Loading

Facing	330 ml can	110	660 ml bottle	110
Loading	330 ml can	805	600 ml bottle	630

Dimensional Tolerances

† Allow for dimensional tolerances when installing the cabinet(s).

Linear dimensions	Single cabinet	Multiple cabinets	
		At each joint	At each end wall
Less than 1 metre	±5 mm	±5 mm	+15 mm
More than 1 metre	-5 mm to +10 mm	-5 mm to +10 mm	+15 mm

Performance

Product Temperature Range (°C)*	1 to 5 (adjustable 1 to 15)
Maximum Ambient Temperature (°C)	40
Sound Power Level (dB(A))	61

Greenhouse and Energy Minimum Standards (GEMS)

Star Rating	7
Product Temperature Class	M1 (-1 to 5°C)
Total Energy Consumption	5.87 kWh/24 h
Annual Running Costs	\$643 (@ \$0.30/kWh)

Electrical

Supply	220 to 240 volts a.c., 50 Hz, single phase supply
Cord	2.1 m power cord with 3-pin, 10 amp plug
Current draw (A)	2.1

Refrigeration

Controller	SCS Connect (SKOPE-connect™ compatible)		
System Type	Removable cartridge		
Cartridge Weight (kg)	29		
Refrigerant/Charge	R290/99 g		
Nominal Capacity (W)	547		
Heat Rejection (W)	Average 245	Peak	330
Defrost Type	Automatic, off-cycle		
Drainage	No plumbing required		

* Controllable via SCS Connect.



TME1500N-A
on the SKOPE website