

The Australian owned and designed* Trueheat RC Series of Gas Cooking Equipment has been developed for the restaurant and cafe market with a high quality finish, designed to fulfill the busy demands within a commercial kitchen.

Our team of professionals have designed and engineered the ultimate barbecue by incorporating premium infrared technology. Heavy duty cast iron radiant hoods over powerful gas burners radiate heat to the grates are reversible for angled or flat operation.

100% Flame failure controls included as standard. Piezo ignition included as standard.

DIMENSIONS & WEIGHT

External Dimension: 600W x 803D x 455H mm

Net Weight: 69kg

Working height : 910mm (+/-15mm with stand)

Combustible wall clearance: Side: 250mm, Rear: 150mm

TECHNICAL DATA

Gas Type: Natural or Propane

| | | |
|----------------------|-------------|-------------|
| Total Output(MJ/hr): | Natural Gas | Propane Gas |
| | 66 | 60 |

| | | | |
|-------------------------|-------------|-------------|---------------|
| Burner Ratings (MJ/hr): | Natural Gas | Propane Gas | Ignition Type |
| Barbecue per 300mm: | 16.5 | 15 | Piezo |

Gas Connection: 3/4" Female

AGA approval number: AGA 6868 G

SHIPPING DATA

Shipping Weight: 89.5kg

Shipping Dimensions: 680W x 900D x 640H mm

OPTIONAL ACCESSORIES

| Part Number: | Description: |
|---------------|--|
| RCSTD6 | 600mm Stand complete with shelf |
| B05002 | Adjustable leg for RCT countertop mounting |
| S35086 | 4 legs, 2 brackets, 6 screws (complete set for table top mounting) |
| MS-CSTRB | Castor with brake to suit both 600mm and 900mm |
| MS-CSTR | Castor without brake to suit both 600mm and 900mm |
| 432018-900HK | 900mm 3/4 flexible gas hose with quick connect fittings and restraint |
| 432018-1200HK | 1200mm 3/4 flexible gas hose with quick connect fittings and restraint |

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Note: Stands fitted with castors will need to be cut down by 120-150mm.

*manufactured in China



Stand sold separately

