

The Australian owned and designed* Trueheat RC Series of Gas Cooking Equipment has been developed for the restaurant and cafe market with a high quality finish, designed to fulfill the busy demands within a commercial kitchen.

Powerful 24MJ/hr open burners with individual standing pilots included. 100% Flame failure controls included as standard. Matt finish premium look cast iron trivets radiant heat and design makes it easy to move pots around the surface.

Static oven with two oven racks fit to removable vertical rack guides which provide 3 rack heights. Oven racks are fabricated from 304 stainless steel. Interior oven panels are coated with black vitreous enamel for ease of cleaning.

DIMENSIONS & WEIGHT

External Dimension: 900W x 830D x 1135H mm

Net Weight: 177kg

Working height : 910mm

Oven Interior : 660W x 540D x 320H mm

Combustible wall clearance: Side: 150mm, Rear: 150mm

TECHNICAL DATA

Gas Type: Natural or Propane

| | | |
|----------------------|-------------|-------------|
| Total Output(MJ/hr): | Natural Gas | Propane Gas |
| | 180 | 177 |

| | | | |
|-------------------------|-------------|-------------|---------------|
| Burner Ratings (MJ/hr): | Natural Gas | Propane Gas | Ignition Type |
| Open Burner (MJ/hr): | 24 | 24 | Manual |
| Oven (MJ/hr): | 36 | 33 | Piezo |

Gas Connection: ¾" Female

AGA approval number: AGA 6652 G

SHIPPING DATA

Shipping Weight: 205kg

Shipping Dimensions: 980W x 900D x 1210H mm

OPTIONAL ACCESSORIES

| Part Number: | Description: |
|---------------|--|
| GF-CSTRB | Front Castor Swivel with brake suits RCR models only |
| GF-CSTR | Rear Castor without brake suits RCR models only |
| 432018-900HK | 900mm ¾ flexible gas hose with quick connect fittings and restraint |
| 432018-1200HK | 1200mm ¾ flexible gas hose with quick connect fittings and restraint |

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

*manufactured in China

