

### Product Information:

- High performance undercounter glasswasher
- **E-Management:** intuitive and advanced electronic interface
- Four wash cycles 90/120/180 seconds, and 9 minute deep clean
- Green standby function that reduces energy consumption when idle
- Low water consumption of 2.0 litres per cycle, minimising water, energy and detergent use
- Partial double skin cabinet, and double skin door
- Pressed wash tank with rounded corners, for increased hygiene
- Upper and lower stainless steel wash and rinse arms
- Robust upper tank scrap filters in stainless steel
- Rack support suits the use of multiple glass basket sizes: 400x400mm, 435x355mm and 355x355mm
- Automatic drain pump with self-cleaning function
- Soft start wash pump
- Built in thermostop, ensures correct rinse temperatures
- Built in detergent and rinse-aid injection
- **18-months parts and labour warranty**

### Included Accessories:

- 2 x glass baskets, 400x400mm
- 1 x saucer insert
- 1 x cutlery insert
- 1 x water inlet hose, length 1.5m
- 1 x drain hose, length 2.0m
- 4 x 95-150mm adjustable legs (interchangeable)
- Adjustable front feet and rear rollers

### Optional Accessories:

- Stand with basket storage under
- Additional baskets

### Specifications:

|                                 |   |
|---------------------------------|---|
| <b>Model</b>                    | AF40.30ELS                                |
| <b>W x D x H (mm)</b>           | 455 x 596 x 700                           |
| <b>Weight</b>                   | 40kg                                      |
| <b>Packed Dimensions (mm)</b>   | 540 x 630 x 850                           |
| <b>Packed Weight</b>            | 44kg                                      |
| <b>Total Connected Load</b>     | 3.03kW                                    |
| <b>Electrical Connection</b>    | 230VAC / 50Hz<br>(15A plug & lead fitted) |
| <b>Water Quantity Per Cycle</b> | 2.0 Litres per cycle                      |
| <b>Water Connection</b>         | 1.5m Hose / 3/4" BSP                      |
| <b>Water Inlet Pressure</b>     | 200 - 500KPA                              |
| <b>Tempered water supply</b>    | 10°C - 60°C                               |
| <b>Waste Connection</b>         | 2m Hose / ø20.5mm                         |

### Legend:

- A Electrical Connection
- B Water Connection
- C Drain Connection
- D Detergent Line
- E Rinse-Aid Line

