

## Wash Basin Knee Operated - Type 1

### Model: SPPL.WB.KO1.xxx.yy


SPPL = Stoddart Plumbing Product  
 WB = Wash Basin  
 KO1 = Knee operated, without lower plumbing shroud  
 xxx = 300 = 300mm splashback  
 yy = TV = Tempering valve  
 = TMVE = Thermostatic mixing valve

eg.: for specification and ordering quote



Code: SPPL.WB.KO1.300.TV

### Features and Benefits:


- Hygienic hands free use with knee operated front panel
- Pressing the front panel activates the timed flow of water from the spout
- Replacement valves for the timed flow valve are available as a spare part
- This basin when fitted with a tempering valve, complies with AS4674 for fit out of food premises
- Water is supplied through an aerated, high rise spout for easy access and minimal splash
- Spout is WELS rated spout for controlled flow to 7.5 litres per minute
- Easy-mount single piece stainless steel wall bracket has multiple fixing holes for quick installation by plumber
- Optional 300mm splashback is available, eliminating the need for a tiled splashback



Plan View



Front View



End View

### Specifications:

- Construction:** 304 grade stainless steel construction, wand operated valve and spout are pre-plumbed.
- Water Connection:** 15mm, 1/2" BSP. For addition of optional TV or TMVE, hot and cold supplies are required. Component claimed temperature control;
- Thermostatic Mixing Valve = +/- 2 deg C
  - Tempering Valve = +/- 3 deg C
- Additional water strainer/filter to protect valves from water-borne dirt and scale is fitted as standard.
- Waste Connection:** 40mm PVC waste supplied (Trap by others)
- Unit Fixing:** Unit is supplied with wall mounting bracket with 10mm fixing holes. Optional TV or TMVE is supplied as a loose kit part for plumber to install in compliance with regulations. Optional splashback supplied loose, fix to wall with double sided tape and silicon around edges to seal.
- Fixing Height:** The unit should be mounted at 800 – 830mm above finished floor level for disabled user access.

Model No.	L x D x H (mm)
SPPL.WB.KO1.xxx.yy	500 x 420 x 160 (326 with spout)



Due to continuous product research and development, the information contained herein is subject to change without notice.

Revision: G - 11/06/2021

www.stoddart.com.au  
 www.stoddart.co.nz



Proudly Manufactured in Australia