



SUF1000 TROPICAL Thermaster 4 x Half door SS Freezer

Quick Overview

- Gross Volume: 1000L
- Net Volume: 689L
- Temperature Range: -22 to -18° C
- Aspera Compressors & German Pabst Fans
- Dixell Digital Temp. Controller & Read-Out
- 4 Levels Of Shelving Plus Floor
- Fan-Forced Evaporator Cooling
- Auto Defrost
- Self-Evaporating Drainage
- Insulation Is Cfc & Hcfc Free
- Self-Closing Doors With Locks
- Internal Corners Are Rounded For Hygiene & Easy Cleaning
- Stainless Steel Exterior & Interior
- Castors
- Gal Metal Back

Description

SUF1000 Tropical Thermaster 4 x ½ Door SS Freezer

For the freezer that has it all! The SUF1000 boasts an impressive array of features, all coming packaged in a huge four-door, heavy-duty unit.

This roomy fridge can fit an impressive 1000 litres, which provides your restaurant, café, supermarket, service station or takeaway shop plenty of space to place food, beverages, ingredients and stock for cooling or freezing.

This broad, behemoth of a fridge comes packed with energy-efficient compressors for function, a Dixell digital temp controller, four levels of shelving, fan-forced cooling, castors, and self-drainage.

The SUF1000 is built and sent from Temperature Thermaster, which is one of the most renowned catering equipment brands when it comes to quality fridges and freezers.

Key Features

- Gross Volume: 1000L
- Net Volume: 689L
- Temperature Range: -22 to -18 ° C
- Aspera Compressors & German Ebm-Pabst Fans
- Dixell Digital Temp. Controller & Read-Out
- 4 Levels Of Shelving Plus Floor
- Fan-Forced Evaporator Cooling
- Auto Defrost
- Self-Evaporating Drainage
- Insulation Is Cfc & Hcfc Free
- Self-Closing Doors With Locks
- Internal Corners Are Rounded For Hygiene & Easy Cleaning
- Stainless Steel Exterior & Interior
- Castors
- Gal Metal Back

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration

Your Shipping Specifications

Product Condition	New
Doors	4
Door Type	Hinged Doors
Body	Stainless Steel
Gross Volume	1000L
Net Volume	689L
Temperature Range	-22 to -18 ° C
Total Energy Consumption	11.91 kWh/24h
Lids	4
Form Factor	Upright
Lid Material	Solid
Net Weight (Kg)	147
Width (mm)	1220
Depth (mm)	760
Height (mm)	1980
Packing Width (mm)	840
Packing Depth (mm)	1290
Packing Height (mm)	2030
Power	240V; 895W
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice