





TD-3NE TECNODOM Nerino 3x GN 2/3 Tray Convection Oven

Quick Overview

- Temperature Range: 30~280Â ° C
- 304 grade Stainless Steel both inside and out, with external Scotch Bright finishing
- Rounded corners in the cooking chamber for easy cleaning
- · Internal global diffusion ventilation system
- · Stainless Steel tubular handle
- Analogue timer and temperature controls (60 minutes / 280Â ° C) - also has infinite time setting.
- Internal fluro lighting.
- Distance between trays: 80mm

Description

TECNODOM Nerino 3x GN 2/3 Tray Convection Oven TD-3NE

ULTRA COMPACT GN 2/3 STANDARD CONVECTION OVEN

GN 2/3 standard makes NERINO an essential machine perfect for small activities wanting to propose snacks, pizza, croissants, and

hot plates. Made completely in stainless steel, it is designed and realized to be placed in small environments. Its compact dimensions

allow it to be placed on narrow shelves. It is fitted with a reliable and precise mechanical control panel.

Convection ovens are designed to save space and to be positioned anywhere, maintaining the capacity.

1

Products studied to grant the best operations and performances for the modern catering.		
Tecnodom introduces the selection of the NERONE range of ovens: excellence dedicated to the cooking systems. The technological, planning, and design skills used by Tecnodom are synthesized in the NERONE range of ovens. The company, thus, offers products that are in step with the needs of the market and that can combine essentiality and simplicity in cleaning and maintenance.		
Key Features		
 Temperature Range: 30-280 ° C 304-grade Stainless Steel both inside and out, with external Scotch Bright finishing Rounded corners in the cooking chamber for easy cleaning Internal global diffusion ventilation system Stainless Steel tubular handle Analogue timer and temperature controls (60 minutes / 280 ° C) - also has infinite time setting. Internal fluro lighting. Cold glass door with removable internal glass (low emissivity) Removable anti-tipping support guides Interlocking door gasket CE Approved Distance between trays: 80mm 		
1 Year Parts and Labour Warranty		

Your Shipping Specifications

Product Condition	New
Knobs	2 knobs
Net Weight (Kg)	25
Width (mm)	600
Depth (mm)	520
Height (mm)	390
Packing Width (mm)	560
Packing Depth (mm)	690
Packing Height (mm)	540
Power	240V; 2.8KW; 15A outlet
Warranty	1 Year Parts and Labour