



MASONRY FLEXIBLE ANCHORS

25 Park Drive, Dandenong, Vic 3175 Phone (03) 9768 3111 Email info@brunswicksales.com.au www.brunswicksales.com.au





RIGID WALL-TIES

SKU: MFA ANCHOR-TIES

This is an improved tie especially for use with larger than normal cavity widths. The use of such a tie is prescribed for cavities of 90mm or more in width. The new design is safer and more convenient to handle than old "fish-tail" wall tie.


Available in Galvanised Steel Z600 or Stainless Steel 3.0mm thickness


Lengths: 200mm, 250mm, 300mm, 350mm, 400mm, 450mm

STRENGTH SUMMARY (BDRI) Test Cert. BO 1151)

Characteristic Strength-Compression = 1.88kN*, Characteristic Strength-Tension = 2.87kN*

*Tested with a cavity





RIGID WALL-TIES

SKU: MFA POSI-TIE

This is a heavy duty corrugated tie for conventional cavity wall construction. Its use is recommended for high wind and cyclone areas.

Available in Galvanised Steel Z600 or 316 Stainless Steel 1.0mm thickness Lengths: 200mm, 250mm, 300mm

STRENGTH SUMMARY (BDRI) Test Cert. 12.1.76)

Characteristic Strength-Compression = 2.12kN, Characteristic Strength-Tension = 1.76kN